PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

Procurement of GOODS

Procurement of
IT Equipment and Peripherals
For Various Offices/Colleges
(Re-bidding)

Batangas State University

REPUBLIC OF THE PHILIPPINES

BATANGAS STATEUNIVERSITY

BATANGASCITY

SECTION I INVITATION TO BID

PROCUREMENT OF IT EQUIPMENT AND PERIPHERALS FOR VARIOUS OFFICES/COLLEGES (RE-BIDDING)

- 1. The Batangas State University, intends to apply the sum of **One Million Four Hundred Eighty Thousand Two Hundred Fifty Pesos Only (Php 1,480,250.00)** being the Approved Budget for the Contract (ABC) to payments under the contract for **Procurement of IT Equipment and Peripherals for Various Offices/Colleges (Re-bidding).** Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The Batangas State University now invites bids for **Procurement of IT Equipment and Peripherals for Various Offices/Colleges (Re-bidding).**Bidders should have completed, within three (3) years from the date of submission and receipt of bids, a contract similar to the Project, equivalent to at least fifty percent (50%) of the ABC. The description of an eligible bidder is contained in the Bidding Documents, particularly, in **Section II Instruction to Bidders.**
- 3. Bidding will be conducted through open competitive bidding procedures using non-discretionary pass/fail criterion as specified in the Revised Implementing Rules and Regulations (IRR) of Republic Act 9184 (RA 9184).
- 4. Interested bidders may obtain further information from Batangas State University and inspect the Bidding Documents at the BAC Office, Ground Floor, ITE Building from 8:00 AM to 5:00 PM, or download it from PhilGEPS or from Batangas State University Website (http://www.batstate-u.edu.ph/) provided the bidders shall pay the fee for the bidding documents upon submission of their bids. A complete set of Bidding Documents may be acquired by interested Bidders from the above mentioned address starting April 1, 2016 until the deadline for submission and receipt of bids and upon submission of letter of intent and payment of a nonrefundable fee for the Bidding Documents in the amount of Two Thousand Pesos Only (Php 2,000.00). Only those who have purchased the Bidding Documents shall be allowed to participate in the pre-bid conference and raise or submit queries or clarifications.
- 5. The Batangas State University will hold a Pre-Bid Conference on **April 8, 2016, 2016, 2:00 PM, BAC Office, Ground Floor,CITE Building GPB Campus I** which shall beopen only to all interested parties who have purchased the Bidding Documents.

- 6. Bids must be delivered to the above mentioned address on **April 20, 2016, 1:00 2:00 PM. Opening of bids will be at 2:00 PM.** All bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 18. Bids will be opened in the presence of the bidders' representatives who choose to attend at the address below. Late bids shall not be accepted.
- 7. The Batangas State University reserves the right to accept or reject any bid, to annul the bidding process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.

For further information, please refer to:

BAC Office, Ground Floor, CITE Building Batangas State University Main Campus

<u>ATTY. EDGARD E. VALDEZ</u> <u>BAC Chairman</u> Tel. No. 043-980-0385 local 1549

SECTION II INSTRUCTION TO BIDDERS

TABLE OF CONTENTS

A.	GENE	RAL	3
	1.	Scope of Bid	3
	2.	Source of Funds	3
	3.	Corrupt, Fraudulent, Collusive, and Coercive Practices	3
	4.	Conflict of Interest	4
	5.	Eligible Bidders	5
	6.	Bidder's Responsibilities	7
	7.	Origin of Goods	8
	8.	Subcontracts	8
B.	Cont	ENTS OF BIDDING DOCUMENTS	8
	9.	Pre-Bid Conference	8
	10.	Clarification and Amendment of Bidding Documents	9
C.	Preparation of Bids		
	11.	Language of Bid	9
	12.	Documents Comprising the Bid: Eligibility and Technical Components	10
	13.	Documents Comprising the Bid: Financial Component	11
	14.	Alternative Bids	12
	15.	Bid Prices	12
	16.	Bid Currencies	13
	17.	Bid Validity	14
	18.	Bid Security	14
	19.	Format and Signing of Bids	16
	20.	Sealing and Marking of Bids	16
D.	SUBMISSION AND OPENING OF BIDS		
	21.	Deadline for Submission of Bids	17
	22.	Late Bids	17
	23.	Modification and Withdrawal of Bids	17
	24.	Opening and Preliminary Examination of Bids	18
E.	EVAL	UATION AND COMPARISON OF BIDS	19
	25.	Process to be Confidential	19
	26.	Clarification of Bids	19

	27.	Domestic Preference	19
	28.	Detailed Evaluation and Comparison of Bids	20
	29.	Post-Qualification	21
	30.	Reservation Clause	22
F.	Award of Contract		23
	31.	Contract Award	23
	32.	Signing of the Contract	24
	33.	Performance Security	24
	34.	Notice to Proceed	25

A. General

1. Scope of Bid

- 1.1. The procuring entity named in the **BDS** (hereinafter referred to as the "Procuring Entity") wishes to receive bids for supply and delivery of the goods as described in Section VII-Technical Specifications (hereinafter referred to as the "Goods").
- 1.2. The name, identification, and number of lots specific to this bidding are provided in the **BDS**. The contracting strategy and basis of evaluation of lots is described in ITB Clause 28.

2. Source of Funds

The Procuring Entity has a budget or has applied for or received funds from the Funding Source named in the **BDS**, and in the amount indicated in the **BDS**. It intends to apply part of the funds received for the Project, as defined in the **BDS**, to cover eligible payments under the contract.

3. Corrupt, Fraudulent, Collusive, and Coercive Practices

- 3.1. Unless otherwise specified in the <u>BDS</u>, the Procuring Entity as well as the bidders and suppliers shall observe the highest standard of ethics during the procurement and execution of the contract. In pursuance of this policy, the Procuring Entity:
 - (a) defines, for purposes of this provision, the terms set forth below as follows:
 - (i) "corrupt practice" means behavior on the part of officials in the public or private sectors by which they improperly and unlawfully enrich themselves, others, or induce others to do so, by misusing the position in which they are placed, and includes the offering, giving, receiving, or soliciting of anything of value to influence the action of any such official in the procurement process or in contract execution; entering, on behalf of the government, into any contract or transaction manifestly and grossly disadvantageous to the same, whether or not the public officer profited or will profit thereby, and similar acts as provided in RA 3019.
 - (ii) "fraudulent practice" means a misrepresentation of facts in order to influence a procurement process or the execution of a contract to the detriment of the Procuring Entity, and includes collusive practices among Bidders (prior to or after bid submission) designed to establish bid prices at artificial, non-competitive levels and to deprive the Procuring Entity of the benefits of free and open competition.
 - (iii) "collusive practices" means a scheme or arrangement between two or more Bidders, with or without the knowledge of the Procuring Entity, designed to establish bid prices at artificial, non-competitive levels.

- (iv) "coercive practices" means harming or threatening to harm, directly or indirectly, persons, or their property to influence their participation in a procurement process, or affect the execution of a contract;
- (v) "obstructive practice" is
 - deliberately destroying, falsifying, altering or concealing of evidence material to an administrative proceedings or investigation or making false statements to investigators in order to materially impede an administrative proceedings or investigation of the Procuring Entity or any foreign government/foreign or international financing institution into allegations of a corrupt, fraudulent, coercive or collusive practice; and/or threatening, harassing or intimidating any party to prevent it from disclosing its knowledge of matters relevant to the administrative proceedings or investigation or from pursuing such proceedings or investigation; or
 - (bb) acts intended to materially impede the exercise of the inspection and audit rights of the Procuring Entity or any foreign government/foreign or international financing institution herein.
- (b) will reject a proposal for award if it determines that the Bidder recommended for award has engaged in any of the practices mentioned in this Clause for purposes of competing for the contract.
- 3.2. Further, the Procuring Entity will seek to impose the maximum civil, administrative, and/or criminal penalties available under applicable laws on individuals and organizations deemed to be involved in any of the practices mentioned in ITB Clause 3.1(a).
- 3.3. Furthermore, the Funding Source and the Procuring Entity reserve the right to inspect and audit records and accounts of a bidder or supplier in the bidding for and performance of a contract themselves or through independent auditors as reflected in the GCC Clause **Error! Reference source not found.**

4. Conflict of Interest

- 4.1. All Bidders found to have conflicting interests shall be disqualified to participate in the procurement at hand, without prejudice to the imposition of appropriate administrative, civil, and criminal sanctions. A Bidder may be considered to have conflicting interests with another Bidder in any of the events described in paragraphs (a) through (c) below and a general conflict of interest in any of the circumstances set out in paragraphs (d) through (f) below:
 - (a) A Bidder has controlling shareholders in common with another Bidder;
 - (b) A Bidder receives or has received any direct or indirect subsidy from any other Bidder;

- (c) A Bidder has the same legal representative as that of another Bidder for purposes of this bid;
- (d) A Bidder has a relationship, directly or through third parties, that puts them in a position to have access to information about or influence on the bid of another Bidder or influence the decisions of the Procuring Entity regarding this bidding process. This will include a firm or an organization who lends, or temporarily seconds, its personnel to firms or organizations which are engaged in consulting services for the preparation related to procurement for or implementation of the project if the personnel would be involved in any capacity on the same project;
- (e) A Bidder submits more than one bid in this bidding process. However, this does not limit the participation of subcontractors in more than one bid; or
- (f) A Bidder who participated as a consultant in the preparation of the design or technical specifications of the Goods and related services that are the subject of the bid.
- 4.2. In accordance with Section 47 of the IRR of RA 9184, all Bidding Documents shall be accompanied by a sworn affidavit of the Bidder that it is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), members of the Technical Working Group (TWG), members of the BAC Secretariat, the head of the Project Management Office (PMO) or the end-user unit, and the project consultants, by consanguinity or affinity up to the third civil degree. On the part of the Bidder, this Clause shall apply to the following persons:
 - (a) If the Bidder is an individual or a sole proprietorship, to the Bidder himself;
 - (b) If the Bidder is a partnership, to all its officers and members;
 - (c) If the Bidder is a corporation, to all its officers, directors, and controlling stockholders; and
 - (d) If the Bidder is a joint venture (JV), the provisions of items (a), (b), or (c) of this Clause shall correspondingly apply to each of the members of the said JV, as may be appropriate.

Relationship of the nature described above or failure to comply with this Clause will result in the automatic disqualification of a Bidder.

5. Eligible Bidders

- 5.1. Unless otherwise provided in the **BDS**, the following persons shall be eligible to participate in this bidding:
 - (a) Duly licensed Filipino citizens/sole proprietorships;
 - (b) Partnerships duly organized under the laws of the Philippines and of which at least sixty percent (60%) of the interest belongs to citizens of the Philippines;

- (c) Corporations duly organized under the laws of the Philippines, and of which at least sixty percent (60%) of the outstanding capital stock belongs to citizens of the Philippines;
- (d) Cooperatives duly organized under the laws of the Philippines, and of which at least sixty percent (60%) of the interest belongs to citizens of the Philippines; and
- (e) Unless otherwise provided in the <u>BDS</u>, persons/entities forming themselves into a JV, *i.e.*, a group of two (2) or more persons/entities that intend to be jointly and severally responsible or liable for a particular contract: Provided, however, that Filipino ownership or interest of the joint venture concerned shall be at least sixty percent (60%).
- 5.2. Foreign bidders may be eligible to participate when any of the following circumstances exist, as specified in the **BDS**:
 - (a) When a Treaty or International or Executive Agreement as provided in Section 4 of the RA 9184 and its IRR allow foreign bidders to participate;
 - (b) Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
 - (c) When the Goods sought to be procured are not available from local suppliers; or
 - (d) When there is a need to prevent situations that defeat competition or restrain trade.
- 5.3. Government corporate entities may be eligible to participate only if they can establish that they (a) are legally and financially autonomous, (b) operate under commercial law, and (c) are not dependent agencies of the GOP or the Procuring Entity.
- 5.4. Unless otherwise provided in the **BDS**, the Bidder must have completed at least one contract similar to the Project the value of which, adjusted to current prices using the National Statistics Office consumer price index, must be at least equivalent to a percentage of the ABC stated in the **BDS**.
 - For this purpose, contracts similar to the Project shall be those described in the **BDS**, and completed within the relevant period stated in the Invitation to Bid and **ITB** Clause 12.1(a)(iii).
- 5.5. The Bidder must submit a computation of its Net Financial Contracting Capacity (NFCC) or a commitment from a Universal or Commercial Bank to extend a credit line in its favor if awarded the contract for this Project (CLC).

The NFCC, computed using the following formula, must be at least equal to the ABC to be bid:

NFCC = [(Current assets minus current liabilities) (K)] minus the value of all outstanding or uncompleted portions of the projects under ongoing contracts, including awarded contracts yet to be started coinciding with the contract for this Project.

Where:

K = 10 for a contract duration of one year or less, 15 for a contract duration of more than one year up to two years, and 20 for a contract duration of more than two years.

The value of the bidder's current assets and current liabilities shall be based on the data submitted to the BIR, through its Electronic Filing and Payment System.

6. Bidder's Responsibilities

- 6.1. The Bidder or its duly authorized representative shall submit a sworn statement in the form prescribed in Section VIII-Bidding Documents as required in **ITB** Clause 12.1(b)(iii).
- 6.2. The Bidder is responsible for the following:
 - (a) Having taken steps to carefully examine all of the Bidding Documents;
 - (b) Having acknowledged all conditions, local or otherwise, affecting the implementation of the contract;
 - (c) Having made an estimate of the facilities available and needed for the contract to be bid, if any;
 - (d) Having complied with its responsibility to inquire or secure Supplemental/Bid Bulletin(s) as provided under **ITB** Clause 10.3.
 - (e) Ensuring that it is not "blacklisted" or barred from bidding by the GOP or any of its agencies, offices, corporations, or LGUs, including foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the GPPB;
 - (f) Ensuring that each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
 - (g) Authorizing the Head of the Procuring Entity or its duly authorized representative/s to verify all the documents submitted;
 - (h) Ensuring that the signatory is the duly authorized representative of the Bidder, and granted full power and authority to do, execute and perform any and all acts necessary and/or to represent the Bidder in the bidding, with the duly notarized Secretary's Certificate attesting to such fact, if the Bidder is a corporation, partnership, cooperative, or joint venture;
 - (i) Complying with the disclosure provision under Section 47 of RA 9184 in relation to other provisions of RA 3019; and
 - (j) Complying with existing labor laws and standards, in the case of procurement of services.

Failure to observe any of the above responsibilities shall be at the risk of the Bidder concerned.

6.3. The Bidder is expected to examine all instructions, forms, terms, and specifications in the Bidding Documents.

- 6.4. It shall be the sole responsibility of the Bidder to determine and to satisfy itself by such means as it considers necessary or desirable as to all matters pertaining to the contract to be bid, including: (a) the location and the nature of this Project; (b) climatic conditions; (c) transportation facilities; and (d) other factors that may affect the cost, duration, and execution or implementation of this Project.
- 6.5. The Procuring Entity shall not assume any responsibility regarding erroneous interpretations or conclusions by the prospective or eligible bidder out of the data furnished by the procuring entity.
- 6.6. The Bidder shall bear all costs associated with the preparation and submission of his bid, and the Procuring Entity will in no case be responsible or liable for those costs, regardless of the conduct or outcome of the bidding process.
- 6.7. Before submitting their bids, the Bidder is deemed to have become familiar with all existing laws, decrees, ordinances, acts and regulations of the Philippines which may affect this Project in any way.
- 6.8. The Bidder should note that the Procuring Entity will accept bids only from those that have paid the nonrefundable fee for the Bidding Documents at the office indicated in the Invitation to Bid.

7. Origin of Goods

Unless otherwise indicated in the <u>BDS</u>, there is no restriction on the origin of goods other than those prohibited by a decision of the United Nations Security Council taken under Chapter VII of the Charter of the United Nations, subject to **ITB** Clause 27.1.

8. Subcontracts

- 8.1. Unless otherwise specified in the <u>BDS</u>, the Bidder may subcontract portions of the Goods to an extent as may be approved by the Procuring Entity and stated in the <u>BDS</u>. However, subcontracting of any portion shall not relieve the Bidder from any liability or obligation that may arise from the contract for this Project.
- 8.2. Subcontractors must comply with the eligibility criteria and the documentary requirements specified in the **BDS**. In the event that any subcontractor is found by the Procuring Entity to be ineligible, the subcontracting of such portion of the Goods shall be disallowed.
- 8.3. The Bidder may identify the subcontractor to whom a portion of the Goods will be subcontracted at any stage of the bidding process or during contract implementation. If the Bidder opts to disclose the name of the subcontractor during bid submission, the Bidder shall include the required documents as part of the technical component of its bid.

B. Contents of Bidding Documents

9. Pre-Bid Conference

9.1. (a) If so specified in the **BDS**, a pre-bid conference shall be held at the venue and on the date indicated therein, to clarify and address the Bidders' questions on the technical and financial components of this Project.

- (b) The pre-bid conference shall be held at least twelve (12) calendar days before the deadline for the submission and receipt of bids. If the Procuring Entity determines that, by reason of the method, nature, or complexity of the contract to be bid, or when international participation will be more advantageous to the GOP, a longer period for the preparation of bids is necessary, the pre-bid conference shall be held at least thirty (30) calendar days before the deadline for the submission and receipt of bids, as specified in the **BDS**.
- 9.2. Bidders are encouraged to attend the pre-bid conference to ensure that they fully understand the Procuring Entity's requirements. Non-attendance of the Bidder will in no way prejudice its bid; however, the Bidder is expected to know the changes and/or amendments to the Bidding Documents discussed during the pre-bid conference.
- 9.3. Any statement made at the pre-bid conference shall not modify the terms of the Bidding Documents unless such statement is specifically identified in writing as an amendment thereto and issued as a Supplemental/Bid Bulletin.

10. Clarification and Amendment of Bidding Documents

- 10.1. Bidders who have purchased the Bidding Documents may request for clarification on any part of the Bidding Documents for an interpretation. Such request must be in writing and submitted to the Procuring Entity at the address indicated in the **BDS** at least ten (10) calendar days before the deadline set for the submission and receipt of bids.
- 10.2. Supplemental/Bid Bulletins may be issued upon the Procuring Entity's initiative for purposes of clarifying or modifying any provision of the Bidding Documents not later than seven (7) calendar days before the deadline for the submission and receipt of bids. Any modification to the Bidding Documents shall be identified as an amendment.
- 10.3. Any Supplemental/Bid Bulletin issued by the BAC shall also be posted on the Philippine Government Electronic Procurement System (PhilGEPS) and the website of the Procuring Entity concerned, if available. It shall be the responsibility of all Bidders who secure the Bidding Documents to inquire and secure Supplemental/Bid Bulletins that may be issued by the BAC. However, Bidders who have submitted bids before the issuance of the Supplemental/Bid Bulletin must be informed and allowed to modify or withdraw their bids in accordance with **ITB** Clause 23.

C. Preparation of Bids

11. Language of Bid

The bid, as well as all correspondence and documents relating to the bid exchanged by the Bidder and the Procuring Entity, shall be written in English. Supporting documents and printed literature furnished by the Bidder may be in another language provided they are accompanied by an accurate translation in English certified by the appropriate embassy or consulate in the Philippines, in which case the English translation shall govern for purposes of interpretation of the bid.

12. Documents Comprising the Bid: Eligibility and Technical Components

- 12.1. Unless otherwise indicated in the **BDS**, the first envelope shall contain the following eligibility and technical documents:
 - (a) Eligibility Documents -

Class "A" Documents:

- (i) Registration certificate from the Securities and Exchange Commission (SEC), Department of Trade and Industry (DTI) for sole proprietorship, or Cooperative Development Authority (CDA) for cooperatives, or any proof of such registration as stated in the **BDS**;
- (ii) Mayor's permit issued by the city or municipality where the principal place of business of the prospective bidder is located;
- (iii) Statement of all its ongoing and completed government and private contracts within the period stated in the **BDS**, including contracts awarded but not yet started, if any. The statement shall include, for each contract, the following:
 - (iii.1) name of the contract;
 - (iii.2) date of the contract;
 - (iii.3) kinds of Goods;
 - (iii.4) amount of contract and value of outstanding contracts;
 - (iii.5) date of delivery; and
 - (iii.6) end user's acceptance or official receipt(s) issued for the contract, if completed.
- (iv) Audited financial statements, stamped "received" by the Bureau of Internal Revenue (BIR) or its duly accredited and authorized institutions, for the preceding calendar year, which should not be earlier than two (2) years from bid submission;
- (v) Annual Income Tax Returns filed through Electronic Filing and Payment System (EFPS) and stamped "received" by the Bureau of Internal Revenue (BIR) or its duly accredited and authorized institutions;
- (vi) NFCC computation in accordance with **ITB** Clause 5.5;
- (vii) Tax Clearance per Executive Order 398, Series of 2005, as finally reviewed and approved by the BIR; and

Class "B" Document:

(viii) If applicable, the JVA in case the joint venture is already in existence, or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide

by the provisions of the JVA in the instance that the bid is successful.

- (b) Technical Documents -
 - (i) Bid security in accordance with **ITB** Clause 18. If the Bidder opts to submit the bid security in the form of:
 - (i.1) a bank draft/guarantee or an irrevocable letter of credit issued by a foreign bank, it shall be accompanied by a confirmation from a Universal or Commercial Bank; or
 - (i.2) a surety bond, it shall be accompanied by a certification by the Insurance Commission that the surety or insurance company is authorized to issue such instruments;
 - (ii) Conformity with technical specifications, as enumerated and specified in Sections VI and VII of the Bidding Documents; and
 - (iii) Sworn statement in accordance with Section 25.2(a)(iv) of the IRR of RA 9184 and using the form prescribed in Section VIII-Bidding Forms.

13. Documents Comprising the Bid: Financial Component

- 13.1. Unless otherwise stated in the **BDS**, the financial component of the bid shall contain the following:
 - (a) Financial Bid Form, which includes bid prices and the bill of quantities and the applicable Price Schedules, in accordance with **ITB** Clauses 15.1 and 15.4;
 - (b) If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification from the DTI, SEC, or CDA issued in accordance with **ITB** Clause 27, unless otherwise provided in the **BDS**; and
 - (c) Any other document related to the financial component of the bid as stated in the **BDS**.
- 13.2. (a) Unless otherwise stated in the **BDS**, all bids that exceed the ABC shall not be accepted.
 - (b) Unless otherwise indicated in the **BDS**, for foreign-funded procurement, a ceiling may be applied to bid prices provided the following conditions are met:
 - (i) Bidding Documents are obtainable free of charge on a freely accessible website. If payment of Bidding Documents is required by the procuring entity, payment could be made upon the submission of bids.
 - (ii) The procuring entity has procedures in place to ensure that the ABC is based on recent estimates made by the responsible unit of the procuring entity and that the estimates reflect the quality, supervision and risk and inflationary factors, as well as prevailing

market prices, associated with the types of works or goods to be procured.

- (iii) The procuring entity has trained cost estimators on estimating prices and analyzing bid variances.
- (iv) The procuring entity has established a system to monitor and report bid prices relative to ABC and engineer's/procuring entity's estimate.
- (v) The procuring entity has established a system to monitor and report bid prices relative to ABC and procuring entity's estimate. The procuring entity has established a monitoring and evaluation system for contract implementation to provide a feedback on actual total costs of goods and works.

14. Alternative Bids

Alternative Bids shall be rejected. For this purpose, alternative bid is an offer made by a Bidder in addition or as a substitute to its original bid which may be included as part of its original bid or submitted separately therewith for purposes of bidding. A bid with options is considered an alternative bid regardless of whether said bid proposal is contained in a single envelope or submitted in two (2) or more separate bid envelopes.

15. Bid Prices

- 15.1. The Bidder shall complete the appropriate Price Schedules included herein, stating the unit prices, total price per item, the total amount and the expected countries of origin of the Goods to be supplied under this Project.
- 15.2. The Bidder shall fill in rates and prices for all items of the Goods described in the Bill of Quantities. Bids not addressing or providing all of the required items in the Bidding Documents including, where applicable, Bill of Quantities, shall be considered non-responsive and, thus, automatically disqualified. In this regard, where a required item is provided, but no price is indicated, the same shall be considered as non-responsive, but specifying a "0" (zero) for the said item would mean that it is being offered for free to the Government.
- 15.3. The terms Ex Works (EXW), Cost, Insurance and Freight (CIF), Cost and Insurance Paid to (CIP), Delivered Duty Paid (DDP), and other trade terms used to describe the obligations of the parties, shall be governed by the rules prescribed in the current edition of the International Commercial Terms (INCOTERMS) published by the International Chamber of Commerce, Paris.
- 15.4. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - (a) For Goods offered from within the Procuring Entity's country:
 - (i) The price of the Goods quoted EXW (ex works, ex factory, ex warehouse, ex showroom, or off-the-shelf, as applicable), including all customs duties and sales and other taxes already paid or payable:

- (i.1) on the components and raw material used in the manufacture or assembly of Goods quoted ex works or ex factory; or
- (i.2) on the previously imported Goods of foreign origin quoted ex warehouse, ex showroom, or off-the-shelf and any Procuring Entity country sales and other taxes which will be payable on the Goods if the contract is awarded.
- (ii) The price for inland transportation, insurance, and other local costs incidental to delivery of the Goods to their final destination.
- (iii) The price of other (incidental) services, if any, listed in the **BDS**.
- (b) For Goods offered from abroad:
 - (i) Unless otherwise stated in the <u>BDS</u>, the price of the Goods shall be quoted DDP with the place of destination in the Philippines as specified in the <u>BDS</u>. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
 - (ii) The price of other (incidental) services, if any, listed in the **BDS**.
- 15.5. Prices quoted by the Bidder shall be fixed during the Bidder's performance of the contract and not subject to variation or price escalation on any account. A bid submitted with an adjustable price quotation shall be treated as non-responsive and shall be rejected, pursuant to **ITB** Clause 24.

All bid prices shall be considered as fixed prices, and therefore not subject to price escalation during contract implementation, except under extraordinary circumstances. Extraordinary circumstances refer to events that may be determined by the National Economic and Development Authority in accordance with the Civil Code of the Philippines, and upon the recommendation of the Procuring Entity. Nevertheless, in cases where the cost of the awarded contract is affected by any applicable new laws, ordinances, regulations, or other acts of the GOP, promulgated after the date of bid opening, a contract price adjustment shall be made or appropriate relief shall be applied on a no loss-no gain basis.

16. Bid Currencies

- 16.1. Prices shall be quoted in the following currencies:
 - (a) For Goods that the Bidder will supply from within the Philippines, the prices shall be quoted in Philippine Pesos.
 - (b) For Goods that the Bidder will supply from outside the Philippines, the prices may be quoted in the currency(ies) stated in the **BDS**. However, for purposes of bid evaluation, bids denominated in foreign currencies shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 16.2. If so allowed in accordance with **ITB** Clause 16.1, the Procuring Entity for purposes of bid evaluation and comparing the bid prices will convert the

amounts in various currencies in which the bid price is expressed to Philippine Pesos at the foregoing exchange rates.

16.3. Unless otherwise specified in the BDS, payment of the contract price shall be made in Philippine Pesos.

17. Bid Validity

- 17.1. Bids shall remain valid for the period specified in the **BDS** which shall not exceed one hundred twenty (120) calendar days from the date of the opening of bids.
- 17.2. In exceptional circumstances, prior to the expiration of the Bid validity period, the Procuring Entity may request Bidders to extend the period of validity of their bids. The request and the responses shall be made in writing. The bid security described in **ITB** Clause 18 should also be extended corresponding to the extension of the bid validity period at the least. A Bidder may refuse the request without forfeiting its bid security, but his bid shall no longer be considered for further evaluation and award. A Bidder granting the request shall not be required or permitted to modify its bid.

18. Bid Security

18.1. The bid security in the amount stated in the **BDS** shall be equal to the percentage of the ABC in accordance with the following schedule:

Form of Bid Security	Amount of Bid Security (Equal to Percentage of the ABC)
(a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	
(b) Bank draft/guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank.	Two percent (2%)
(c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the Insurance Commission as authorized to issue such security.	Five percent (5%)
(d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security
(e) Bid Securing Declaration	No percentage required

For biddings conducted by LGUs, the Bidder may also submit bid securities in the form of cashier's/manager's check, bank draft/guarantee, or irrevocable letter of credit from other banks certified by the BSP as authorized to issue such financial statement.

The Bid Securing Declaration mentioned above is an undertaking which states, among others, that the bidder shall enter into contract with the procuring entity and furnish the performance security required under ITB Clause 33.2, from

receipt of the Notice of Award, and committing to pay the corresponding fine, and be suspended for a period of time from being qualified to participate in any government procurement activity in the event it violates any of the conditions stated therein as provided in the guidelines issued by the GPPB.

- 18.2. The bid security should be valid for the period specified in the <u>BDS</u>. Any bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.
- 18.3. No bid securities shall be returned to bidders after the opening of bids and before contract signing, except to those that failed or declared as post-disqualified, upon submission of a written waiver of their right to file a motion for reconsideration and/or protest. Without prejudice on its forfeiture, bid securities shall be returned only after the bidder with the Lowest Calculated and Responsive Bid has signed the contract and furnished the performance security, but in no case later than the expiration of the bid security validity period indicated in **ITB** Clause 18.2.
- 18.4. Upon signing and execution of the contract pursuant to **ITB** Clause 32, and the posting of the performance security pursuant to **ITB** Clause 33, the successful Bidder's bid security will be discharged, but in no case later than the bid security validity period as indicated in the **ITB** Clause 18.2.
- 18.5. The bid security may be forfeited:
 - (a) if a Bidder:
 - (i) withdraws its bid during the period of bid validity specified in **ITB** Clause 17;
 - (ii) does not accept the correction of errors pursuant to **ITB** Clause 28.3(b);
 - (iii) fails to submit the requirements within the prescribed period or a finding against their veracity as stated in **ITB** Clause 29.2;
 - (iv) submission of eligibility requirements containing false information or falsified documents;
 - (v) submission of bids that contain false information or falsified documents, or the concealment of such information in the bids in order to influence the outcome of eligibility screening or any other stage of the public bidding;
 - (vi) allowing the use of one's name, or using the name of another for purposes of public bidding;
 - (vii) withdrawal of a bid, or refusal to accept an award, or enter into contract with the Government without justifiable cause, after the Bidder had been adjudged as having submitted the Lowest Calculated and Responsive Bid;
 - (viii) refusal or failure to post the required performance security within the prescribed time;

- (ix) refusal to clarify or validate in writing its bid during postqualification within a period of seven (7) calendar days from receipt of the request for clarification;
- (x) any documented attempt by a bidder to unduly influence the outcome of the bidding in his favor;
- (xi) failure of the potential joint venture partners to enter into the joint venture after the bid is declared successful; or
- (xii) all other acts that tend to defeat the purpose of the competitive bidding, such as habitually withdrawing from bidding, submitting late Bids or patently insufficient bid, for at least three (3) times within a year, except for valid reasons.
- (b) if the successful Bidder:
 - (i) fails to sign the contract in accordance with **ITB** Clause 32; or
 - (ii) fails to furnish performance security in accordance with **ITB** Clause 33.

19. Format and Signing of Bids

- 19.1. Bidders shall submit their bids through their duly authorized representative using the appropriate forms provided in Section VIII-Bidding Forms on or before the deadline specified in the **ITB** Clauses 21 in two (2) separate sealed bid envelopes, and which shall be submitted simultaneously. The first shall contain the technical component of the bid, including the eligibility requirements under **ITB** Clause 12.1, and the second shall contain the financial component of the bid.
- 19.2. Forms as mentioned in **ITB** Clause 19.1 must be completed without any alterations to their format, and no substitute form shall be accepted. All blank spaces shall be filled in with the information requested.
- 19.3. The Bidder shall prepare and submit an original of the first and second envelopes as described in **ITB** Clauses 12 and 13. In the event of any discrepancy between the original and the copies, the original shall prevail.
- 19.4. The bid, except for unamended printed literature, shall be signed, and each and every page thereof shall be initialed, by the duly authorized representative/s of the Bidder.
- 19.5. Any interlineations, erasures, or overwriting shall be valid only if they are signed or initialed by the duly authorized representative/s of the Bidder.

20. Sealing and Marking of Bids

- 20.1. Bidders shall enclose their original eligibility and technical documents described in **ITB** Clause 12 in one sealed envelope marked "ORIGINAL TECHNICAL COMPONENT", and the original of their financial component in another sealed envelope marked "ORIGINAL FINANCIAL COMPONENT", sealing them all in an outer envelope marked "ORIGINAL BID".
- 20.2. Each copy of the first and second envelopes shall be similarly sealed duly marking the inner envelopes as "COPY NO. ___ TECHNICAL COMPONENT" and

"COPY NO. ___ - FINANCIAL COMPONENT" and the outer envelope as "COPY NO. ___", respectively. These envelopes containing the original and the copies shall then be enclosed in one single envelope.

20.3. The original and the number of copies of the Bid as indicated in the **BDS** shall be typed or written in indelible ink and shall be signed by the bidder or its duly authorized representative/s.

20.4. All envelopes shall:

- (a) contain the name of the contract to be bid in capital letters;
- (b) bear the name and address of the Bidder in capital letters;
- (c) be addressed to the Procuring Entity's BAC in accordance with **ITB** Clause 1.1;
- (d) bear the specific identification of this bidding process indicated in the **ITB** Clause 1.2; and
- (e) bear a warning "DO NOT OPEN BEFORE..." the date and time for the opening of bids, in accordance with **ITB** Clause 21.
- 20.5. If bids are not sealed and marked as required, the Procuring Entity will assume no responsibility for the misplacement or premature opening of the bid.

D. Submission and Opening of Bids

21. Deadline for Submission of Bids

Bids must be received by the Procuring Entity's BAC at the address and on or before the date and time indicated in the **BDS**.

22. Late Bids

Any bid submitted after the deadline for submission and receipt of bids prescribed by the Procuring Entity, pursuant to **ITB** Clause 21, shall be declared "Late" and shall not be accepted by the Procuring Entity.

23. Modification and Withdrawal of Bids

- 23.1. The Bidder may modify its bid after it has been submitted; provided that the modification is received by the Procuring Entity prior to the deadline prescribed for submission and receipt of bids. The Bidder shall not be allowed to retrieve its original bid, but shall be allowed to submit another bid equally sealed, properly identified, linked to its original bid marked as "TECHNICAL MODIFICATION" or "FINANCIAL MODIFICATION" and stamped "received" by the BAC. Bid modifications received after the applicable deadline shall not be considered and shall be returned to the Bidder unopened.
- 23.2. A Bidder may, through a Letter of Withdrawal, withdraw its bid after it has been submitted, for valid and justifiable reason; provided that the Letter of Withdrawal is received by the Procuring Entity prior to the deadline prescribed for submission and receipt of bids.

- 23.3. Bids requested to be withdrawn in accordance with **ITB** Clause 23.1 shall be returned unopened to the Bidders. A Bidder may also express its intention not to participate in the bidding through a letter which should reach and be stamped by the BAC before the deadline for submission and receipt of bids. A Bidder that withdraws its bid shall not be permitted to submit another bid, directly or indirectly, for the same contract.
- 23.4. No bid may be modified after the deadline for submission of bids. No bid may be withdrawn in the interval between the deadline for submission of bids and the expiration of the period of bid validity specified by the Bidder on the Financial Bid Form. Withdrawal of a bid during this interval shall result in the forfeiture of the Bidder's bid security, pursuant to **ITB** Clause 18.5, and the imposition of administrative, civil and criminal sanctions as prescribed by RA 9184 and its IRR.

24. Opening and Preliminary Examination of Bids

- 24.1. The BAC shall open the first bid envelopes of Bidders in public as specified in the **BDS** to determine each Bidder's compliance with the documents prescribed in **ITB** Clause 12. For this purpose, the BAC shall check the submitted documents of each bidder against a checklist of required documents to ascertain if they are all present, using a non-discretionary "pass/fail" criterion. If a bidder submits the required document, it shall be rated "passed" for that particular requirement. In this regard, bids that fail to include any requirement or are incomplete or patently insufficient shall be considered as "failed". Otherwise, the BAC shall rate the said first bid envelope as "passed".
- 24.2. Unless otherwise specified in the BDS, immediately after determining compliance with the requirements in the first envelope, the BAC shall forthwith open the second bid envelope of each remaining eligible bidder whose first bid envelope was rated "passed". The second envelope of each complying bidder shall be opened within the same day. In case one or more of the requirements in the second envelope of a particular bid is missing, incomplete or patently insufficient, and/or if the submitted total bid price exceeds the ABC unless otherwise provided in ITB Clause 13.2, the BAC shall rate the bid concerned as "failed". Only bids that are determined to contain all the bid requirements for both components shall be rated "passed" and shall immediately be considered for evaluation and comparison.
- 24.3. Letters of withdrawal shall be read out and recorded during bid opening, and the envelope containing the corresponding withdrawn bid shall be returned to the Bidder unopened. If the withdrawing Bidder's representative is in attendance, the original bid and all copies thereof shall be returned to the representative during the bid opening. If the representative is not in attendance, the bid shall be returned unopened by registered mail. The Bidder may withdraw its bid prior to the deadline for the submission and receipt of bids, provided that the corresponding Letter of Withdrawal contains a valid authorization requesting for such withdrawal, subject to appropriate administrative sanctions.
- 24.4. If a Bidder has previously secured a certification from the Procuring Entity to the effect that it has previously submitted the above-enumerated Class "A" Documents, the said certification may be submitted in lieu of the requirements enumerated in **ITB** Clause 12.1(a), items (i) to (v).

- 24.5. In the case of an eligible foreign Bidder as described in **ITB** Clause 5, the Class "A" Documents described in **ITB** Clause 12.1(a) may be substituted with the appropriate equivalent documents, if any, issued by the country of the foreign Bidder concerned.
- 24.6. Each partner of a joint venture agreement shall likewise submit the requirements in **ITB** Clauses 12.1(a)(i) and 12.1(a)(ii). Submission of documents required under **ITB** Clauses 12.1(a)(iii) to 12.1(a)(vi) by any of the joint venture partners constitutes compliance.
- 24.7. The Procuring Entity shall prepare the minutes of the proceedings of the bid opening that shall include, as a minimum: (a) names of Bidders, their bid price, bid security, findings of preliminary examination; and (b) attendance sheet. The BAC members shall sign the abstract of bids as read.

E. Evaluation and Comparison of Bids

25. Process to be Confidential

- 25.1. Members of the BAC, including its staff and personnel, as well as its Secretariat and TWG, are prohibited from making or accepting any kind of communication with any bidder regarding the evaluation of their bids until the issuance of the Notice of Award, unless otherwise allowed in the case of **ITB** Clause 26.
- 25.2. Any effort by a bidder to influence the Procuring Entity in the Procuring Entity's decision in respect of bid evaluation, bid comparison or contract award will result in the rejection of the Bidder's bid.

26. Clarification of Bids

To assist in the evaluation, comparison, and post-qualification of the bids, the Procuring Entity may ask in writing any Bidder for a clarification of its bid. All responses to requests for clarification shall be in writing. Any clarification submitted by a Bidder in respect to its bid and that is not in response to a request by the Procuring Entity shall not be considered.

27. Domestic Preference

- 27.1. Unless otherwise stated in the **BDS**, the Procuring Entity will grant a margin of preference for the purpose of comparison of bids in accordance with the following:
 - (a) The preference shall be applied when (i) the lowest Foreign Bid is lower than the lowest bid offered by a Domestic Bidder, or (ii) the lowest bid offered by a non-Philippine national is lower than the lowest bid offered by a Domestic Entity.
 - (b) For evaluation purposes, the lowest Foreign Bid or the bid offered by a non-Philippine national shall be increased by fifteen percent (15%).
 - (c) In the event that (i) the lowest bid offered by a Domestic Entity does not exceed the lowest Foreign Bid as increased, or (ii) the lowest bid offered by a non-Philippine national as increased, then the Procuring Entity shall award the contract to the Domestic Bidder/Entity at the amount of the

lowest Foreign Bid or the bid offered by a non-Philippine national, as the case may be.

- (d) If the Domestic Entity/Bidder refuses to accept the award of contract at the amount of the Foreign Bid or bid offered by a non-Philippine national within two (2) calendar days from receipt of written advice from the BAC, the Procuring Entity shall award to the bidder offering the Foreign Bid or the non-Philippine national, as the case may be, subject to post-qualification and submission of all the documentary requirements under these Bidding Documents.
- 27.2. A Bidder may be granted preference as a Domestic Entity subject to the certification from the DTI (in case of sole proprietorships), SEC (in case of partnerships and corporations), or CDA (in case of cooperatives) that the (a) sole proprietor is a citizen of the Philippines or the partnership, corporation, cooperative, or association is duly organized under the laws of the Philippines with at least seventy five percent (75%) of its interest or outstanding capital stock belonging to citizens of the Philippines, (b) habitually established in business and habitually engaged in the manufacture or sale of the merchandise covered by his bid, and (c) the business has been in existence for at least five (5) consecutive years prior to the advertisement and/or posting of the Invitation to Bid for this Project.
- 27.3. A Bidder may be granted preference as a Domestic Bidder subject to the certification from the DTI that the Bidder is offering unmanufactured articles, materials or supplies of the growth or production of the Philippines, or manufactured articles, materials, or supplies manufactured or to be manufactured in the Philippines substantially from articles, materials, or supplies of the growth, production, or manufacture, as the case may be, of the Philippines.

28. Detailed Evaluation and Comparison of Bids

- 28.1. The Procuring Entity will undertake the detailed evaluation and comparison of bids which have passed the opening and preliminary examination of bids, pursuant to **ITB** Clause 24, in order to determine the Lowest Calculated Bid.
- 28.2. The Lowest Calculated Bid shall be determined in two steps:
 - (a) The detailed evaluation of the financial component of the bids, to establish the correct calculated prices of the bids; and
 - (b) The ranking of the total bid prices as so calculated from the lowest to the highest. The bid with the lowest price shall be identified as the Lowest Calculated Bid.
- 28.3. The Procuring Entity's BAC shall immediately conduct a detailed evaluation of all bids rated "passed," using non-discretionary pass/fail criteria. Unless otherwise specified in the **BDS**, the BAC shall consider the following in the evaluation of bids:
 - (a) <u>Completeness of the bid.</u> Unless the ITB specifically allows partial bids, bids not addressing or providing all of the required items in the Schedule of Requirements including, where applicable, bill of quantities, shall be considered non-responsive and, thus, automatically disqualified. In this regard, where a required item is provided, but no price is

indicated, the same shall be considered as non-responsive, but specifying a "0" (zero) for the said item would mean that it is being offered for free to the Procuring Entity; and

- (b) <u>Arithmetical corrections.</u> Consider computational errors and omissions to enable proper comparison of all eligible bids. It may also consider bid modifications, if allowed in the <u>BDS</u>. Any adjustment shall be calculated in monetary terms to determine the calculated prices.
- 28.4. Based on the detailed evaluation of bids, those that comply with the above-mentioned requirements shall be ranked in the ascending order of their total calculated bid prices, as evaluated and corrected for computational errors, discounts and other modifications, to identify the Lowest Calculated Bid. Total calculated bid prices, as evaluated and corrected for computational errors, discounts and other modifications, which exceed the ABC shall not be considered, unless otherwise indicated in the **BDS**.
- 28.5. The Procuring Entity's evaluation of bids shall only be based on the bid price quoted in the Financial Bid Form.
- 28.6. Bids shall be evaluated on an equal footing to ensure fair competition. For this purpose, all bidders shall be required to include in their bids the cost of all taxes, such as, but not limited to, value added tax (VAT), income tax, local taxes, and other fiscal levies and duties which shall be itemized in the bid form and reflected in the detailed estimates. Such bids, including said taxes, shall be the basis for bid evaluation and comparison.

29. Post-Qualification

- 29.1. The Procuring Entity shall determine to its satisfaction whether the Bidder that is evaluated as having submitted the Lowest Calculated Bid (LCB) complies with and is responsive to all the requirements and conditions specified in **ITB** Clauses 5, 12, and 13.
- 29.2. Within a non-extendible period of three (3) calendar days from receipt by the bidder of the notice from the BAC that it submitted the LCB, the Bidder shall submit the following documentary requirements:
 - (a) Tax clearance per Executive Order 398, Series of 2005;
 - (b) Latest income and business tax returns in the form specified in the **BDS**;
 - (c) Certificate of PhilGEPS Registration; and
 - (d) Other appropriate licenses and permits required by law and stated in the **BDS**.

Failure of the Bidder declared as Lowest Calculated Bid to duly submit the requirements under this Clause or a finding against the veracity of such shall be ground for forfeiture of the bid security and disqualification of the Bidder for award.

29.3. The determination shall be based upon an examination of the documentary evidence of the Bidder's qualifications submitted pursuant to **ITB** Clauses 12 and 13, as well as other information as the Procuring Entity deems necessary and appropriate, using a non-discretionary "pass/fail" criterion.

- 29.4. If the BAC determines that the Bidder with the Lowest Calculated Bid passes all the criteria for post-qualification, it shall declare the said bid as the Lowest Calculated Responsive Bid, and recommend to the Head of the Procuring Entity the award of contract to the said Bidder at its submitted price or its calculated bid price, whichever is lower.
- 29.5. A negative determination shall result in rejection of the Bidder's Bid, in which event the Procuring Entity shall proceed to the next Lowest Calculated Bid to make a similar determination of that Bidder's capabilities to perform satisfactorily. If the second Bidder, however, fails the post qualification, the procedure for post qualification shall be repeated for the Bidder with the next Lowest Calculated Bid, and so on until the Lowest Calculated Responsive Bid is determined for contract award.
- 29.6. Within a period not exceeding seven (7) calendar days from the date of receipt of the recommendation of the BAC, the Head of the Procuring Entity shall approve or disapprove the said recommendation. In the case of GOCCs and GFIs, the period provided herein shall be fifteen (15) calendar days.

30. Reservation Clause

- 30.1. Notwithstanding the eligibility or post-qualification of a Bidder, the Procuring Entity concerned reserves the right to review its qualifications at any stage of the procurement process if it has reasonable grounds to believe that a misrepresentation has been made by the said Bidder, or that there has been a change in the Bidder's capability to undertake the project from the time it submitted its eligibility requirements. Should such review uncover any misrepresentation made in the eligibility and bidding requirements, statements or documents, or any changes in the situation of the Bidder which will affect its capability to undertake the project so that it fails the preset eligibility or bid evaluation criteria, the Procuring Entity shall consider the said Bidder as ineligible and shall disqualify it from submitting a bid or from obtaining an award or contract.
- 30.2. Based on the following grounds, the Procuring Entity reserves the right to reject any and all bids, declare a failure of bidding at any time prior to the contract award, or not to award the contract, without thereby incurring any liability, and make no assurance that a contract shall be entered into as a result of the bidding:
 - (a) If there is *prima facie* evidence of collusion between appropriate public officers or employees of the Procuring Entity, or between the BAC and any of the Bidders, or if the collusion is between or among the bidders themselves, or between a Bidder and a third party, including any act which restricts, suppresses or nullifies or tends to restrict, suppress or nullify competition;
 - (b) If the Procuring Entity's BAC is found to have failed in following the prescribed bidding procedures; or
 - (c) For any justifiable and reasonable ground where the award of the contract will not redound to the benefit of the GOP as follows:
 - (i) If the physical and economic conditions have significantly changed so as to render the project no longer economically,

financially or technically feasible as determined by the head of the procuring entity;

- (ii) If the project is no longer necessary as determined by the head of the procuring entity; and
- (iii) If the source of funds for the project has been withheld or reduced through no fault of the Procuring Entity.
- 30.3. In addition, the Procuring Entity may likewise declare a failure of bidding when:
 - (a) No bids are received;
 - (b) All prospective Bidders are declared ineligible;
 - (c) All bids fail to comply with all the bid requirements or fail post-qualification; or
 - (d) The Bidder with the Lowest Calculated Responsive Bid (LCRB) refuses, without justifiable cause to accept the award of contract, and no award is made.

F. Award of Contract

31. Contract Award

- 31.1. Subject to **ITB** Clause 29, the Procuring Entity shall award the contract to the Bidder whose bid has been determined to be the LCRB.
- 31.2. Prior to the expiration of the period of bid validity, the Procuring Entity shall notify the successful Bidder in writing that its bid has been accepted, through a Notice of Award received personally or sent by registered mail or electronically, receipt of which must be confirmed in writing within two (2) days by the Bidder with the LCRB and submitted personally or sent by registered mail or electronically to the Procuring Entity.
- 31.3. Notwithstanding the issuance of the Notice of Award, award of contract shall be subject to the following conditions:
 - (a) Submission of the valid JVA, if applicable, within ten (10) calendar days from receipt by the Bidder of the notice from the BAC that the Bidder has the LCRB;
 - (b) Posting of the performance security in accordance with **ITB** Clause 33;
 - (c) Signing of the contract as provided in **ITB** Clause 32; and
 - (d) Approval by higher authority, if required.
- 31.4. At the time of contract award, the Procuring Entity shall not increase or decrease the quantity of goods originally specified in Section VI-Schedule of Requirements.

32. Signing of the Contract

- 32.1. At the same time as the Procuring Entity notifies the successful Bidder that its bid has been accepted, the Procuring Entity shall send the Contract Form to the Bidder, which contract has been provided in the Bidding Documents, incorporating therein all agreements between the parties.
- 32.2. Within ten (10) calendar days from receipt of the Notice of Award, the successful Bidder shall post the required performance security and sign and date the contract and return it to the Procuring Entity.
- 32.3. The Procuring Entity shall enter into contract with the successful Bidder within the same ten (10) calendar day period provided that all the documentary requirements are complied with.
- 32.4. The following documents shall form part of the contract:
 - (a) Contract Agreement;
 - (b) Bidding Documents;
 - (c) Winning bidder's bid, including the Technical and Financial Proposals, and all other documents/statements submitted;
 - (d) Performance Security;
 - (e) Credit line in accordance with **ITB** Clause 5.5, if applicable;
 - (f) Notice of Award of Contract; and
 - (g) Other contract documents that may be required by existing laws and/or specified in the **BDS**.

33. Performance Security

- 33.1. To guarantee the faithful performance by the winning Bidder of its obligations under the contract, it shall post a performance security within a maximum period of ten (10) calendar days from the receipt of the Notice of Award from the Procuring Entity and in no case later than the signing of the contract.
- 33.2. The performance security shall be denominated in Philippine Pesos and posted in favor of the Procuring Entity in an amount equal to the percentage of the total contract price in accordance with the following schedule:

Form of Performance Security	Amount of Performance Security (Equal to Percentage of the Total Contract Price)
(a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	Five percent (5%)

(b) Bank draft/guarantee or irrevocable letter of credit issued	
by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank.	Five percent (5%)
(c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the Insurance Commission as authorized to issue such security; and/or	Thirty percent (30%)
(d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security

33.3. Failure of the successful Bidder to comply with the above-mentioned requirement shall constitute sufficient ground for the annulment of the award and forfeiture of the bid security, in which event the Procuring Entity shall initiate and complete the post qualification of the second Lowest Calculated Bid. The procedure shall be repeated until the LCRB is identified and selected for contract award. However if no Bidder passed post-qualification, the BAC shall declare the bidding a failure and conduct a re-bidding with re-advertisement.

34. Notice to Proceed

- 34.1. Within three (3) calendar days from the date of approval of the contract by the appropriate government approving authority, the Procuring Entity shall issue its Notice to Proceed to the Bidder.
- 34.2. The contract effectivity date shall be provided in the Notice to Proceed by the Procuring Entity, which date shall not be later than seven (7) calendar days from the issuance of the Notice to Proceed.

SECTION III BID DATA SHEETS

ITB Clause	
1.1	The Procuring Entity is Batangas State University
1.2	Not applicable
<u>2</u>	The Funding Source is:
	The Government of the Philippines (GOP) in the amount of One Million Four Hundred Eighty Thousand Two Hundred Fifty Pesos Only (Php 1,480,250.00).
	The name of the Project is Procurement of IT Equipment & Peripherals for Various Offices/Colleges (Re-bidding).
	Theidentification number of the Project is BSU-Project No. 2016-117.
3.1	No further instructions.
5.1	No further instructions.
5.2	Bidding is restricted to eligible bidders as defined in ITB Clause 5.1.
5.4	Bidders should have completed, within three (3) years from the date of submission and receipt of bids, a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
5.5	No further instructions.
6.3	No further instructions.
7	No further instructions.
8.1	Subcontracting is not allowed.
8.2	Not applicable.
9.1	The Procuring Entity will hold a pre-bid conference for this Project on <i>April 8, 2016, 2:00 PM</i> .
	BAC Office Ground Floor, CITE Building Batangas State University, GPB Campus I Rizal Avenue Extension, BatangasCity
10.1	The Procuring Entity's address is:
	2 nd Floor, CITE Building, Batangas State University, GPB Campus I Rizal Avenue Extension, BatangasCity

	Dr. Tirso A. Ronquillo University President
40.4	Tel. No.(043) 723-0339 / 980-0385 local 1546
12.1	No further instructions.
12.1(a)(i)	No other acceptable proof of registration is recognized.
12.1(a)(iii)	The statement "covers all ongoing and completed government and private contracts" shall include all such contracts within <i>three (3) years</i> prior to the deadline for the submission and receipt of bids, including contracts awarded but not yet started, if any. The value of the prospective Bidder's largest contract, adjusted to current price index must be at least fifty percent (50%) of the ABC/Sub ABC in order to be eligible to bid for the project.
13.1	No additional requirements.
13.2	The Total ABC is One Million Four Hundred Eighty Thousand Two Hundred Fifty Pesos Only (Php 1,480,250.00).
	Any bid with a financial component exceeding this amount shall not be accepted.
15.4(a)(iii)	No incidental services are required.
15.4(a)(iii)	Not applicable
	No incidental services are required.
15.5	Bid Prices shall be fixed. Adjustable price proposals shall be treated as non-responsive and shall be rejected.
15.6	Extraordinary circumstances refer to events that may be determined by the National Economic and Development Authority in accordance with the Civil Code of the Philippines, and upon the recommendation of the Procuring Entity.
16.1(b)	The Bid prices for Goods supplied from outside of the Philippines shall be quoted in Philippine Pesos.
16.3	No further instructions.
17.1	Bid validity period is <i>One Hundred Twenty (120) calendar days</i> from the date of opening of bids.
18.1	The bid security shall be in the following amount:
	 Two (2%) of the ABC, if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit;
	2. Five (5%) of the ABC if bid security is in Surety Bond; or
	3. Any combination of the foregoing proportionate to the share of form with respect to total amount of security.

	4. Bid Securing Declaration (Use BatStateU Goods Form No. 5c)
18.2	The validity period for bid security is One Hundred twenty (120) calendar days from the date of opening of bid.
20.3	Each Bidder shall submit <i>one</i> (1) original and <i>two</i> (2) copies of the first and second components of its bid.
21	The address for submission of bids is
	BAC Office Ground Floor, CITEBuilding Batangas State University, GPB Campus I Rizal Avenue Extension, BatangasCity
	The deadline for submission of bids is 1:00 to 2:00 PM, April 20, 2016.
24.1	The place of bid opening is
	BAC Office
	Ground Floor, CITEBuilding
	Batangas State University, GPB Campus I
	Rizal Avenue Extension, BatangasCity
	The date and time of bid opening is 2:00PM, April 20, 2016.
24.2	No further instructions.
27.1	No further instructions.
28.3	The goods are grouped in a single lot and the lot shall not be divided into sub-lots for the purpose of bidding, evaluation, and contract award.
28.3(b)	Bid modification in whatever form is not allowed.
28.3	No further instructions.
29.2(a)	No further instructions.
29.2(b)	Not applicable
29.2(d)	No other licenses required.
32.4(g)	No other contract documents needed.

SECTION IV GENERAL CONDITIONS OF THE CONTRACT

TABLE OF CONTENTS

1.	DEFINITIONS	3
2.	CORRUPT, FRAUDULENT, COLLUSIVE, AND COERCIVE PRACTICES	3
3.	INSPECTION AND AUDIT BY THE FUNDING SOURCE	5
4.	GOVERNING LAW AND LANGUAGE	5
5.	NOTICES	5
6.	SCOPE OF CONTRACT	5
7.	SUBCONTRACTING	5
8.	PROCURING ENTITY'S RESPONSIBILITIES	6
9.	PRICES	6
10.	PAYMENT	6
11.	ADVANCE PAYMENT AND TERMS OF PAYMENT	7
12.	TAXES AND DUTIES	7
13.	Performance Security	7
14.	USE OF CONTRACT DOCUMENTS AND INFORMATION	8
15.	STANDARDS	8
16.	INSPECTION AND TESTS	8
17.	WARRANTY	9
18.	DELAYS IN THE SUPPLIER'S PERFORMANCE	.10
19.	LIQUIDATED DAMAGES	.10
20.	SETTLEMENT OF DISPUTES	.10
21.	LIABILITY OF THE SUPPLIER	.11
22.	FORCE MAJEURE	.11
23.	TERMINATION FOR DEFAULT	.11
24.	TERMINATION FOR INSOLVENCY	.12
25	TERMINATION FOR CONVENIENCE	12

26.	TERMINATION FOR UNLAWFUL ACTS	13
27.	PROCEDURES FOR TERMINATION OF CONTRACTS	13
28.	ASSIGNMENT OF RIGHTS	14
29.	CONTRACT AMENDMENT	14
30.	APPLICATION	14

1. Definitions

- 1.1. In this Contract, the following terms shall be interpreted as indicated:
 - (a) "The Contract" means the agreement entered into between the Procuring Entity and the Supplier, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.
 - (b) "The Contract Price" means the price payable to the Supplier under the Contract for the full and proper performance of its contractual obligations.
 - (c) "The Goods" means all of the supplies, equipment, machinery, spare parts, other materials and/or general support services which the Supplier is required to provide to the Procuring Entity under the Contract.
 - (d) "The Services" means those services ancillary to the supply of the Goods, such as transportation and insurance, and any other incidental services, such as installation, commissioning, provision of technical assistance, training, and other such obligations of the Supplier covered under the Contract.
 - (e) "GCC" means the General Conditions of Contract contained in this Section.
 - (f) "SCC" means the Special Conditions of Contract.
 - (g) "The Procuring Entity" means the organization purchasing the Goods, as named in the **SCC**.
 - (h) "The Procuring Entity's country" is the Philippines.
 - (i) "The Supplier" means the individual contractor, manufacturer distributor, or firm supplying/manufacturing the Goods and Services under this Contract and named in the **SCC**.
 - (j) The "Funding Source" means the organization named in the **SCC**.
 - (k) "The Project Site," where applicable, means the place or places named in the **SCC**.
 - (l) "Day" means calendar day.
 - (m) The "Effective Date" of the contract will be the date of receipt by the Supplier of the Notice to Proceed or the date provided in the Notice to Proceed. Performance of all obligations shall be reckoned from the Effective Date of the Contract.
 - (n) "Verified Report" refers to the report submitted by the Implementing Unit to the Head of the Procuring Entity setting forth its findings as to the existence of grounds or causes for termination and explicitly stating its recommendation for the issuance of a Notice to Terminate.

2. Corrupt, Fraudulent, Collusive, and Coercive Practices

2.1. Unless otherwise provided in the <u>SCC</u>, the Procuring Entity as well as the bidders, contractors, or suppliers shall observe the highest standard of ethics during the procurement and execution of this Contract. In pursuance of this policy, the Procuring Entity:

- (a) defines, for the purposes of this provision, the terms set forth below as follows:
 - (i) "corrupt practice" means behavior on the part of officials in the public or private sectors by which they improperly and unlawfully enrich themselves, others, or induce others to do so, by misusing the position in which they are placed, and it includes the offering, giving, receiving, or soliciting of anything of value to influence the action of any such official in the procurement process or in contract execution; entering, on behalf of the Government, into any contract or transaction manifestly and grossly disadvantageous to the same, whether or not the public officer profited or will profit thereby, and similar acts as provided in Republic Act 3019.
 - (ii) "fraudulent practice" means a misrepresentation of facts in order to influence a procurement process or the execution of a contract to the detriment of the Procuring Entity, and includes collusive practices among Bidders (prior to or after bid submission) designed to establish bid prices at artificial, non-competitive levels and to deprive the Procuring Entity of the benefits of free and open competition.
 - (iii) "collusive practices" means a scheme or arrangement between two or more Bidders, with or without the knowledge of the Procuring Entity, designed to establish bid prices at artificial, noncompetitive levels.
 - (iv) "coercive practices" means harming or threatening to harm, directly or indirectly, persons, or their property to influence their participation in a procurement process, or affect the execution of a contract;
 - (v) "obstructive practice" is
 - deliberately destroying, falsifying, altering or concealing of evidence material to an administrative proceedings or investigation or making false statements to investigators in order to materially impede an administrative proceedings or investigation of the Procuring Entity or any foreign government/foreign or international financing institution into allegations of a corrupt, fraudulent, coercive or collusive practice; and/or threatening, harassing or intimidating any party to prevent it from disclosing its knowledge of matters relevant to the administrative proceedings or investigation or from pursuing such proceedings or investigation; or
 - (bb) acts intended to materially impede the exercise of the inspection and audit rights of the Procuring Entity or any foreign government/foreign or international financing institution herein.
- (b) will reject a proposal for award if it determines that the Bidder recommended for award has engaged in any of the practices mentioned in this Clause for purposes of competing for the contract.

2.2. Further the Funding Source, Borrower or Procuring Entity, as appropriate, will seek to impose the maximum civil, administrative and/or criminal penalties available under the applicable law on individuals and organizations deemed to be involved with any of the practices mentioned in **GCC** Clause 2.1(a).

3. Inspection and Audit by the Funding Source

The Supplier shall permit the Funding Source to inspect the Supplier's accounts and records relating to the performance of the Supplier and to have them audited by auditors appointed by the Funding Source, if so required by the Funding Source.

4. Governing Law and Language

- 4.1. This Contract shall be interpreted in accordance with the laws of the Republic of the Philippines.
- 4.2. This Contract has been executed in the English language, which shall be the binding and controlling language for all matters relating to the meaning or interpretation of this Contract. All correspondence and other documents pertaining to this Contract exchanged by the parties shall be written in English.

5. Notices

- 5.1. Any notice, request, or consent required or permitted to be given or made pursuant to this Contract shall be in writing. Any such notice, request, or consent shall be deemed to have been given or made when received by the concerned party, either in person or through an authorized representative of the Party to whom the communication is addressed, or when sent by registered mail, telex, telegram, or facsimile to such Party at the address specified in the **SCC**, which shall be effective when delivered and duly received or on the notice's effective date, whichever is later.
- 5.2. A Party may change its address for notice hereunder by giving the other Party notice of such change pursuant to the provisions listed in the **SCC** for **GCC** Clause 5.1.

6. Scope of Contract

- 6.1. The GOODS and Related Services to be provided shall be as specified in Error! Reference source not found.
- 6.2. This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. Any additional requirements for the completion of this Contract shall be provided in the <u>SCC</u>.

7. Subcontracting

7.1. Subcontracting of any portion of the Goods, if allowed in the **BDS**, does not relieve the Supplier of any liability or obligation under this Contract. The Supplier will be responsible for the acts, defaults, and negligence of any subcontractor, its agents, servants or workmen as fully as if these were the Supplier's own acts, defaults, or negligence, or those of its agents, servants or workmen.

7.2. Subcontractors disclosed and identified during the bidding may be changed during the implementation of this Contract, subject to compliance with the required qualifications and the approval of the Procuring Entity.

8. Procuring Entity's Responsibilities

- 8.1. Whenever the performance of the obligations in this Contract requires that the Supplier obtain permits, approvals, import, and other licenses from local public authorities, the Procuring Entity shall, if so needed by the Supplier, make its best effort to assist the Supplier in complying with such requirements in a timely and expeditious manner.
- 8.2. The Procuring Entity shall pay all costs involved in the performance of its responsibilities in accordance with **GCC** Clause 6.

9. Prices

- 9.1. For the given scope of work in this Contract as awarded, all bid prices are considered fixed prices, and therefore not subject to price escalation during contract implementation, except under extraordinary circumstances and upon prior approval of the GPPB in accordance with Section 61 of R.A. 9184 and its IRR or except as provided in this Clause.
- 9.2. Prices charged by the Supplier for Goods delivered and/or services performed under this Contract shall not vary from the prices quoted by the Supplier in its bid, with the exception of any change in price resulting from a Change Order issued in accordance with **GCC** Clause 29.

10. Payment

- 10.1. Payments shall be made only upon a certification by the Head of the Procuring Entity to the effect that the Goods have been rendered or delivered in accordance with the terms of this Contract and have been duly inspected and accepted. Except with the prior approval of the President no payment shall be made for services not yet rendered or for supplies and materials not yet delivered under this Contract. Ten percent (10%) of the amount of each payment shall be retained by the Procuring Entity to cover the Supplier's warranty obligations under this Contract as described in **GCC** Clause 17.
- 10.2. The Supplier's request(s) for payment shall be made to the Procuring Entity in writing, accompanied by an invoice describing, as appropriate, the Goods delivered and/or Services performed, and by documents submitted pursuant to the <u>SCC</u> provision for GCC Clause 6.2, and upon fulfillment of other obligations stipulated in this Contract.
- 10.3. Pursuant to **GCC** Clause 10.2, payments shall be made promptly by the Procuring Entity, but in no case later than sixty (60) days after submission of an invoice or claim by the Supplier.
- 10.4. Unless otherwise provided in the SCC, the currency in which payment is made to the Supplier under this Contract shall be in Philippine Pesos.

11. Advance Payment and Terms of Payment

- 11.1. Advance payment shall be made only after prior approval of the President, and shall not exceed fifteen percent (15%) of the Contract amount, unless otherwise directed by the President or in cases allowed under Annex "D" of RA 9184.
- 11.2. For Goods supplied from abroad, the terms of payment shall be as follows:
 - (a) On Contract Signature: Ten percent (10%) of the Contract Price shall be paid within sixty (60) days from signing of the Contract and upon submission of a claim and a bank guarantee for the equivalent amount valid until the Goods are delivered and in the form provided in Section VIII. Bidding Forms.
 - (b) On Delivery: Seventy percent (70%) of the Contract Price shall be paid to the Supplier within sixty (60) days after the date of receipt of the Goods and upon submission of the documents (i) through (vi) specified in the SCC provision on Delivery and Documents.
 - (c) On Acceptance: The remaining twenty percent (20%) of the Contract Price shall be paid to the Supplier within sixty (60) days after the date of submission of the acceptance and inspection certificate for the respective delivery issued by the Procuring Entity's authorized representative. In the event that no inspection or acceptance certificate is issued by the Procuring Entity's authorized representative within forty five (45) days of the date shown on the delivery receipt the Supplier shall have the right to claim payment of the remaining twenty percent (20%) subject to the Procuring Entity's own verification of the reason(s) for the failure to issue documents (vii) and (viii) as described in the SCC provision on Delivery and Documents.
- 11.3. All progress payments shall first be charged against the advance payment until the latter has been fully exhausted.

12. Taxes and Duties

The Supplier, whether local or foreign, shall be entirely responsible for all the necessary taxes, stamp duties, license fees, and other such levies imposed for the completion of this Contract.

13. Performance Security

- 13.1. Within ten (10) calendar days from receipt of the Notice of Award from the Procuring Entity but in no case later than the signing of the contract by both parties, the successful Bidder shall furnish the performance security in any the forms prescribed in the **ITB** Clause 33.2.
- 13.2. The performance security posted in favor of the Procuring Entity shall be forfeited in the event it is established that the winning bidder is in default in any of its obligations under the contract.
- 13.3. The performance security shall remain valid until issuance by the Procuring Entity of the Certificate of Final Acceptance.

- 13.4. The performance security may be released by the Procuring Entity and returned to the Supplier after the issuance of the Certificate of Final Acceptance subject to the following conditions:
 - (a) There are no pending claims against the Supplier or the surety company filed by the Procuring Entity;
 - (b) The Supplier has no pending claims for labor and materials filed against it: and
 - (c) Other terms specified in the **SCC**.
- 13.5. In case of a reduction of the contract value, the Procuring Entity shall allow a proportional reduction in the original performance security, provided that any such reduction is more than ten percent (10%) and that the aggregate of such reductions is not more than fifty percent (50%) of the original performance security.

14. Use of Contract Documents and Information

- 14.1. The Supplier shall not, except for purposes of performing the obligations in this Contract, without the Procuring Entity's prior written consent, disclose this Contract, or any provision thereof, or any specification, plan, drawing, pattern, sample, or information furnished by or on behalf of the Procuring Entity. Any such disclosure shall be made in confidence and shall extend only as far as may be necessary for purposes of such performance.
- 14.2. Any document, other than this Contract itself, enumerated in **GCC** Clause 14.1 shall remain the property of the Procuring Entity and shall be returned (all copies) to the Procuring Entity on completion of the Supplier's performance under this Contract if so required by the Procuring Entity.

15. Standards

The Goods provided under this Contract shall conform to the standards mentioned in the **Error! Reference source not found.**; and, when no applicable standard is mentioned, to the authoritative standards appropriate to the Goods' country of origin. Such standards shall be the latest issued by the institution concerned.

16. Inspection and Tests

- 16.1. The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Contract specifications at no extra cost to the Procuring Entity. The <u>SCC</u> and <u>Error!</u> Reference source not found. shall specify what inspections and/or tests the Procuring Entity requires and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.
- 16.2. If applicable, the inspections and tests may be conducted on the premises of the Supplier or its subcontractor(s), at point of delivery, and/or at the goods' final destination. If conducted on the premises of the Supplier or its subcontractor(s), all reasonable facilities and assistance, including access to drawings and production data, shall be furnished to the inspectors at no charge to the

- Procuring Entity. The Supplier shall provide the Procuring Entity with results of such inspections and tests.
- 16.3. The Procuring Entity or its designated representative shall be entitled to attend the tests and/or inspections referred to in this Clause provided that the Procuring Entity shall bear all of its own costs and expenses incurred in connection with such attendance including, but not limited to, all traveling and board and lodging expenses.
- 16.4. The Procuring Entity may reject any Goods or any part thereof that fail to pass any test and/or inspection or do not conform to the specifications. The Supplier shall either rectify or replace such rejected Goods or parts thereof or make alterations necessary to meet the specifications at no cost to the Procuring Entity, and shall repeat the test and/or inspection, at no cost to the Procuring Entity, upon giving a notice pursuant to **GCC** Clause 5.
- 16.5. The Supplier agrees that neither the execution of a test and/or inspection of the Goods or any part thereof, nor the attendance by the Procuring Entity or its representative, shall release the Supplier from any warranties or other obligations under this Contract.

17. Warranty

- 17.1. The Supplier warrants that the Goods supplied under the Contract are new, unused, of the most recent or current models, and that they incorporate all recent improvements in design and materials, except when the technical specifications required by the Procuring Entity provides otherwise.
- 17.2. The Supplier further warrants that all Goods supplied under this Contract shall have no defect, arising from design, materials, or workmanship or from any act or omission of the Supplier that may develop under normal use of the supplied Goods in the conditions prevailing in the country of final destination.
- 17.3. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier for a minimum period specified in the SCC. The obligation for the warranty shall be covered by, at the Supplier's option, either retention money in an amount equivalent to at least ten percent (10%) of the final payment, or a special bank guarantee equivalent to at least ten percent (10%) of the Contract Price or other such amount if so specified in the SCC. The said amounts shall only be released after the lapse of the warranty period specified in the SCC; provided, however, that the Supplies delivered are free from patent and latent defects and all the conditions imposed under this Contract have been fully met.
- 17.4. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, within the period specified in the **SCC** and with all reasonable speed, repair or replace the defective Goods or parts thereof, without cost to the Procuring Entity.
- 17.5. If the Supplier, having been notified, fails to remedy the defect(s) within the period specified in **GCC** Clause 17.4, the Procuring Entity may proceed to take such remedial action as may be necessary, at the Supplier's risk and expense and without prejudice to any other rights which the Procuring Entity may have against the Supplier under the Contract and under the applicable law.

18. Delays in the Supplier's Performance

- 18.1. Delivery of the Goods and/or performance of Services shall be made by the Supplier in accordance with the time schedule prescribed by the Procuring Entity in **Section VI-Schedule of Requirements**.
- 18.2. If at any time during the performance of this Contract, the Supplier or its Subcontractor(s) should encounter conditions impeding timely delivery of the Goods and/or performance of Services, the Supplier shall promptly notify the Procuring Entity in writing of the fact of the delay, its likely duration and its cause(s). As soon as practicable after receipt of the Supplier's notice, and upon causes provided for under **GCC** Clause 22, the Procuring Entity shall evaluate the situation and may extend the Supplier's time for performance, in which case the extension shall be ratified by the parties by amendment of Contract.
- 18.3. Except as provided under **GCC** Clause 22, a delay by the Supplier in the performance of its obligations shall render the Supplier liable to the imposition of liquidated damages pursuant to **GCC** Clause 19, unless an extension of time is agreed upon pursuant to **GCC** Clause 29 without the application of liquidated damages.

19. Liquidated Damages

Subject to **GCC** Clauses 18 and 22, if the Supplier fails to satisfactorily deliver any or all of the Goods and/or to perform the Services within the period(s) specified in this Contract inclusive of duly granted time extensions if any, the Procuring Entity shall, without prejudice to its other remedies under this Contract and under the applicable law, deduct from the Contract Price, as liquidated damages, the applicable rate of one tenth (1/10) of one (1) percent of the cost of the unperformed portion for every day of delay until actual delivery or performance. The maximum deduction shall be ten percent (10%) of the amount of contract. Once the maximum is reached, the Procuring Entity shall rescind the Contract pursuant to **GCC** Clause 23, without prejudice to other courses of action and remedies open to it.

20. Settlement of Disputes

- 20.1. If any dispute or difference of any kind whatsoever shall arise between the Procuring Entity and the Supplier in connection with or arising out of this Contract, the parties shall make every effort to resolve amicably such dispute or difference by mutual consultation.
- 20.2. If after thirty (30) days, the parties have failed to resolve their dispute or difference by such mutual consultation, then either the Procuring Entity or the Supplier may give notice to the other party of its intention to commence arbitration, as hereinafter provided, as to the matter in dispute, and no arbitration in respect of this matter may be commenced unless such notice is given.
- 20.3. Any dispute or difference in respect of which a notice of intention to commence arbitration has been given in accordance with this Clause shall be settled by arbitration. Arbitration may be commenced prior to or after delivery of the Goods under this Contract.

- 20.4. In the case of a dispute between the Procuring Entity and the Supplier, the dispute shall be resolved in accordance with Republic Act 9285 ("R.A. 9285"), otherwise known as the "Alternative Dispute Resolution Act of 2004."
- 20.5. Notwithstanding any reference to arbitration herein, the parties shall continue to perform their respective obligations under the Contract unless they otherwise agree; and the Procuring Entity shall pay the Supplier any monies due the Supplier.

21. Liability of the Supplier

- 21.1. The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines, subject to additional provisions, if any, set forth in the **SCC**.
- 21.2. Except in cases of criminal negligence or willful misconduct, and in the case of infringement of patent rights, if applicable, the aggregate liability of the Supplier to the Procuring Entity shall not exceed the total Contract Price, provided that this limitation shall not apply to the cost of repairing or replacing defective equipment.

22. Force Majeure

- 22.1. The Supplier shall not be liable for forfeiture of its performance security, liquidated damages, or termination for default if and to the extent that the Supplier's delay in performance or other failure to perform its obligations under the Contract is the result of a *force majeure*.
- 22.2. For purposes of this Contract the terms "force majeure" and "fortuitous event" may be used interchangeably. In this regard, a fortuitous event or force majeure shall be interpreted to mean an event which the Contractor could not have foreseen, or which though foreseen, was inevitable. It shall not include ordinary unfavorable weather conditions; and any other cause the effects of which could have been avoided with the exercise of reasonable diligence by the Contractor. Such events may include, but not limited to, acts of the Procuring Entity in its sovereign capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions, and freight embargoes.
- 22.3. If a *force majeure* situation arises, the Supplier shall promptly notify the Procuring Entity in writing of such condition and the cause thereof. Unless otherwise directed by the Procuring Entity in writing, the Supplier shall continue to perform its obligations under the Contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the *force majeure*.

23. Termination for Default

- 23.1. The Procuring Entity shall terminate this Contract for default when any of the following conditions attends its implementation:
 - (a) Outside of *force majeure*, the Supplier fails to deliver or perform any or all of the Goods within the period(s) specified in the contract, or within any extension thereof granted by the Procuring Entity pursuant to a request

- made by the Supplier prior to the delay, and such failure amounts to at least ten percent (10%) of the contact price;
- (b) As a result of *force majeure*, the Supplier is unable to deliver or perform any or all of the Goods, amounting to at least ten percent (10%) of the contract price, for a period of not less than sixty (60) calendar days after receipt of the notice from the Procuring Entity stating that the circumstance of force majeure is deemed to have ceased; or
- (c) The Supplier fails to perform any other obligation under the Contract.
- 23.2. In the event the Procuring Entity terminates this Contract in whole or in part, for any of the reasons provided under **GCC** Clauses 23 to 26, the Procuring Entity may procure, upon such terms and in such manner as it deems appropriate, Goods or Services similar to those undelivered, and the Supplier shall be liable to the Procuring Entity for any excess costs for such similar Goods or Services. However, the Supplier shall continue performance of this Contract to the extent not terminated.
- 23.3. In case the delay in the delivery of the Goods and/or performance of the Services exceeds a time duration equivalent to ten percent (10%) of the specified contract time plus any time extension duly granted to the Supplier, the Procuring Entity may terminate this Contract, forfeit the Supplier's performance security and award the same to a qualified Supplier.

24. Termination for Insolvency

The Procuring Entity shall terminate this Contract if the Supplier is declared bankrupt or insolvent as determined with finality by a court of competent jurisdiction. In this event, termination will be without compensation to the Supplier, provided that such termination will not prejudice or affect any right of action or remedy which has accrued or will accrue thereafter to the Procuring Entity and/or the Supplier.

25. Termination for Convenience

- 25.1. The Procuring Entity may terminate this Contract, in whole or in part, at any time for its convenience. The Head of the Procuring Entity may terminate a contract for the convenience of the Government if he has determined the existence of conditions that make Project Implementation economically, financially or technically impractical and/or unnecessary, such as, but not limited to, fortuitous event(s) or changes in law and national government policies.
- 25.2. The Goods that have been delivered and/or performed or are ready for delivery or performance within thirty (30) calendar days after the Supplier's receipt of Notice to Terminate shall be accepted by the Procuring Entity at the contract terms and prices. For Goods not yet performed and/or ready for delivery, the Procuring Entity may elect:
 - (a) to have any portion delivered and/or performed and paid at the contract terms and prices; and/or
 - (b) to cancel the remainder and pay to the Supplier an agreed amount for partially completed and/or performed goods and for materials and parts previously procured by the Supplier.

25.3. If the Supplier suffers loss in its initial performance of the terminated contract, such as purchase of raw materials for goods specially manufactured for the Procuring Entity which cannot be sold in open market, it shall be allowed to recover partially from this Contract, on a *quantum meruit* basis. Before recovery may be made, the fact of loss must be established under oath by the Supplier to the satisfaction of the Procuring Entity before recovery may be made.

26. Termination for Unlawful Acts

- 26.1. The Procuring Entity may terminate this Contract in case it is determined *prima facie* that the Supplier has engaged, before or during the implementation of this Contract, in unlawful deeds and behaviors relative to contract acquisition and implementation. Unlawful acts include, but are not limited to, the following:
 - (a) Corrupt, fraudulent, and coercive practices as defined in **ITB** Clause **Error! Reference source not found.**;
 - (b) Drawing up or using forged documents;
 - (c) Using adulterated materials, means or methods, or engaging in production contrary to rules of science or the trade; and
 - (d) Any other act analogous to the foregoing.

27. Procedures for Termination of Contracts

- 27.1. The following provisions shall govern the procedures for termination of this Contract:
 - (a) Upon receipt of a written report of acts or causes which may constitute ground(s) for termination as aforementioned, or upon its own initiative, the Implementing Unit shall, within a period of seven (7) calendar days, verify the existence of such ground(s) and cause the execution of a Verified Report, with all relevant evidence attached;
 - (b) Upon recommendation by the Implementing Unit, the Head of the Procuring Entity shall terminate this Contract only by a written notice to the Supplier conveying the termination of this Contract. The notice shall state:
 - (i) that this Contract is being terminated for any of the ground(s) afore-mentioned, and a statement of the acts that constitute the ground(s) constituting the same;
 - (ii) the extent of termination, whether in whole or in part;
 - (iii) an instruction to the Supplier to show cause as to why this Contract should not be terminated; and
 - (iv) special instructions of the Procuring Entity, if any.
 - (c) The Notice to Terminate shall be accompanied by a copy of the Verified Report;
 - (d) Within a period of seven (7) calendar days from receipt of the Notice of Termination, the Supplier shall submit to the Head of the Procuring Entity a verified position paper stating why this Contract should not be terminated. If the Supplier fails to show cause after the lapse of the seven

- (7) day period, either by inaction or by default, the Head of the Procuring Entity shall issue an order terminating this Contract;
- (e) The Procuring Entity may, at any time before receipt of the Supplier's verified position paper described in item (d) above withdraw the Notice to Terminate if it is determined that certain items or works subject of the notice had been completed, delivered, or performed before the Supplier's receipt of the notice;
- (f) Within a non-extendible period of ten (10) calendar days from receipt of the verified position paper, the Head of the Procuring Entity shall decide whether or not to terminate this Contract. It shall serve a written notice to the Supplier of its decision and, unless otherwise provided, this Contract is deemed terminated from receipt of the Supplier of the notice of decision. The termination shall only be based on the ground(s) stated in the Notice to Terminate;
- (g) The Head of the Procuring Entity may create a Contract Termination Review Committee (CTRC) to assist him in the discharge of this function. All decisions recommended by the CTRC shall be subject to the approval of the Head of the Procuring Entity; and
- (h) The Supplier must serve a written notice to the Procuring Entity of its intention to terminate the contract at least thirty (30) calendar days before its intended termination. The Contract is deemed terminated if it is not resumed in thirty (30) calendar days after the receipt of such notice by the Procuring Entity.

28. Assignment of Rights

The Supplier shall not assign his rights or obligations under this Contract, in whole or in part, except with the Procuring Entity's prior written consent.

29. Contract Amendment

Subject to applicable laws, no variation in or modification of the terms of this Contract shall be made except by written amendment signed by the parties.

30. Application

These General Conditions shall apply to the extent that they are not superseded by provisions of other parts of this Contract.

SECTION V SPECIAL CONDITIONS OF THE CONTRACT

GCC Clause	
1.1(g)	The Procuring Entity is <i>Batangas State University</i>
1.1(i)	The Supplier is
1.1(j)	The Funding Source is:
	The Government of the Philippines (GOP) through the <i>Approved Budget</i> in the amount of <i>One Million Four Hundred Eighty Thousand Two Hundred Fifty Pesos Only (Php 1,480,250.00).</i>
1.1(k)	The Project Site is
	Batangas State University Various Offices/Campuses
5.1	The Procuring Entity's address for Notices is:
	Dr. Tirso A. Ronquillo
	University President Batangas State University
	International Affairs Office, GPB Main Campus I
	Batangas City
	The Supplier's address for Notices is:
6.2	Delivery and Documents -
	The delivery terms applicable to this Contract are delivered to Batangas State University . Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination.
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI. Schedule of Requirements. The details of shipping and/or other documents to be furnished by the Supplier are as follows:
	For Goods supplied from within the Philippines:
	Upon delivery of the Goods to the Project Site, the Supplier shall notify the Procuring Entity and present the following documents to the Procuring Entity:
	(i) Original and copies of the Supplier's invoice showing Goods' description, quantity, unit price, and total amount;
	(ii) Original and copies delivery receipt/note, railway receipt,

or truck receipt;

- (iii) Original Supplier's factory inspection report;
- (iv) Original and copies of the Manufacturer's and/or Supplier's warranty certificate;
- (v) Delivery receipt detailing number and description of items received signed by the authorized receiving personnel;
- (vi) Certificate of Acceptance/Inspection Report signed by the Procuring Entity's representative at the Project Site; and
- (vii) Four copies of the Invoice Receipt for Property signed by the Procuring Entity's representative at the Project Site.

For purposes of this Clause the Procuring Entity's Representative at the Project Site is the Asst. Director for Supply & Property Management Office, **MR. MARIO EBORA.**

Incidental Services -

The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements:

Select appropriate requirements and delete the rest.

- (a) performance or supervision of on-site assembly and/or start-up of the supplied Goods;
- (b) furnishing of tools required for assembly and/or maintenance of the supplied Goods;
- (c) furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
- (d) performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
- (e) training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.

The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

	Patent Rights -
	The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof.
10.4	Not applicable
13.4(c)	No further instructions.
16.1	The inspections and tests that will be conducted are: Checking based on the required specifications.
17.3	One (1) year after acceptance by the Procuring Entity of the delivered Goods.
17.4	The period for correction of defects in the warranty period is <i>fifteen (15) days.</i>
21.1	No additional provision.

SECTION VI

SCHEDULE OF REQUIREMENTS

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of de livery to the project site.

			Days/Weeks
1	 Processor: Intel Core i5-4690 Motherboard: Asus H81M-A Motherboard (Socket 1150) Memory: 2 x 2 GB Kingston DDR3 PCI 1600 (IKvR16N11S6/2) Hard Disk: Seagate 500GB7200RPM 3.5" SATA (ST500DM002) Case: ATX Casing V17 Powerlogic KB/Mouse: A4TECH KRS8520D Black Keyboard Monitor: AOC 18.5" LED E950SWN BLK monitor With AVR 	17 units	30 days
2	 PRINTER (REGISTRAR) Technology: Laser Print sped: up to 30 ppm – B/W – Letter A Size (8.5 x 11) Connectivity Technology: wired Interface: USB, LAN Mas Resolution (B&W): 600 dpi Image Enhancement Technology: FastRes 1200 PostScript Support: Standard First Print Out Time B/W: 8 sec Language Simulation: PCL 5E Fonts Included: TrueType Media Handling: 250-sheet input tray, 50-sheet multipurpose tray Networking Connectivity Technology: wired Data Link Protocol: Ethernet, Fast Ethernet Remote Management Protocol: SNMP Network/Transport Protocol: Bonjour, TCP/IP Processor: 266 MHz Power 	5 units	30 days

- ➤ Control Code: ESC/P and IBM PPDS emulation 3 units

Print Speed

3

- High Speed Draft10/12/15 cpi: 347 / 357 / 390 cps
- ➤ High Speed Draft Condensed17/20 cpi: 383 / 298 cps
- Draft10/12/15 cpi: 260 / 312 / 223 cps
- Draft Condensed17/20 cpi: 222 / 260 cps

- Draft Emphasized10 cpi: 130 cps
- NLQ10/12/15/17/20 cpi: 65 / 78 / 55 / 47 / 56 cps

• Print Characteristics

- Character Sets: Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15
- Bitmap Fonts: Epson Draft: 10, 12, 15 cpi;
 Epson Roman & San Serif: 10, 12, 15 cpi,
 Proportional; Epson Courier: 10, 12, 15 cpi;
 Epson Prestige: 10, 12 cpi; Epson Script, OCR-B, Orator & Orator-S: 10cpi; Epson Script C: Proporational
- Barcode Fonts: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet

• Printable Columns

Pitch10/12/15/17/20 cpi: 80 / 96 / 120 / 137 / 160 cpl

Paper Handling Paper Path

- > Tractor: Rear in, Top out
- > Manual Insertion: Rear in, Top out
- Cut Sheet (Single Sheet): 100 364mm

(3.9 - 14.3")100 -

257mm

(3.9 - 10.1")0.065 -

0.14mm

(0.0025 - 0.0055")

Cut Sheet (Multi Part): 100 - 364mm

(3.9 - 14.3")100 - 257mm (3.9 - 10.1")0.12 - 0.39mm (0.0047 - 0.015") (Total)

Envelope (No.6): 92mm

(3.6")165mm (6.5")0.16 - 0.52mm (0.0063 - 0.0205") (Total)

Envelope (No.10): 105mm

(4.1")241mm (9.5")0.16 - 0.52mm (0.0063 - 0.0205") (Total)

Continuous Paper (Single Sheet an Multi part):

101.6 - 558.8mm (4.0 - 22.0")101.6 - 254.0mm (4.0 - 10.0")0.065 - 0.39mm (0.0025 - 0.015") (Total)

➤ Roll Paper: 216mm

(8.5")0.07 - 0.09mm (0.0025 - 0.0035")

 Paper Feeding Standard: Friction, Push Tractor Optional: Roll Paper Holder Copies: Original + 4 copies 	
Optional: Roll Paper Holder	
Copies: Original + 4 copies	
PRINTER (REGISTRAR-ROSARIO)	
I KINTER (REGISTRANC ROSARTO)	
Print Speed Black:	
➤ Normal: Up to 30 ppm	
First page out (ready)	
➤ Black: As fast as 8.0 sec	
Print Quality Black (best)	
> Up to 600 x 600 dpi effective output with HP	
FastRes 1200)	
Tustites 1200)	
Duty Cycle: Up to 25,000 pages	
Recommended monthly page volume: 500 to 2500	
Print Technology: Laser	
Processor Speed: 2660MHz	
Print Languages: Host Based, UPD	
Connectivity, standard	
Hi-Speed USB 2.0, IEEE 1284-compliant parallel	
Minimum System requirements:	
➤ Microsoft®Windows®2000, XP Home, XP	
Professional, Server 2003: 512 MB RAM	
> 350 MB available Hard Disk Space	
Windows Vista®, 32/64:512 MB RAM, 350	
4 MB available hard disk space, CD-ROM Drive, 1 unit 30 days	S
USB port	
➤ Mac OS x v10.3.9, v10.4.3, v10.5	
> 128 MB RAM minimum (256 MB	
recommended), 150 MB available hard disk	
space, CD-ROM Drive	
• USB port	
Mac OS X v 10.3.9, v 10.4.3, v10.5	
> 128 MB RAM minimum (256 recommended),	
150 MB available hard disk space	
Compatible operating System Normal Column 1	
Microsoft®Window®2000, XP Home, XP	
Professional, XP Professional x 64, Server	
2003, NT 4.0 (PCL5 driver on web only) Windows Vista®, x 64	
> Mac OS X 10.3.9, v10.4.3, v10.5	
Mac O3 X 10.3.9, V10.4.3, V10.3 Linux	
> UNIX	
Paper Handling	
Paper handling input, standard: 250-sheet	
input tray, 50-sheet multipurpose tray	
Paper handling output, standard: 150-sheet	
output bin	
Maximum output capacity (sheets): Up to 150	
Duplex printing: Manual (driver support	
provided)	

Bidding Doo	cuments (l	Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	•	
		Media Sizes supported:		
		Tray 1: A4, A5, A6, B5, envelopes (C5,		
		B5, DL)		
		→ Tray 2: A4, A5, A6		
		Media sizes, custom		
		→ Tray 1: 76 x 127 to 216 x 356mm		
		→ Tray 2: 105 x 148 to 216 x 356mm		
		Media Types: Paper (bond, light, heavy, plain,		
		recycled, rough), envelopes, labels, cardstock,		
		transparencies, heavy media		
	•	Supported media weight ➤ Tray 1: 60 to 163 g/m² (straight through		
		paper path for special media)		
		> Tray 2: 60 to 120 g/m ²		
		7 11 d		
	PRINT	ER (ROSARIO CAMPUS)		
		· ·		
	•	Functions: Print, Copy, Scan, Fax		
	•	Printing Specifications		
		Print Speed Black		
		→ ISO: Up to 7 ppm		
		→ Draft: Up to 20 ppm		
		> Print speed color		
		→ ISO: Up to 4 ppm→ Draft: Up to 16 ppm		
		First page out (ready)		
		→ Black: As fast 17 sec		
		Color: As fast 24 sec		
		Duty Cycle (monthly,A4): Up to 1000 pages		
		Recommended monthly page volume: 300 to		
		400		
		Print technology: Thermal Inkjet		
		Print quality (best):		
5		Color: Up to 4800 x 1200 optimised dpi colour	1	
3		(when printing from a computer on selected HP photo papers and 1200 input dpi)	1 unit	
		Black: Up to 600 x 600 rendered dpi		
		Display: 5 cm (2.0 in) Hi-Res Mono LCD		
		> Processor speed: 360 MHz		
		Number of print cartridges: 2 (1 black, 1 Tri-		
		color)		
	•	Connectivity, standard: Hi-Speed USB		
	•	Memory Specifications:		
		Memory, standard: 32 MB SDRAM		
		> Memory, maximum: 32 MB SDRAM		
	•	Paper handling		
		Paper handling input, standard: 60-sheet input		
		tray		
		➤ Paper handling output, standard: 25-sheet		
		output tray		
		Media sizes supported: A4, B5, A6, DL		
		envelope		
		envelope	<u> </u>	

bluullig Do	cuments (Based on Revised IKR of RA 9184, Fourth Edition, December	er 2010)
	➤ Media sizes custom: 100 x 148 to 216	x 356
	mm	
	Media types: Paper (brochure, inkjet, j	plain),
	photo paper, envelopes, labels, cards	
	(greeting)	
	Barcode scanner: 20 lb	
	• Scanner	
	Scanner type: Flatbed, ADF	
	Scan file format: PDF, BMP, PNG, TIF, J	JPG
	Scan resolution, optical: Up to 1200 dp	pi
	➤ Bit depth: 24-bit	
	Scan size (flatbed), maximum: 216 x 2	.97 mm
	Scan size (ADF), maximum: 216 x 356	mm
	Automatic document feeder capacity:	
	Standard, 35 sheets	
	Scan input modes: Front-panel scan, c	copy, fax,
	or from software	
	Copy resolution (black text): 600 x 300 dp	oi l
	 Copy resolution (color text and graphics): 	: 600 x
	300 dpi	
	• Copy reduce / enlarge settings: 25 to 400 ^o	%
	Copies, maximum: Up to 50 copies	
	SCANNER (REGISTRAR-LIPA)	
	Scanner Type: Flatbed	
	 Scanning Element: Contact Image Sensor ((CIS)
	Light Source: Three-color (RGB) LED	
	• Features: 5 EZ Buttons, Advanced Z-lid, Au	
	& Scratch Reduction, Auto Document Fix, Scan Mode, Backlight Correction, Conveni	
	Filing Function (PDF Function), Digital Fil	
	Fading Correction, Grain Correction, Gutte	
	Shadow Correction, High-Speed Scanning,	
6	Power Consumption, One Cable for Data 8 Vertical Scanning	& Power, 1 unit 30 days
	 Scanner Buttons: Auto Scan, Copy, PDF (x) 	2), E-
	mail	
	• Scanning Mode:	tornal
	Color: 48-bit internal/48- or24-bit extGrayscale: 16-bit input/8-bit external	
	• Max. Document Size: 8.5" x 11.7"	
	• Interface: Hi-Speed USB	(D) v
	• Dimensions (W x D x H): 9.9" (W) x 14.4" (1.6" (H)	(D) X
	Weight: 3.4 Ibs	

Blading Documents	s (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
•	OS Compatibility: Windows® 7, Windows Vista®,		
	Windows XP/2000 and Mac OS® X v.10.4.1-10.6		
	Software: Setup Software & User's Guide CD-ROM		
	MP Navigator EX; Solution Menu		
	9		
•	Power Source: Hi-Speed USB		
•	Max. Power Consumption: 2.5W (1.4W Standby)		
•	Operating Temperature: 41° - 95°F		
•	Operating Humidity: 10% - 90% RH		
PRIN	TER (College of Industrial Technology and OSAS)		
•	Print Method: On demand ink jet		
•	Nozzle Configuration: 180 nozzles Black, 59		
	nozzles each colour (Cyan, magenta, Yellow)		
	Print Direction: Bi-directional printing, Uni-		
	directional printing		
	Maximum Resolution: 5760 x 1440 dpi (With		
•			
	Variable-Sized Droplet Technology)		
•	Maximum Ink Droplet Volume: 3pl		
•	Print Speed		
	Max Black Draft Text – Memo (A4): Approx. 27		
	ppm / 15 ppm (Bk/Cl)		
	➤ ISO 24734, A4: Approx. 6.0 ipm/3.0 ipm		
	(Bk/Cl)		
	Max photo Draft – 10x15cm/4x6" – Approx. 27		
	sec per photo (W/Border)		
	Photo Default – 10x15cm/4x6" – Approx. 69		
	sce per photo (W/Border)		
•	Copying		
_	Max. Black Draft Text – Memo (A4) – Approx. 5		
7	500 (21410)	5 units	30 days
	Max. Colour Draft Text - Memo (A4) - Approx.		
	10 sec (Draft)		
	Copy Mode: Standard copy mode		
	Maximum Copies From Standalone: 20 sheets		
	(fixed)		
	Scanning		
	Scanner Type: Flatbed colour image scanner		
	Sensor Type: CIS		
	Optical Resolution: 600 x 1200 dpi		
	Maximum Scan Area: 216 x 297mm (8.5 x		
	11.7)		
	> Scanner Bit Depth		
	Colour: 48-bit internal, 24-bit external		
	Grayscale: 16-bit internal, 8-bit external		
	→ Black & White: 16-bit internal, 1-bit		
	external		
•	Scan Speed		
	➤ Monochrome 300 dpi: 2.4 msec/line		
	Colour 300 dpi: 9.5 msec/lime		
	Monochrome 600 dpi: 7.2 msec/line		
	Colour 600 dpi: 14.3 msec/line		
	, colour ood upi. 17.3 msec/mie		

	PRINTER (ICT)		
8	 Print Speed Black (Normal): Up to 33 ppm Print quality Black (Best): Up to 1200 x 1200 dpi Duty Cycle (monthly, A4): Up to 50,000 pages Print Technology: Laser Processor Speed: 800 Mhz Display: 2-line LCD (text and graphics) Connectivity, standard: 1 Hi-Speed USB 2.0 1 Ethernet 10/100/1000T network Network Ready: Standard (built-in Gigabit Ethernet) Minimum system requirements: Windows 8, Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit): 1 Ghz 32-bit (x86) or 64-bit (x64) processor, 1 GB RAM (32-bit) or 2 GB RAM (64-bit), 400 MB free hard disk space, CD/DVD ROM or Internet, USB or Network port Windows XP (32-bit) SP2: Pentium® 233 MHz processor, 512 MB RAM, 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Netwrok port MAC OS X v 10.5, v 10.6, 10.7 PowerPC G4, G5, or Intel® Core™ Processor 500 MB Hard Disk CD-ROM/DVD-ROM or Internet USB or Network Paper Handling input, standard: 50-sheet multipurpose tray 1, 250-sheet input tray 2 Paper handling output, standard: 150-sheet output bin Maximum output capacity (sheets): Up to 150 sheets Duplex printing: Manual (driver support provided) Media sizes supported: A4, A5, A6, B5(JIS) Media sizes (custom): Multipurpose tray: 76 x 127 to 216 x 356mm Tray 2 and optional 500-sheet tray 3: 105 x 148 to 216 x 356 mm Media types: Paper (plain, Green mode, light, heavy, bond, color, letterhead, preprinted, prepunched, recycled, rough), envelopes, labels Supported media weight: Tray 1: 60 to 163 g/m² (straight through paper path for special media) 		30 days
	Tray 2: 500 sheet Tray 3: 60 to 120 g/m²		
	PRINTER (GENERAL ENGINEERING)		
9	 Print Method: On-demand ink jet Nozzle Configuration: 180 nozzles Black, 59 nozzles each colour (Cyan, Magenta, Yellow) 	1 unit	30 days

- Print Direction: Bi-directional printing, Unidirectional printing
- Maximum Resolution: 5760 x 1440 dpi (with Variable-Sized Droplet Technology)
- Minimum Ink Droplet Volume: 3pl

• Print Speed

- Max Black Draft Text Memo (A4): Approx.33 ppm / 15 ppm (Bk/Cl)
- ➤ ISO 24734, A4: Approx. 9.0 ipm / 4.5 ipm (Bk/Cl))
- Max Photo Draft 10x15cm/4x6": Approx. 27 sec per photo (W/Border)
- Photo Default 10x15cm/4x6": Approx. 69 sec per photo (W/Border)
- Double-sided Printing: Yes (Manual)

Copying

Copy Speed

- Max. Black Draft Text Memo (A4): Approx. 5 sec (Draft)
- Max. Colour Draft Text Memo (A4): Approx. 10 sec (Draft)
- > Copy Mode: Standard copy mode
- Maximum Copies From Standalone: 20 sheets (fixed)

Scanning

- Scanner Type: Flatbed colour image scanner
- > Sensor Type: CIS
- Optical Resolution: 600 x 1200 dpi
- Maximum Scan Area: 216 x 297mm (8.5 x 11.7")
- Scanner Bit Depth
 - → Colour: 48-bit internal, 24-bit external
 - → Grayscale: 16-bit internal, 8-bit external
 - → Black & White: 16-bit internal, 1-bit external
- Scan Speed
 - → Monochrome 300 dpi: 2.4 msec/line
 - → Colour 300 dpi: 9.5 msec/line
 - → Monochrome 600 dpi: 7.2 msec/line
 - Colour 600 dpi: 14.3 msec/line

Paper Handling

- Paper Feed Method: Friction feed
- Number of Paper Trays: 1
- Paper Hold Capacity
 - Input Capacity: 100 sheets, A4 Plain paper (75g/m2)
 - 20 sheets, Premium Glossy Photo Paper
 - Output Capacity: 30 sheets, A4 Plain paper
 20 sheets, Premium Glossy Photo Paper

Connectivity

Standard: USB 2.0 Hi-Speed

Printer Software

Operating System Compatibility: Windows XP/XP Professional x64 Edition/Vista/7 Mac OS X 10.5.8, 10.6.x, 10.7.x

 LAPTOP (VPRDE) Operating System: Windows 8 Processor: Intel®Core™i5 Processor 3317UM (1.7 Ghz, 3MB L3 Cache) LCD Display: 13.3" Super Bright 300 nit HD LED Display (1,366 x 768), Anti-Reflect Graphic Processor: Table System Memory: 4GB DDR3 System Memory at 1,600 Mhz (on BD 4GB) Memory Slot: 1 DIMM Slots HDD Storage: 500 GB S-ATA All Slim Hard drive (5,400 RPM) with Express Cache 2 Multimedia: Sound: HD Audio
 Processor: Intel®Core™i5 Processor 3317UM (1.7 Ghz, 3MB L3 Cache) LCD Display: 13.3" Super Bright 300 nit HD LED Display (1,366 x 768), Anti-Reflect Graphic Processor: Table System Memory: 4GB DDR3 System Memory at 1,600 Mhz (on BD 4GB) Memory Slot: 1 DIMM Slots HDD Storage: 500 GB S-ATA All Slim Hard drive (5,400 RPM) with Express Cache 2 Multimedia:
> Sound Effect: Mic Noise Suppression SoundAlive™ > Speaker: 4 watts Stereo Speaker (2 watts x 2) > Integrated Camera: 1.3 megapixel HD Webcam • Wired Ethernet LAN: 10/100/1,000 Gigabit Ethernet LAN • Wireless LAN: Intel®Centrino®Advanced-N 6235, 2 x 2 802.11 abg/n (up to 300Mb) • Bluetooth: Bluetooth 4.0 • Port > Headphone Out: Headphone-out/Mic-Combo > Mic-in: Headphone-out/Mic-Combo > WSB: 1 USB 3.0, 2 USB 2.0 > Mulkti Card Slot: 4-in-1 (SD, SDHC, SDXC, MMC) • Keyboard: 81 Key 80 Key • Touch Pad, Touch Screen: Touch Pad (Scroll Scope, Flat Type, Gesture UI) • AC Adapter: 40 watts • Standard Battery: 4 Cell (45 Wh) • Standard DVD: OS DVD Universal Printer/ Scanner Driver Easy File Share Easy Migration Adobe Acrobat Reader Microsoft Office Starter 2010 Support Center • Installed S/W: Windows Live Anti-Virus Easy Settings Software Launcher Intel®Anti-Theft Technology Intel® Identity Protection Technology

	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	 LAPTOP (ON-THE-JOB TRAINING OFFICE) Intel Core i5-4200U 1.6 Ghz Haswell 4GB DDR3 500 GB HDD DVD writer 		
11	 14" Active Matrix TFT Colour LCD HD 1366 x 768 LED Backlit Intel HD Graphics Wifi Gigabit LAN 	1 unit	
	Webcam MicHDMIUSB 3.04 Hour Battery Life		
	LAPTOP (ICT)		
12	 15.6" HD Intel-Core i7-5500U/8Fb/1Tb/2Gb GeForce 940 M/Windows 8.1 Processor: Intel Core i7-5500U processor (4M Cache, up to 3.00 Ghz) Operating System: Windows 8.1 Memory: 8 GB DDR3L 1600 Mhz SDRAM Display: 15.6" 16:9 HD (1366 x 768) Display Graphic: 2 GB NVIDIA GeForce 940M DDR3 VRAM Storage: 1TB HDD Optical Drive: Super-Multi DVD Card Reader: 3 - in 1 card reader (SD/SDHC/SDXC) Camera: VGA web Camera Networking: Integrated 802.11 b/g/n Built-in Bluetooth™ V4.0 10/100/1000 Base T Interface: 1 X COMBO audio jack 1 X VGA port/Mini D-sub 15-pin for external monitor 2 X USB 3.0 port (s) 1 X USB 2.0 port 1 X RJ45 LAN Jack for LAN insert 1 X HDMI 1 X SD card reader Audio: Built-in Speakers And Microphone Battery: 2 Cells 37 Whrs Polymer Battery Power Adapter → Output: 19 V DC, 3.42 A, 65 W → Input: 100-240 V AC, 50/60 Hz universal Dimensions: 38.2 x 25.6 x 2.58 cm (WxDxH) Weight: 2.3 kg (with Polymer Battery) Security: Kensington lock BIOS Booting User Password Protection HDD User Password Protection and Security 	2 sets	30 days

	APTOP (EXTENSION)		
13	 Color: White/Silver Quad Core Ultrathin Operating System: Windows 8 Pro Screen Size: 13.3 /14" HD LED Display (1366 x 768), Anti Reflective Processor: Quad-Core Processor (up to 1.4 Ghz) Graphics: AMD radeon HD Graphics Memory: 4GB DDR3L System Memory at 1066 MHz (on BD 4GB) Storage: 500 GB Solid-state Drive Connectivity: 802.11 bg/n 1 x 1 Bluetooth v4.0 Gigabit Ethernet (10/100/1000) Camera: 720p HD Web Camera Battery: 2-cell Battery Power Consumption: 220V, 40W With Laptop Bag, Mouse, Mouse Pad, Laptop Screen Protector, Cooling Pad and 1TB External Drive 	1 unit	30 days
	 6-PORT FAST ETHERNET UNMANAGED DESKTOP WITCH Inexpensive Fast Ethernet solution for SOHO/SMB Auto MDI/MDIX crossover for all ports Store-and-forward switching scheme Full/half-duplex for Ethernet/Fast Ethernet speeds IEEE 802.3x Flow Control Plug-and-play installation Switching Fabric: 3.2 Gpbs Standards: IEEE 802.3 10BASE-T Ethernet (twistedpair copper) IEEE 802.3u 100 BASE-TX Fast Ethernet (twisted-pair copper) ANSI/IEEE 802.3 NWay Auto-Negotiation IEEE 802.3z Flow Control IEEE 802.3az EEE function Protocol: CSMA/CD Data Transfer Rates Ethernet: 100 Mbps (half duplex) 200 Mbps (full duplex) Fast Ethernet: 100 Mbps (half duplex) 200 Mbps (full duplex) Number of ports: 16 10/100 Mbps fast Ethernet ports Topology: Star Network Cables 10BASE-T: UTP CAT 3/4/5/5e (100 m max.) EIA/TIA-586 100-ohm STP (100 m max.) EIA/TIA-586 100-ohm STP (100 m max.)	5 units	30 days

Batangas State Univ Bidding Documents	versity s (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	→ UTP CAT 5/5e (100 m max.)		
	→ EIA/TIA-568 100-ohm STP (100 m max.)		
	,		
•	Media Interface Exchange: Auto MDI/MDIX		
	adjustment for all ports		
•	LED Indicators		
	Per port: Link/Activity		
	Per device: Power		
•	Transmission Method: Store-and-forward		
•	MAC Address Table: 8K entries per device		
•	MAC Address Learning: Automatic update		
•	Packet Filtering /Forwarding Rates (half		
	duplex)		
	Ethernet: 14,880 pps per port		
	Fast Ethernet: 148,800 pps per port		
•	RAM Buffer: 256 Bytes (2M bits)		
•	Power Input: 100~240 V AC 50/60 Hz internal		
	universal power supply		
•	Power Consumption		
	Power On (Standby): DC input: 0.61 Watts		
	AC input: 1.19 Watts		
	Max.: DC input: 1.55 Watts		
	AC input: 2.89 Watts		
•	Heat Dissipation		
	Power On (Standby): AC input: 4.06 BTU/h		
	Maximum: AC input: 9.86 BTU/h		
•	MTBF: 2,266,559 hours		
•	Operating Temp.: 0° to 40°C (32 ° to 104 °F)		
•	Storage Temp.: -10 ° to 70 °C (14 ° to 158 °F)		
•	Operating Humidity: 10% to 90% RH non-		
	condensing		
•	Storage Humidity: 5% to 90% RH non-		
	condensing		
	Director of one (III D II) - 200 125 0 44		
•	Dimensions (W x D x H): 280 x 125.8 x 44 mm		
	$(11.0 \times 5.0 \times 1.7 \text{ inches})$		
	Certificationsf		
	FCC Class A		
	> ICES-003 Class A		
	CE Class A		
	C-Tick Class A		
	> VCCI Class A		
	> cUL		
	> LVD		
MUL'	TIMEDIA PROJECTOR (ICT)		
15		1 unit	30 days
•	Aspect Ratio: 16:10 (Native) 4:3, 16:9		50 44,5
•	Brightness (ANSI Lumens): 1000 ANSI lumens		
•	Contrast Ratio: 10000:1		

Blading Doc	uments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	_	
	Display Type: DLP		
	Resolution (Native/Max): WXGA (1280 x 800)		
	HD (1920 X 1080)		
	• Video Compatibility: PAL, SECAM, NTSC, HDTV		
	(480i, 480p, 576i, 576p, 720p, 1080i)		
	• Projection Lens: F=1.5		
	• Number of colors: 1.07 Billion Colors		
	• Dimension (WxHxD): 8.7 in. x 1.7 in. x 6.7 in. (22.1		
	cm x 4.32 cm x 17.02 cm) • Weight: 2.6 lbs (1.18 kg)		
	Weight: 2.6 lbs (1.18 kg)Connectivity		
	➤ Inputs: 1 x HDMI		
	1 x VGA D-Sub 15pin		
	1 x Composite		
	1 x Stereo Mini Jack		
	1 x USB Type A		
	Outputs: 1 x Stereo Mini Jack		
	Audio: 1 x 3W Mono Speaker		
	Control: 1 x USB Type B		
	 Power Supply: 100~220V / 50-60 Hz 		
	 Projection Lens 		
	Lamp Type: Laser/LED		
	Lamp Life: 20000 hrs (Normal)		
	30000 hrs (Eco mode)		
	Projection Distance: ft. ~ 3.0 ft. (0m ~ 0.91 m)		
	Projection Mode: Front, Rear, Ceiling		
	Projection Screen Size: (Diagonal)		
	30in.~100in. (76.2cm~254cm)		
	Digital Zoom: 1.7x		
	Vertical Keystone Correction: +/- 40 DegreesH-Sync Range: 100 KHz		
	V-Sync Range: 120 Hz		
	V-Sylic Range. 120 Hz		
	PROJECTOR (VPRDE)		
	Native Aspect Ratio: 4x3		
	Technology: DLP Response (200)		
	• Resolution: SVGA(800x600)		
	• Lumens (Eco/High): 2800/3000		
	• Contrast: 15000		
	3D: Supports 3D content from Blu-ray, cable bayes dish services and many (aver HDM) at		
16	boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP	1 unit	20 days
16	Link 3D glasses required.	1 unit	30 days
	 Closed Captioning: Yes 		
	Speakers: 2W (1 x 2W)		
	Audible Noise (Eco/High, dBA): 29/30		
	Keystone: ± 40°		
	• Lamp: SP-LAMP-086		
	 Lamp Hours (Eco/High): 10000/5000 		
	 Connections: HDMI 1.4, VGA x 2, Composite video 		
	S-Video, 3.5 mm stereo in x 2, 3.5mm stereo out,		
	RS232C		

	cuments (Based on Revised IKK of KA 9184, Fourth Edition, December 2010)		 ,
	 Image Offset: 15 Lens Shift: Horz (min/max): None Lens Shift: Vert (min/max): None Throw Ratio: 2.2~1.9 Weight(lbs/kg): 5.4/2.5 Product Dimensions HxWxD: 8.7in x 11.5in x 4.7in (220mm x 292mm x 121mm) Shipping Weight(lbs/kg): 7.1/3.2 		
17	 PROJECTOR (ON-THE-JOB TRAINING OFFICE) WXVGA (1280 x 800) UXGA (1,600 x 1,200), 1080p (1,920 x 1,080) 16:10 (Native), 4:3, 16:9 Contrast Ratio at 4000:1 1.07 Billion Colors 500 ANSI Lumens (Standard) 350 ANSI Lumens (ECO) USB and HDMI port LED Life 20,000 Hours Remote One Internal Speaker with 2 watts Output 2.73 Ibs (1.24 kg) 	1 unit	30 days
18	 PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 Technology: DLP Resolution: SVGA(800x600) Lumens (Eco/High): 3200/3500 Contrast: 15000 3D: Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP Link 3D glasses required. Closed Captioning: Yes Speakers: 2W (1 x 2W) Audible Noise (Eco/High, dBA): 30/32 Keystone: ± 40° Lamp Hours (Eco/High): 5000/3500 Connections: HDMI 1.4, VGA x 2, USB-A (for USB thumb drive or wireless network adapter), USB Mini-B (for display over USB & internal memory file mgmt), Composite Video, S-Video, 3.5 mm stereo in x 2, RS232, USB-B (control & firmware), VGA monitor out, 3.5mm audio out Image Offset: 15 	9 units	30 days

	Throw Ratio: 2.2~1.9 Weight(lbs/kg): 7/3.2 Product Dimensions HxWxD: 8.7in x 11.5in x		
	 4.3in (220mm x 292mm x 108mm) Shipping Weight(lbs/kg): 8.1/3.7 Shipping Dimensions HxWxD: 12in x 14.25in x 7.75in (305mm x 362mm x 197mm) Product Warranty: 1 Year Lamp Warranty: 6 months 		
	PROJECTOR (CICS)		
19	 Native Aspect Ratio: 4:3 Technology: DLP Resolution: SVGA (800x600) Lumens (Eco/High): 3200/3500 Contrast: 15000 3D: Supports 3D content form Blu-ray, clable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP Link 3D glasses required Closed Captioning: Yes Speakers: 2W (1 x 2W) Audible Noise (Eco/High dBA): 30/32 Keystone ±40° Lamp Hours: 5000/3500 	2 units	30 days
20	 Wireless 802.11 b/g/n and 802.3ab gigabit LAN support Transfers computer content to a project/monitor wirelessly Features Quarter View, Direct Show, and a WPS Button Multiple video format support (codec installation needed) Infrared remote control included Simultaneous content projection and web surfing Supports Windows XP/Vista/7 and Mac OS (10.4 & 10.5 only) 	1 unit	30 days
21	Hard Drive (ICT) ● 2TB	2 units	30 days

SECTION VII TECHNICAL SPECIFICATIONS

Item No.		QTY.	STATEMENT OF COMPLIANCE	
	Specifications		Comply/Not Comply	
1	DESKTOP COMPUTER		s 30 days	
	 Processor: Intel Core i5-4690 Motherboard: Asus H81M-A Motherboard (Socket 1150) Memory: 2 x 2 GB Kingston DDR3 PCI 1600 (IKvR16N11S6/2) Hard Disk: Seagate 500GB7200RPM 3.5" SATA 	17 units		
	 (ST500DM002) Case: ATX Casing V17 Powerlogic KB/Mouse: A4TECH KRS8520D Black Keyboard Monitor: AOC 18.5" LED E950SWN BLK monitor With AVR 			
	PRINTER (REGISTRAR) • Technology: Laser			
2	 Print sped: up to 30 ppm – B/W – Letter A Size (8.5 x 11) Connectivity Technology: wired Interface: USB, LAN Mas Resolution (B&W): 600 dpi Image Enhancement Technology: FastRes 1200 PostScript Support: Standard First Print Out Time B/W: 8 sec Language Simulation: PCL 5E Fonts Included: TrueType Media Handling: 250-sheet input tray, 50-sheet multipurpose tray Networking Connectivity Technology: wired Data Link Protocol: Ethernet, Fast Ethernet Remote Management Protocol: SNMP Networking: Print Server – integrated Network/Transport Protocol: Bonjour, TCP/IP Processor: 266 MHz 	5 units	30 days	
	 Processor: 266 MHz Power Type: power supply 			

	 ➢ Frequency Required: 60 Hz ➢ Power Consumption Operational: 550 Watt ➢ Power Consumption Standby/Sleep: 7 Watt ➢ Software Included: Drivers and Utilities OS Required: Apple MAcOS X 10.3.9, Novell Netware, UNIX, Apple MacOS x 10.4.3, Apple MacOS X 10.5x, Microsoft Windows 2000, Microsoft Windows Server 20013, Microsoft Windows Vista, Microsoft Windows XP Home Edition, Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition RAM Installed (Max) − 16MB / 16 MB (max) Max Supported Size: 16 Mb Manufacturer Warranty: Service and support (1 year warranty) Environmental Parameters: ➢ Minimum Operating Temperature: 63.5°F ➢ Maximum Operating Temperature: 77°F ➢ Humidity Range Operating: 30-70% Media Handling ➢ Media Type: Bond Paper, Cards, Envelopes, Glossy Paper, Labels, Plain Paper, Recycled Paper, Transparencies ➢ Max Media Size (Custom): 8.5 x 14 in ➢ Envelope Sizes: Com-10 (4.13 in x 9.5 in), Monarch (3.87 in x 7.5 in) ➢ Total Media Capacity: 300 sheets ➢ Media Feeders 1 x autoload – 50 sheets – Letter A Size (8.5 in x 11 in) 1 x autoload – 250 sheets – Letter A Size (8.5 in x 11 in) A under Capacity: 150 sheets Media Sizes: Letter A Size (8.5 x 11 in), Legal (8.5 in x 14 in), Executive (7.25 in x 10.5 in) Monthly Duty Cycle (max): 25,000 pages
PR 3	 Printing Technology Print Method: Impact dot matrix Number of Pins in Head: 9 pins Print Direction: Bi-direction with logic seeking Control Code: ESC/P and IBM PPDS emulation Print Speed High Speed Draft10/12/15 cpi: 347 / 357 / 390 cps High Speed Draft Condensed17/20 cpi: 383 / 298 cps

- > Draft10/12/15 cpi: 260 / 312 / 223 cps
- > Draft Condensed17/20 cpi: 222 / 260 cps
- > Draft Emphasized10 cpi: 130 cps
- NLQ10/12/15/17/20 cpi: 65 / 78 / 55 / 47 / 56 cps

• Print Characteristics

- Character Sets: Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15
- ➤ Bitmap Fonts: Epson Draft: 10, 12, 15 cpi; Epson Roman & San Serif: 10, 12, 15 cpi, Proportional; Epson Courier: 10, 12, 15 cpi; Epson Prestige: 10, 12 cpi; Epson Script, OCR-B, Orator & Orator-S: 10cpi; Epson Script C: Proporational
- ➤ Barcode Fonts: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet

• Printable Columns

Pitch10/12/15/17/20 cpi: 80 / 96 / 120 / 137 / 160 cpl

• Paper Handling Paper Path

- > Tractor: Rear in, Top out
- Manual Insertion: Rear in, Top out
- Cut Sheet (Single Sheet): 100 364mm

(3.9 - 14.3")100 -

257mm

(3.9 - 10.1")0.065 -

0.14mm

(0.0025 - 0.0055")

Cut Sheet (Multi Part): 100 - 364mm

(3.9 - 14.3")100 - 257mm (3.9 - 10.1")0.12 - 0.39mm (0.0047 - 0.015") (Total)

Envelope (No.6): 92mm

(3.6")165mm

(6.5")0.16 - 0.52mm

(0.0063 - 0.0205") (Total)

Envelope (No.10): 105mm

(4.1")241mm

(9.5")0.16 - 0.52mm

(0.0063 - 0.0205") (Total)

Continuous Paper (Single Sheet an Multi part):

101.6 - 558.8mm

(4.0 - 22.0")101.6 - 254.0mm

(4.0 - 10.0")0.065 - 0.39mm (0.0025 - 0.015") (Total)

		N. II D 216	1	l I
		Roll Paper: 216mm (8.5")0.07 - 0.09mm		
		(0.0025 - 0.0035")		
		(0.0023 - 0.0033)		
		Paper Feeding		
		Standard: Friction, Push Tractor		
		Optional: Roll Paper Holder		
		Copies: Original + 4 copies		
		Copies. Original + 1 copies		
	PRINTI	ER (REGISTRAR-ROSARIO)		
		Dwint Coood Dlook.		
	•	Print Speed Black:		
		Normal: Up to 30 ppmFirst page out (ready)		
		Black: As fast as 8.0 sec		
		P Diack. As last as 0.0 sec		
		Print Quality Black (best)		
		> Up to 600 x 600 dpi effective output with HP		
		FastRes 1200)		
		1 0311(63 1200)		
		Duty Cycle: Up to 25,000 pages		
		Recommended monthly page volume: 500 to 2500		
		Print Technology: Laser		
		Processor Speed: 2660MHz		
		Print Languages: Host Based, UPD		
		Connectivity, standard		
		Hi-Speed USB 2.0, IEEE 1284-compliant		
		parallel		
		Minimum System requirements:		
		Microsoft®Windows®2000, XP Home, XP		
4		Professional, Server 2003: 512 MB RAM	1 unit	30 days
		> 350 MB available Hard Disk Space		
		Windows Vista®, 32/64:512 MB RAM, 350		
		MB available hard disk space, CD-ROM Drive,		
		USB port		
		➤ Mac OS x v10.3.9, v10.4.3, v10.5		
		> 128 MB RAM minimum (256 MB		
		recommended), 150 MB available hard disk		
		space, CD-ROM Drive		
	•	USB port		
		Mac OS X v 10.3.9, v 10.4.3, v10.5		
		➤ 128 MB RAM minimum (256 recommended),		
		150 MB available hard disk space		
	•	Compatible operating System		
		Microsoft®Window®2000, XP Home, XP		
		Professional, XP Professional x 64, Server		
		2003, NT 4.0 (PCL5 driver on web only)		
		Windows Vista®, x 64Mac OS X 10.3.9, v10.4.3, v10.5		
		Mac OS X 10.3.9, V10.4.5, V10.5 Linux		
		> UNIX		
		Paper Handling		
		Paper handling input, standard: 250-sheet		
	l	r aper nanuning input, stanuaru. 250-sileet		

			Ī	1
		input tray, 50-sheet multipurpose tray		
		Paper handling output, standard: 150-sheet		
		output bin		
		Maximum output capacity (sheets): Up to 150		
		Duplex printing: Manual (driver support		
		provided)Media Sizes supported:		
		→ Tray 1: A4, A5, A6, B5, envelopes (C5,		
		B5, DL)		
		→ Tray 2: A4, A5, A6		
		> Media sizes, custom		
		→ Tray 1: 76 x 127 to 216 x 356mm		
		→ Tray 2: 105 x 148 to 216 x 356mm		
		Media Types: Paper (bond, light, heavy, plain,		
		recycled, rough), envelopes, labels, cardstock,		
		transparencies, heavy media		
	•	Supported media weight		
		> Tray 1: 60 to 163 g/m ² (straight through		
		paper path for special media)		
		> Tray 2: 60 to 120 g/m ²		
	DDINT	ED (DOCADIO CAMBIIC)		
	PKINI	ER (ROSARIO CAMPUS)		
		Functions: Print, Copy, Scan, Fax		
		Printing Specifications		
		Print Speed Black		
		→ ISO: Up to 7 ppm		
		→ Draft: Up to 20 ppm		
		Print speed color		
		→ ISO: Up to 4 ppm		
		Draft: Up to 16 ppm		
		First page out (ready)		
		→ Black: As fast 17 sec		
		→ Color: As fast 24 sec		
		Duty Cycle (monthly,A4): Up to 1000 pages		
		Recommended monthly page volume: 300 to		
5		400 ➤ Print technology: Thermal Inkjet	1 unit	
		Print technology: Thermal majetPrint quality (best):		
		Color: Up to 4800 x 1200 optimised dpi colour		
		(when printing from a computer on selected		
		HP photo papers and 1200 input dpi)		
		Black: Up to 600 x 600 rendered dpi		
		Display: 5 cm (2.0 in) Hi-Res Mono LCD		
		Processor speed: 360 MHz		
		Number of print cartridges: 2 (1 black, 1 Tri-		
		color)		
	•	Connectivity, standard: Hi-Speed USB		
	•	Memory Specifications:		
		Memory, standard: 32 MB SDRAM		
		Memory, maximum: 32 MB SDRAM		
	_	-		
	•	Paper handling		

			1	į
		Paper handling input, standard: 60-sheet input tray		
		Paper handling output, standard: 25-sheet		
		output tray		
		Media sizes supported: A4, B5, A6, DL		
		envelope		
	>	Media sizes custom: 100 x 148 to 216 x 356		
		mm		
	>	Media types: Paper (brochure, inkjet, plain),		
		photo paper, envelopes, labels, cards		
		(greeting)		
	>	Barcode scanner: 20 lb		
	• Sca	anner		
	>	Scanner type: Flatbed, ADF		
	>	Scan file format: PDF, BMP, PNG, TIF, JPG		
	>	Scan resolution, optical: Up to 1200 dpi		
	>	Bit depth: 24-bit		
	>	Scan size (flatbed), maximum: 216 x 297 mm		
		Scan size (ADF), maximum: 216 x 356 mm		
		Automatic document feeder capacity:		
		Standard, 35 sheets		
		Scan input modes: Front-panel scan, copy, fax,		
		or from software		
	=	y resolution (black text): 600 x 300 dpi		
	-	y resolution (color text and graphics): 600 x dpi		
	 Cop 	y reduce / enlarge settings: 25 to 400%		
	• Cop	ies, maximum: Up to 50 copies		
S	CANNER ((REGISTRAR-LIPA)		
	• Scar	nner Type: Flatbed		
	• Scar	nning Element: Contact Image Sensor (CIS)		
	_	nt Source: Three-color (RGB) LED		
6		tures: 5 EZ Buttons, Advanced Z-lid, Auto Dust cratch Reduction, Auto Document Fix, Auto	1 unit	30 days
		n Mode, Backlight Correction, Convenient		
		ng Function (PDF Function), Digital Filing,		
		ing Correction, Grain Correction, Gutter dow Correction, High-Speed Scanning, Low		
		ver Consumption, One Cable for Data & Power,		
	Ver	tical Scanning		
	• Scar	nner Buttons: Auto Scan, Copy, PDF (x2), E-		

	mail Scanning Mode: ➤ Color: 48-bit internal/48- or 24-bit external ➤ Grayscale: 16-bit input/8-bit external Max. Document Size: 8.5" x 11.7" Interface: Hi-Speed USB Dimensions (W x D x H): 9.9" (W) x 14.4" (D) x 1.6" (H) Weight: 3.4 Ibs OS Compatibility: Windows® 7, Windows Vista®, Windows XP/2000 and Mac OS® X v.10.4.1-10.6 Software: Setup Software & User's Guide CD-ROM MP Navigator EX; Solution Menu Power Source: Hi-Speed USB Max. Power Consumption: 2.5W (1.4W Standby) Operating Temperature: 41° - 95°F Operating Humidity: 10% - 90% RH	
PRIN' • • • • • • • • • • • • • • • • • •	Print Method: On demand ink jet Nozzle Configuration: 180 nozzles Black, 59 nozzles each colour (Cyan, magenta, Yellow) Print Direction: Bi-directional printing, Uni-directional printing Maximum Resolution: 5760 x 1440 dpi (With Variable-Sized Droplet Technology) Maximum Ink Droplet Volume: 3pl Print Speed Max Black Draft Text – Memo (A4): Approx. 27 ppm / 15 ppm (Bk/Cl) ISO 24734, A4: Approx. 6.0 ipm/3.0 ipm (Bk/Cl) Max photo Draft – 10x15cm/4x6" – Approx. 27 sec per photo (W/Border) Photo Default – 10x15cm/4x6" – Approx. 69 sce per photo (W/Border) Max. Black Draft Text – Memo (A4) – Approx. 5 sec (Draft) Max. Colour Draft Text – Memo (A4) – Approx. 10 sec (Draft) Max. Colour Draft Text – Memo (A4) – Approx. 5 sec (Draft) Copy Mode: Standard copy mode Maximum Copies From Standalone: 20 sheets (fixed) Scanning Scanner Type: Flatbed colour image scanner Sensor Type: CIS Optical Resolution: 600 x 1200 dpi Maximum Scan Area: 216 x 297mm (8.5 x 11.7)	its 30 days

	Scanner Bit Depth]	
	→ Colour: 48-bit internal, 24-bit external		
	→ Grayscale: 16-bit internal, 8-bit external→ Black & White: 16-bit internal, 1-bit		
	external		
	Scan SpeedMonochrome 300 dpi: 2.4 msec/line		
	Colour 300 dpi: 9.5 msec/lime		
	Monochrome 600 dpi: 7.2 msec/line		
	Colour 600 dpi: 14.3 msec/line		
	PRINTER (ICT)		
	 Print Speed Black (Normal): Up to 33 ppm 		
	Print quality Black (Best): Up to 1200 x 1200 dpi		
	Duty Cycle (monthly, A4): Up to 50,000 pages		
	Print Technology: LaserProcessor Speed: 800 Mhz		
	Display: 2-line LCD (text and graphics)		
	Connectivity, standard: 1 Hi-Speed USB 2.0		
	1 Ethernet 10/100/1000T network		
	Network Ready: Standard (built-in Gigabit		
	Ethernet)		
	Minimum system requirements: Windows 8, Windows 7, (22) bit /(4) bit) Windows Victor (22)		
	Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit): 1 Ghz 32-bit (x86) or 64-bit (x64)		
	processor, 1 GB RAM (32-bit) or 2 GB RAM (64-		
	bit), 400 MB free hard disk space, CD/DVD ROM or		
8	Internet, USB or Network portWindows XP (32-bit) SP2: Pentium® 233 MHz	2 units	30 days
	processor, 512 MB RAM, 400 MB free hard disk	2 units	30 days
	space, CD/DVD-ROM or Internet, USB or Netwrok		
	portMAC OS X v 10.5, v 10.6, 10.7		
	 PowerPC G4, G5, or Intel® Core™ Processor 		
	• 500 MB Hard Disk		
	CD-ROM/DVD-ROM or Internet HGB. No. 1		
	USB or NetworkPaper Handling input, standard: 50-sheet		
	multipurpose tray 1, 250-sheet input tray 2		
	Paper handling output, standard: 150-sheet		
	output binMaximum output capacity (sheets): Up to 150		
	sheets		
	 Duplex printing: Manual (driver support provided) 		
	 Media sizes supported: A4, A5, A6, B5(JIS) 		
	Media sizes (custom): Multiproper to the Translation of the Tran		
	 Multipurpose tray: 76 x 127 to 216 x 356mm Tray 2 and optional 500-sheet tray 3: 105 x 		
	r ray 2 and optional 300 sheet day 3. 103 A	ı	

	1		Ī	1
		148 to 216 x 356 mm		
	•	Media types: Paper (plain, Green mode, light,		
		heavy, bond, color, letterhead, preprinted,		
		prepunched, recycled, rough), envelopes, labels		
	•	Supported media weight: Tray 1: 60 to 163 g/m ²		
		(straight through paper path for special media)		
		Tray 2: 500 sheet		
		Tray 2: 300 sheet Tray 3: 60 to 120 g/m ²		
	DDINT	TER (GENERAL ENGINEERING)		
	PKINI	EK (GENEKAL ENGINEEKING)		
	•	Print Method: On-demand ink jet		
		·		
	•	Nozzle Configuration: 180 nozzles Black, 59		
		nozzles each colour (Cyan, Magenta, Yellow)		
	•	Print Direction: Bi-directional printing, Uni-		
		directional printing		
	•	Maximum Resolution: 5760 x 1440 dpi (with		
		Variable-Sized Droplet Technology)		
	•	Minimum Ink Droplet Volume: 3pl		
	•	Print Speed		
		Max Black Draft Text - Memo (A4): Approx.		
		33 ppm / 15 ppm (Bk/Cl)		
		> ISO 24734, A4: Approx. 9.0 ipm / 4.5 ipm		
		(Bk/Cl))		
		Max Photo Draft - 10x15cm/4x6": Approx. 27		
		sec per photo (W/Border)		
		Photo Default - 10x15cm/4x6": Approx. 69		
		sec per photo (W/Border)		
		Double-sided Printing: Yes (Manual)		
		9 ,		
	•	Copying		
9		Copy Speed	1 unit	30 days
9		Max. Black Draft Text - Memo (A4): Approx. 5	1 uiiit	30 days
		sec (Draft)		
		Max. Colour Draft Text - Memo (A4): Approx.		
		10 sec (Draft)		
		Copy Mode: Standard copy mode		
		Maximum Copies From Standalone: 20 sheets		
		(fixed)		
	•	Scanning		
		Scanner Type: Flatbed colour image scanner		
		Sensor Type: CIS		
		➤ Optical Resolution: 600 x 1200 dpi		
		Maximum Scan Area: 216 x 297mm (8.5 x		
		11.7")		
		Scanner Bit Depth		
		Colour: 48-bit internal, 24-bit external		
		Grayscale: 16-bit internal, 8-bit external		
		→ Black & White: 16-bit internal, 1-bit		
		external		
		> Scan Speed		
		→ Monochrome 300 dpi: 2.4 msec/line		
		→ Colour 300 dpi: 9.5 msec/line		
		→ Monochrome 600 dpi: 7.2 msec/line		
		± '		
		→ Colour 600 dpi: 14.3 msec/line		

		n v 111	İ	ı ı
	•	Paper Handling		
		Paper Feed Method: Friction feed		
		Number of Paper Trays: 1		
	•	Paper Hold Capacity		
		Input Capacity: 100 sheets, A4 Plain paper		
		(75g/m2)		
		20 sheets, Premium Glossy Photo Paper		
		Output Capacity: 30 sheets, A4 Plain paper		
		20 sheets, Premium Glossy Photo Paper		
	•	Connectivity		
		Standard: USB 2.0 Hi-Speed		
	•	Printer Software		
		> Operating System Compatibility: Windows		
		XP/XP Professional x64 Edition/Vista/7		
		Mac OS X 10.5.8, 10.6.x, 10.7.x		
	I.APT	OP (VPRDE)		
		or (trime)		
	•	Operating System: Windows 8		
	•	Processor: Intel®Core™i5 Processor 3317UM (1.7		
		Ghz, 3MB L3 Cache)		
	•	LCD Display: 13.3" Super Bright 300 nit HD LED		
		Display (1,366 x 768), Anti-Reflect		
	•	Graphic Processor: Table		
	•	System Memory: 4GB DDR3 System Memory at		
		1,600 Mhz (on BD 4GB)		
	•	Memory Slot: 1 DIMM Slots		
	•	HDD Storage: 500 GB S-ATA All Slim Hard drive		
		(5,400 RPM) with Express Cache 2		
	•	Multimedia:		
		Sound: HD Audio		
		Sound Effect: Mic Noise Suppression		
		SoundAlive™		
10		Speaker: 4 watts Stereo Speaker (2 watts x 2)	1 unit	30 days
		Integrated Camera: 1.3 megapixel HD Webcam		,
		Wired Ethernet LAN: 10/100/1,000 Gigabit		
	•	Ethernet LAN		
		Wireless LAN: Intel®Centrino®Advanced-N 6235,		
		2 x 2 802.11 abg/n (up to 300Mb)		
	•	Bluetooth: Bluetooth 4.0		
	•	Port		
		Headphone Out: Headphone-out/Mic-Combo		
		Mic-in: Headphone-out/Mic-Combo		
		➤ USB: 1 USB 3.0, 2 USB 2.0		
		Mulkti Card Slot: 4-in-1 (SD, SDHC, SDXC,		
		MMC)		
	•	Keyboard: 81 Key		
		80 Key		
	•	Touch Pad, Touch Screen: Touch Pad (Scroll		
		Scope, Flat Type, Gesture UI)		
	•	AC Adapter: 40 watts		
	•	Standard Battery: 4 Cell (45 Wh)		

	0 1 1 Novem	1	j
	 Standard DVD: OS DVD		
	LAPTOP (ON-THE-JOB TRAINING OFFICE)		
11	 Intel Core i5-4200U 1.6 Ghz Haswell 4GB DDR3 500 GB HDD DVD writer 14" Active Matrix TFT Colour LCD HD 1366 x 768 LED Backlit Intel HD Graphics Wifi Gigabit LAN Webcam Mic HDMI USB 3.0 4 Hour Battery Life 	1 unit	
12	 15.6" HD Intel-Core i7-5500U/8Fb/1Tb/2Gb GeForce 940 M/Windows 8.1 Processor: Intel Core i7-5500U processor (4M Cache, up to 3.00 Ghz) Operating System: Windows 8.1 Memory: 8 GB DDR3L 1600 Mhz SDRAM Display: 15.6" 16:9 HD (1366 x 768) Display Graphic: 2 GB NVIDIA GeForce 940M DDR3 VRAM Storage: 1TB HDD Optical Drive: Super-Multi DVD Card Reader: 3 - in 1 card reader (SD/SDHC/SDXC) Camera: VGA web Camera Networking: Integrated 802.11 b/g/n Built-in Bluetooth™ V4.0 10/100/1000 Base T Interface: 1 X COMBO audio jack 1 X VGA port/Mini D-sub 15-pin for external monitor 2 X USB 3.0 port (s) 1 X USB 2.0 port 	2 sets	30 days

	1 X RJ45 LAN Jack for LAN insert 1 X HDMI 1 X SD card reader • Audio: Built-in Speakers And Microphone • Battery: 2 Cells 37 Whrs Polymer Battery • Power Adapter ➤ Output: 19 V DC, 3.42 A, 65 W ➤ Input: 100-240 V AC, 50/60 Hz universal • Dimensions: 38.2 x 25.6 x 2.58 cm (WxDxH) • Weight: 2.3 kg (with Polymer Battery)		
	 Security: Kensington lock BIOS Booting User Password Protection HDD User Password Protection and Security 		
13	 LAPTOP (EXTENSION) Color: White/Silver Quad Core Ultrathin Operating System: Windows 8 Pro Screen Size: 13.3 /14" HD LED Display (1366 x 768), Anti Reflective Processor: Quad-Core Processor (up to 1.4 Ghz) Graphics: AMD radeon HD Graphics Memory: 4GB DDR3L System Memory at 1066 MHz (on BD 4GB) Storage: 500 GB Solid-state Drive Connectivity: 802.11 bg/n 1 x 1 Bluetooth v4.0 Gigabit Ethernet (10/100/1000) Camera: 720p HD Web Camera Battery: 2-cell Battery Power Consumption: 220V, 40W With Laptop Bag, Mouse, Mouse Pad, Laptop Screen Protector, Cooling Pad and 1TB External Drive 	1 unit	30 days
14	 16-PORT FAST ETHERNET UNMANAGED DESKTOP SWITCH Inexpensive Fast Ethernet solution for SOHO/SMB Auto MDI/MDIX crossover for all ports Store-and-forward switching scheme Full/half-duplex for Ethernet/Fast Ethernet speeds IEEE 802.3x Flow Control Plug-and-play installation Switching Fabric: 3.2 Gpbs Standards: IEEE 802.3 10BASE-T Ethernet (twistedpair copper) IEEE 802.3u 100 BASE-TX Fast Ethernet (twisted-pair copper) ANSI/IEEE 802.3 NWay Auto-Negotiation 	5 units	30 days

- ► IEEE 802.3 x Flow Control
- ➤ IEEE 802.3az EEE function
- Protocol: CSMA/CD
- Data Transfer Rates
 - Ethernet: 100 Mbps (half duplex) 20 Mbps (full duplex)
 - Fast Ethernet: 100 Mbps (half duplex)
 200 Mbps (full duplex)
- Number of ports: 16 10/100 Mbps fast Ethernet ports
- Topology: Star
- Network Cables
 - ➤ 10BASE-T:
 - → UTP CAT 3/4/5/5e (100 m max.)
 - → EIA/TIA-586 100-ohm STP (100 m max.)
 - ➤ 100BASE-TX
 - → UTP CAT 5/5e (100 m max.)
 - → EIA/TIA-568 100-ohm STP (100 m max.)
- Media Interface Exchange: Auto MDI/MDIX adjustment for all ports
- LED Indicators
 - > Per port: Link/Activity
 - > Per device: Power
- Transmission Method: Store-and-forward
- MAC Address Table: 8K entries per device
- MAC Address Learning: Automatic update
- Packet Filtering /Forwarding Rates (half duplex)
 - Ethernet: 14,880 pps per port
 - Fast Ethernet: 148,800 pps per port
- **RAM Buffer:** 256 Bytes (2M bits)
- **Power Input:** 100~240 V AC 50/60 Hz internal universal power supply
- Power Consumption
 - Power On (Standby): DC input: 0.61 Watts
 AC input: 1.19 Watts
 - Max.: DC input: 1.55 Watts AC input: 2.89 Watts
- Heat Dissipation
 - Power On (Standby): AC input: 4.06 BTU/h
 - Maximum: AC input: 9.86 BTU/h
- **MTBF:** 2,266,559 hours
- **Operating Temp.:**0° to 40°C (32° to 104°F)
- **Storage Temp.:** -10 ° to 70 °C (14 ° to 158 °F)
- Operating Humidity: 10% to 90% RH noncondensing
- **Storage Humidity:** 5% to 90% RH non-condensing
- **Dimensions (W x D x H):** 280 x 125.8 x 44 mm

	(11.0 x 5.0 x 1.7 inches)		
	 Certificationsf 		
	FCC Class A		
	➤ ICES-003 Class A		
	> CE Class A		
	C-Tick Class A		
	> VCCI Class A		
	> cUL		
	> LVD		
	MULTIMEDIA PROJECTOR (ICT)		
	MOLTIMEDIA PROJECTOR (ICT)		
	• Aspect Ratio: 16:10 (Native) 4:3, 16:9		
	Brightness (ANSI Lumens): 1000 ANSI lumens		
	• Contrast Ratio: 10000:1		
	Display Type: DLP		
	• Resolution (Native/Max): WXGA (1280 x 800) HD (1920 X 1080)		
	Video Compatibility: PAL, SECAM, NTSC, HDTV		
	(480i, 480p, 576i, 576p, 720p, 1080i)		
	• Projection Lens: F=1.5		
	Number of colors: 1.07 Billion Colors		
	• Dimension (WxHxD): 8.7 in. x 1.7 in. x 6.7 in. (22.1		
	cm x 4.32 cm x 17.02 cm)		
	• Weight: 2.6 lbs (1.18 kg)		
	• Connectivity		
	> Inputs: 1 x HDMI		
	1 x VGA D-Sub 15pin		
15	1 x Composite	1 unit	30 days
	1 x Stereo Mini Jack		,
	1 x USB Type A		
	> Outputs: 1 x Stereo Mini Jack		
	> Audio: 1 x 3W Mono Speaker		
	Control: 1 x USB Type B		
	• Power Supply: 100~220V / 50-60 Hz		
	• Projection Lens		
	Lamp Type: Laser/LED		
	Lamp Life: 20000 hrs (Normal)		
	30000 hrs (Eco mode)		
	➤ Projection Distance: ft. ~ 3.0 ft. (0m~0.91m)		
	Projection Mode: Front, Rear, Ceiling		
	Projection Mode: Front, Rear, centingProjection Screen Size: (Diagonal)		
	30in.~100in. (76.2cm~254cm)		
	Digital Zoom: 1.7x		
	 Vertical Keystone Correction: +/- 40 Degrees 		
	H-Sync Range: 100 KHz		
	V-Sync Range: 120 Hz		
	7 Offic Range, 120 Hz		
L		l	

16	PROJECTOR (VPRDE) Native Aspect Ratio: 4x3 Technology: DLP Resolution: SVGA(800x600) Lumens (Eco/High): 2800/3000 Contrast: 15000 3D: Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP Link 3D glasses required. Closed Captioning: Yes Speakers: 2W (1 x 2W) Audible Noise (Eco/High, dBA): 29/30 Keystone: ± 40° Lamp: SP-LAMP-086 Lamp Hours (Eco/High): 10000/5000 Connections: HDMI 1.4, VGA x 2, Composite video, S-Video, 3.5 mm stereo in x 2, 3.5mm stereo out, RS232C Image Offset: 15 Lens Shift: Horz (min/max): None Lens Shift: Vert (min/max): None Throw Ratio: 2.2~1.9 Weight(lbs/kg): 5.4/2.5 Product Dimensions HxWxD: 8.7in x 11.5in x 4.7in (220mm x 292mm x 121mm) Shipping Weight(lbs/kg): 7.1/3.2	1 unit	30 days
17	PROJECTOR (ON-THE-JOB TRAINING OFFICE) WXVGA (1280 x 800) UXGA (1,600 x 1,200), 1080p (1,920 x 1,080) 16:10 (Native), 4:3, 16:9 Contrast Ratio at 4000:1 1.07 Billion Colors 500 ANSI Lumens (Standard) 350 ANSI Lumens (ECO) USB and HDMI port LED Life 20,000 Hours Remote One Internal Speaker with 2 watts Output 2.73 Ibs (1.24 kg)	1 unit	30 days
18	PROJECTOR (OSAS and ROSARIO CAMPUS) • Native Aspect Ratio: 4x3	9 units	30 days

	Technology: DLP		
	• Resolution: SVGA(800x600)		
	• Lumens (Eco/High): 3200/3500		
	• Contrast: 15000		
	• 3D: Supports 3D content from Blu-ray, cable		
	boxes, dish services and more (over HDMI) at		
	144Hz and PC-based 3D content at 120Hz.		
	DLP Link 3D glasses required.		
	Closed Captioning: Yes		
	• Speakers: 2W (1 x 2W)		
	• Audible Noise (Eco/High, dBA): 30/32		
	• Keystone: ± 40°		
	• Lamp Hours (Eco/High): 5000/3500		
	• Connections: HDMI 1.4, VGA x 2, USB-A (for		
	USB thumb drive or wireless network		
	adapter), USB Mini-B (for display over USB &		
	internal memory file mgmt), Composite Video,		
	S-Video, 3.5 mm stereo in x 2, RS232, USB-B		
	(control & firmware), VGA monitor out,		
	3.5mm audio out		
	Image Offset: 15		
	• Throw Ratio: 2.2~1.9		
	 Weight(lbs/kg): 7/3.2 		
	 Product Dimensions HxWxD: 8.7in x 11.5in x 		
	4.3in (220mm x 292mm x 108mm)		
	 Shipping Weight(lbs/kg): 8.1/3.7 		
	 Shipping Dimensions HxWxD: 12in x 14.25in x 		
	7.75in (305mm x 362mm x 197mm)		
	Product Warranty: 1 Year		
	Lamp Warranty: 6 months		
	PROJECTOR (CICS)		
	Native Aspect Ratio: 4:3		
	Technology: DLP		
	• Resolution: SVGA (800x600)		
	 Lumens (Eco/High): 3200/3500 		
	• Contrast: 15000		
19	• 3D: Supports 3D content form Blu-ray, clable	2 units	30 days
13	boxes, dish services and more (over HDMI) at	2 units	30 uays
	144Hz and PC-based 3D content at 120Hz.		
	DLP Link 3D glasses required		
	Closed Captioning: Yes		
	• Speakers: 2W (1 x 2W)		
	Audible Noise (Eco/High dBA): 30/32		
	• Keystone ±40°		
	• Lamp Hours: 5000/3500		
<u> </u>	I	l	I

20	 Wireless 802.11 b/g/n and 802.3ab gigabit LAN support Transfers computer content to a project/monitor wirelessly Features Quarter View, Direct Show, and a WPS Button Multiple video format support (codec installation needed) Infrared remote control included Simultaneous content projection and web surfing Supports Windows XP/Vista/7 and Mac OS (10.4 & 10.5 only) 	1 unit	30 days
	Hard Drive (ICT) • 2TB	2 units	30 days

SECTION VIII BIDDING FORMS

List of Forms

Form No.	Title
BatStateU Goods Form No. 1	Bid Form
BatStateU Goods Form No. 2	List of On-going Government and Private
	Contracts including Contracts Awarded but not
	yet started
BatStateU Goods Form No. 3	Statement of all Government and Private
	completed contracts which are similar in nature
BatStateU Goods Form No. 4	Net Financial Contracting Capacity
BatStateU Goods Form No. 5a	Bank Guarantee
BatStateU Goods Form No. 5b	Surety Bond
BatStateU Goods Form No. 5c	Bid Securing Declaration
BatStateU Goods Form No. 6	Conformity with Technical Specifications and
	Schedule of Requirements
BatStateU Goods Form No. 7	Omnibus Sworn Statement
BatStateU Goods Form No. 8	Request for Clarification
BatStateU Goods Form No. 9	Bill of Quantities

		BID FORM		
			Date:	
То:	ATTY. EDGARD E. BAC Chairman Batangas State Uni Batangas City			
Gentle	emen and / or Ladies:			
perfor	ot of which is her m][description of the	eby duly acknowledge, we, the codes in conformity with the s	g Bid Bulletin Numbers [insert numbers undersigned, offer to [supply / deaid Bidding Documents for the sum as and herewith and made part of this Bid.	eliver /
specif	We undertake, if o		goods in accordance with the delivery s	chedule
withir		ted, we undertake to provide a pn the Bidding Documents.	erformance security in the form, amour	nts, and
and it	<u>o</u>		ecified in the <u>BDS</u> provision for ITB Clau by time before the expiration of that perio	
contra		ratuities, if any, paid or to be pa e awarded the contract, are listed b	aid to us to agents relating to this Bid, pelow:	and to
Name Addre	and ess of agent	Amount and Currency	Purpose of Commission or Gratuity	
(if nor	ne, state "None")			
thereo		ract is prepared and executed, this Award, shall be binding upon us.	Bid, together with your writtenacceptan	ıce
	We understand tha	t you are not bound to accept the l	owest or any bid you may receive.	
Biddir	We certify / confing Documents.	m that we comply with the eligi	bility requirements as per ITB Clause 5	of the
Dated	thisday	of, 2015.		
[Signa	nture]	[in th	ne capacity of]	
Duly a	authorized to sign Bid	for and on behalf of		

List of all Ongoing Government & Private Contracts including contracts awarded but not yet started

Business Name : Business Address :								
Name of Contract/	a. Owner's Name	Nature of Work	Bidder's Role		a. Date Awarded	% of Accomplishment		Value of Outstanding
Project Cost	b. Address c. Telephone Nos.		Description	%	b. Date Started c. Date of Completion	Planned	Actual	Works / Undelivered Portion
Government								
<u>Private</u>								
Note: This statement shall be supported with:						Total Cost	;	
1 Notice of Award and/or Contract	t							

- 2 Notice to Proceed issued by the owner
- 3 Certificate of Accomplishments signed by the owner or authorized representative

Submitted by	:
•	(Printed Name & Signature)
Designation	:
Date	:

Statement of all Government & Private Contracts completed which are similar in nature

Business Name : Business Address :		-				
Name of Contract	a. Owner's Name		Bidder's Rol	le	a. Amount at Award	a. Date Awarded
Name of contract	b. Addressc. Telephone Nos.	Nature of Work	Description	%	b. Amount at Completion	b. Contract Effectivity
Government						
<u>Private</u>						
Note: This statement shall be supported	ed with:					
1 Contract						

- 2 Certificate of Completion
- 3 Certificate of Acceptance

Submitted by	:_	
-		(Printed Name & Signature)
Designation	:_	
Date	:_	

NET FINANCIAL CONTRACTING CAPACITY

A. Summary of the Applicant Supplier's/Distributor's/Manufacturer's assets and liabilities on the basis of the attached income tax return and audited financial statement, stamped "RECEIVED" by the Bureau of Internal Revenue or BIR authorized collecting agent, for the immediately preceding year and a certified copy of Schedule of Fixed Assets particularly the list of construction equipment.

		Year 20
1.	Total Assets	
2.	Current Assets	
3.	Total Liabilities	
4.	Current Liabilities	
5.	Net Worth (1-3)	
6.	Net Working Capital (2-4)	

B.	The Net Financial Contracting Capacity (NFCC) based on the above data is computed as follows:

NFCC = K (current asset – current liabilities) minus value of all outstanding works under ongoin contracts including awarded contracts yet to be started
NFCC = P
K = 10 for a contract duration of one year or less, 15 for more than one year up to two years and 20 for more than two years
Herewith attached are certified true copies of the income tax return and audited financial statemen stamped "RECEIVED" by the BIR or BIR authorized collecting agent for the immediately preceding year.
Submitted by:
Name of Supplier / Distributor / Manufacturer
Signature of Authorized Representative Date :

NOTE:

1. If Partnership or Joint Venture, each Partner or Member Firm of Joint Venture shall submit the above requirements.

BID SECURITY (BANK GUARANTEE)

WHEREAS, <u>(Name of Bidder)</u> (hereinafter called "the Bidder") has submitted his bid dated <u>(Date)</u> for the <u>(Name of Contract)</u> (hereinafter called "the Bid").
KNOW ALL MEN by these presents that We <u>(Name of Bank)</u> of <u>(Name of Country)</u> having our registered office at (hereinafter called "the Bank" are bound unto <u>(Name of Employer)</u> (hereinafter called "the Employer") in the sum of ² for which payment well and truly to be made to the said Employer the Bank binds himself, his successors and assigns by these presents.
SEALED with the Common Seal of the said Bank this day of 20
THE CONDITIONS of this obligation are:
1) If the Bidder withdraws his Bid during the period of bid validity specified in the Form of Bid; or
2) If the Bidder does not accept the correction of arithmetical errors of his bid price in accordance with the Instructions to Bidder; or
3) If the Bidder having been notified of the acceptance of his bid by the Employer during the period of bid validity:
 fails or refuses to execute the Form of Agreement in accordance with the Instructions to Bidders, if required; or
b) fails or refuses to furnish the Performance Security in accordance with the Instructions to Bidders;
we undertake to pay to the Employer up to the above amount upon receipt of his first written demand, without the Employer having to substantiate his demand, provided that in his demand the Employer will note that the amount claimed by him is due to him owning to the occurrence of one or both of the two (2) conditions, specifying the occurred condition or conditions.
The Guarantee will remain in force up to and including the date3 days after the deadline for submission of Bids as such deadline is stated in the Instructions to Bidders or as it may be extended by the Employer, notice of which extension(s) to the Bank is hereby waived. Any demand in respect of this Guarantee should reach the Bank not later than the above date.
DATESIGNATURE OF THE BANK
WITNESS SEAL
(Signature, Name and Address)

 $^{^2}$ The bidder should insert the amount of the guarantee in words and figures, denominated in the currency of the Employer's country or an equivalent amount in a freely convertible currency. This figure should be the same as shown of the Instructions to Bidders.

³ Úsually 28 days after the end of the validity period of the Bid. Date should be inserted by the Employer before the bidding documents are issued.

BID SECURITY SURETY BOND

BOND NO.: _		DATE BOND EXECUTED:
(Name of S business in the are held and Obligee, in the made, we, the	<i>urety)</i> he cour firmly e sum e said F	(Name of Bidder) (hereinafter called "the Principal") as Principal and of the country of (Name of Country of Surely), authorized to transact atry of (Name of Country of Employer) (hereinafter called "the Surety") bound unto (Name of Employer) (hereinafter called "the Employer") as of1 for the payment of which sum, well and truly to be Principal and Surety bind ourselves, our successors and assigns, jointly and these presents.
SEALED with	our se	als and dated this day of 20
		cipal has submitted a written Bid to the Employer dated the day of , for the (hereinafter called "the Bid").
NOW, THERE	FORE,	the conditions of this obligation are:
1)		Principal withdraws his Bid during the period of bid validity specified in the of Bid; or
2)		Principal does not accept the correction of arithmetical errors of his bid n accordance with the Instruction's to Bidders: or
3)		Principal having been notified of the acceptance of his Bid by the Employer the period of bid validity:
	a)	fails or refuses to execute the Form of Agreement in accordance with the Instructions to Bidders, if required; or
	b)	fails or refuses to furnish the Performance Security in accordance with the Instructions to Bidders;
then this obli	gation	shall remain in full force and effect, otherwise it shall be null and void.

¹ The bidder should insert the amount of bond in words and figures, denominated in the currency of the Employer's country of an equivalent amount in a freely convertible currency and callable on demand. This figure should be the same as shown in the Instructions to Bidders.

PROVIDED HOWEVER, that the Surety shall not be:

- a) liable for a greater sum than the specified penalty of this bond, nor
- b) liable for a greater sum that the difference between the amount of the said Principal's Bid and the amount of the Bid that is accepted by the Employer.

This Surety executing this instrument hereby agrees that its obligation shall be valid for 120 calendar days after the deadline for submission of Bids as such deadline is stated in the Instructions to Bidders or as it may be extended by the Employer, notice of which extension(s) to the Surety is hereby waived.

PRINCIPAL	SURETY
SIGNATURE(S)	SIGNATURES(S)
NAME(S) AND TITLE(S)	NAME(S)
SEAL.	SFAI.

		F THE PHILIPPINES)
		BID-SECURING DECLARATION Invitation to Bid No[insert reference number]
То:		ANGAS STATE UNIVERSITY L AVENUE, BATANGAS CITY
I / We	, the ui	ndersigned, declare that:
1.	•	ve understand that, according to your conditions, bids must be supported by a Bidrity, which may be in the form of a Bid-Securing Declaration.
2.	with Orde	e accept that: (a) I / we will be automatically disqualified from bidding for any contract any procuring entity for the period of two (2) years upon receipt of your Blacklisting r; and (b) I / we will pay the applicable fine provided under Section 6 of the Guidelines be Use of Bid Securing Declaration, if I / we have committed any of the following hs:
	-	Vithdrawn my / our Bid during the period of bid validity required in the Bidding ocuments; or
	n a	ail or refuse to accept the award and enter into contract or perform any and all acts ecessary to the execution of the contract, in accordance with the Bidding Documents fter having been notified of your acceptance of our Bid during the period of bid alidity.
3.	•	e understand that this Bid-Securing Declaration shall cease to be valid on the following mstances:
	a	Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
	b	I am / we are declared ineligible or post-disqualified upon receipt of your notice to such effect, and (i) I / we failed to timely file a request for reconsideration or (ii) I / we filed a waiver to avail of said right;
	c]	I am / we are declared as the bidder with the Lowest Calculated and Responsive Bid / Highest Rated and Responsive Bid, and I / we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I / we have hereunto set my / our hand/s this ____ day of

Name of Bidder
Authorized Representative
Legal Capacity
Affiant

Batangas State University
Bidding Documents (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)

BatStateU-Goods Form No. <u>5c</u>

SUBSCRIBED AND SWORN to before, Philippines. Affiant /s is / are identified by me through competent evidence of ident Practice (A.M.) No. 02-8-13-SC). Affiant/s exhibited identification card used, with his / her photograph and and his / her Community Tax Certificate No i Witness my hand and seal this day of	e personally known to me and was / were city as defined in the 2004 Rules on Notarial to me his / her [insert type of government d signature appearing thereon, with no issued on at
S N R P	IAME OF NOTARIAL PUBLIC erial No. of Commission lotary Public for until coll of Attorney's No TR No, [date issued], [place issued] BP No, [date issued], [place issued]
Doc. No Page No Book No Series of	

CONFORMITY WITH SCHEDULE OF REQUIREMENTS

Item No.	Section VI-Schedule of Requirements		REMARKS	
			Comply/Not Comply	
	DESKTOP COMPUTER			
1	 Processor: Intel Core i5-4690 Motherboard: Asus H81M-A Motherboard (Socket 1150) Memory: 2 x 2 GB Kingston DDR3 PCI 1600 (IKvR16N11S6/2) Hard Disk: Seagate 500GB7200RPM 3.5" SATA (ST500DM002) Case: ATX Casing V17 Powerlogic KB/Mouse: A4TECH KRS8520D Black Keyboard Monitor: AOC 18.5" LED E950SWN BLK monitor With AVR 	17 units	30 days	
2	 PRINTER (REGISTRAR) Technology: Laser Print sped: up to 30 ppm – B/W – Letter A Size (8.5 x 11) Connectivity Technology: wired Interface: USB, LAN Mas Resolution (B&W): 600 dpi Image Enhancement Technology: FastRes 1200 PostScript Support: Standard First Print Out Time B/W: 8 sec Language Simulation: PCL 5E Fonts Included: TrueType Media Handling: 250-sheet input tray, 50-sheet multipurpose tray Networking Connectivity Technology: wired Data Link Protocol: Ethernet, Fast Ethernet Remote Management Protocol: SNMP Network/Transport Protocol: Bonjour, TCP/IP Processor: 266 MHz Power Type: power supply Frequency Required: 60 Hz 	5 units	30 days	

Blading Doc	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	•	Power Consumption Standby/Sleep: 7 Watt Software Included: Drivers and Utilities OS Required: Apple MAcOS X 10.3.9, Novell		
		Netware, UNIX, Apple MacOS x 10.4.3, Apple		
		MacOS X 10.5x, Microsoft Windows 2000,		
		Microsoft Windows Server 20013, Microsoft		
		Windows Vista, Microsoft Windows XP Home		
		Edition, Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition		
		RAM Installed (Max) – 16MB / 16 MB (max)		
		Max Supported Size: 16 Mb		
	•	Manufacturer Warranty: Service and support		
		(1 year warranty)		
	•	Environmental Parameters:		
		Minimum Operating Temperature: 63.5°F		
		Maximum Operating Temperature: 77°F		
		Humidity Range Operating: 30-70%		
	•	Media Handling		
		Media Type: Bond Paper, Cards, Envelopes,		
		Glossy Paper, Labels, Plain Paper, Recycled Paper, Transparencies		
		Max Media Size (Custom): 8.5 x 14 in		
		 Envelope Sizes: Com-10 (4.13 in x 9.5 in), 		
		Monarch (3.87 in x 7.5 in)		
		➤ Total Media Capacity: 300 sheets		
		Media Feeders		
		1 x autoload - 50 sheets - Letter A Size (8.5 in		
		x 11 in)		
		1 x autoload – 250 sheets – Letter A Size (8.5		
		in x 11 in)		
		 Output Trays Capacity: 150 sheets Media Sizes: Letter A Size (8.5 x 11 in), Legal 		
		(8.5 in x 14 in), Executive (7.25 in x 10.5 in)		
	•	Monthly Duty Cycle (max): 25,000 pages		
	PRINT	TER (CASHIER)		
	•	Printing Technology		
		Print Method: Impact dot matrix		
		Number of Pins in Head: 9 pins		
		Print Direction: Bi-direction with logic		
		seekingControl Code: ESC/P and IBM PPDS emulation		
3			3 units	
	•	Print Speed		
		High Speed Draft10/12/15 cpi: 347 / 357 /		
		390 cps High Speed Draft Condensed 17/20 cpi; 383/		
		High Speed Draft Condensed17/20 cpi: 383 / 298 cps		
		> Draft10/12/15 cpi: 260 / 312 / 223 cps		
		> Draft Condensed17/20 cpi: 222 / 260 cps		
		> Draft Emphasized10 cpi: 130 cps		
		➤ NLQ10/12/15/17/20 cpi: 65 / 78 / 55 / 47 /		

56 cps

• Print Characteristics

- Character Sets: Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15
- ➤ Bitmap Fonts: Epson Draft: 10, 12, 15 cpi; Epson Roman & San Serif: 10, 12, 15 cpi, Proportional; Epson Courier: 10, 12, 15 cpi; Epson Prestige: 10, 12 cpi; Epson Script, OCR-B, Orator & Orator-S: 10cpi; Epson Script C: Proporational
- ➤ Barcode Fonts: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet

• Printable Columns

Pitch10/12/15/17/20 cpi: 80 / 96 / 120 / 137 / 160 cpl

Paper Handling Paper Path

- > Tractor: Rear in, Top out
- Manual Insertion: Rear in, Top out
- Cut Sheet (Single Sheet): 100 364mm

(3.9 - 14.3")100 -

257mm

(3.9 - 10.1")0.065 -

0.14mm

(0.0025 - 0.0055")

Cut Sheet (Multi Part): 100 - 364mm

(3.9 - 14.3")100 - 257mm (3.9 - 10.1")0.12 - 0.39mm (0.0047 - 0.015") (Total)

Envelope (No.6): 92mm

(3.6")165mm

(6.5")0.16 - 0.52mm

(0.0063 - 0.0205") (Total)

Envelope (No.10): 105mm

(4.1")241mm

(9.5")0.16 - 0.52mm

(0.0063 - 0.0205") (Total)

Continuous Paper (Single Sheet an Multi part):

101.6 - 558.8mm

(4.0 - 22.0")101.6 - 254.0mm

(4.0 - 10.0")0.065 - 0.39mm

(0.0025 - 0.015") (Total)

Roll Paper: 216mm

(8.5")0.07 - 0.09mm (0.0025 - 0.0035")

Paper Feeding

> Standard: Friction, Push Tractor

PRINTER (REGISTRAR-ROSARIO) Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space, CD-ROM Drive
PRINTER (REGISTRAR-ROSARIO) Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft@Windows@2000, XP Home, XP Professional, Server 2003: 512 MB RAM Masailable Hard Disk Space Mindows Vista@, 32/64:512 MB RAM, 350 MB available Hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64-512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64-512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64-512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Speed Black: Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64-512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Normal: Up to 30 ppm First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 First page out (ready) Black: As fast as 8.0 sec Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 ▶ Black: As fast as 8.0 sec Print Quality Black (best) ▶ Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard ▶ Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: ▶ Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM → 350 MB available Hard Disk Space ▶ Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port ▶ Mac OS x v10.3.9, v10.4.3, v10.5 ▶ 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 ▶ 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Quality Black (best) Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Up to 600 x 600 dpi effective output with HP FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
FastRes 1200) Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM Ma vailable Hard Disk Space Mindows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 Mac OS x v10.3.9, v10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5
 Duty Cycle: Up to 25,000 pages Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Recommended monthly page volume: 500 to 2500 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Technology: Laser Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Processor Speed: 2660MHz Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Print Languages: Host Based, UPD Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Connectivity, standard Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Hi-Speed USB 2.0, IEEE 1284-compliant parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
parallel Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Minimum System requirements: Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 USB MB RAM minimum (256 recommended), 150 MB available hard disk space
 Microsoft®Windows®2000, XP Home, XP Professional, Server 2003: 512 MB RAM 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
Professional, Server 2003: 512 MB RAM > 350 MB available Hard Disk Space > Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port > Mac OS x v10.3.9, v10.4.3, v10.5 > 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive • USB port > Mac OS X v 10.3.9, v 10.4.3, v10.5 > 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 350 MB available Hard Disk Space Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
Windows Vista®, 32/64:512 MB RAM, 350 MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
MB available hard disk space, CD-ROM Drive, USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
USB port Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Mac OS x v10.3.9, v10.4.3, v10.5 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
recommended), 150 MB available hard disk space, CD-ROM Drive • USB port > Mac OS X v 10.3.9, v 10.4.3, v10.5 > 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
space, CD-ROM Drive USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 USB port Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
 Mac OS X v 10.3.9, v 10.4.3, v10.5 128 MB RAM minimum (256 recommended), 150 MB available hard disk space
128 MB RAM minimum (256 recommended),150 MB available hard disk space
150 MB available hard disk space
Compatible operating System
➤ Microsoft®Window®2000, XP Home, XP
Professional, XP Professional x 64, Server
2003, NT 4.0 (PCL5 driver on web only)
Windows Vista®, x 64
> Mac OS X 10.3.9, v10.4.3, v10.5
► Mac 05 X 10.3.9, V10.4.5, V10.5 ► Linux
→ Linux → UNIX
Paper Handling Paper handling input standard, 250 sheet
Paper handling input, standard: 250-sheet
input tray, 50-sheet multipurpose tray
Paper handling output, standard: 150-sheet
output bin
Maximum output capacity (sheets): Up to 150
Duplex printing: Manual (driver support
provided)

Blading Do	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	Media sizes custom: 100 x 148 to 216 x 356		
	mm		
	Media types: Paper (brochure, inkjet, plain),		
	photo paper, envelopes, labels, cards		
	(greeting)		
	➤ Barcode scanner: 20 lb		
	• Scanner		
	Scanner type: Flatbed, ADF		
	Scan file format: PDF, BMP, PNG, TIF, JPG		
	Scan resolution, optical: Up to 1200 dpi		
	➤ Bit depth: 24-bit		
	Scan size (flatbed), maximum: 216 x 297 mm		
	Scan size (ADF), maximum: 216 x 356 mm		
	 Automatic document feeder capacity: 		
	Standard, 35 sheets		
	· ·		
	Scan input modes: Front-panel scan, copy, fax, or from software		
	Copy resolution (black text): 600 x 300 dpi Copy resolution (color text and graphics): 600 x		
	• Copy resolution (color text and graphics): 600 x		
	300 dpi		
	• Copy reduce / enlarge settings: 25 to 400%		
	Copies, maximum: Up to 50 copies		
	SCANNER (REGISTRAR-LIPA)		
	Scanner Type: Flatbed		
	 Scanning Element: Contact Image Sensor (CIS) 		
	Light Source: Three-color (RGB) LED		
	• Features: 5 EZ Buttons, Advanced Z-lid, Auto Dust		
	& Scratch Reduction, Auto Document Fix, Auto		
	Scan Mode, Backlight Correction, Convenient Filing Function (PDF Function), Digital Filing,		
	Fading Correction, Grain Correction, Gutter		
	Shadow Correction, High-Speed Scanning, Low		
6	Power Consumption, One Cable for Data & Power,	1 unit	30 days
	Vertical ScanningScanner Buttons: Auto Scan, Copy, PDF (x2), E-		
	mail		
	Scanning Mode:		
	Color: 48-bit internal/48- or24-bit externalGrayscale: 16-bit input/8-bit external		
	 Max. Document Size: 8.5" x 11.7" 		
	Interface: Hi-Speed USB		
	• Dimensions (W x D x H): 9.9" (W) x 14.4" (D) x		
	1.6" (H)		
	Weight: 3.4 Ibs	<u> </u>	

Didding Doc	cuments	(Dased off Revised IRR of RA 9104, Fourth Edition, December 2010)		
	•	OS Compatibility: Windows® 7, Windows Vista®,		
		Windows XP/2000 and Mac OS® X v.10.4.1-10.6		
	•	Software: Setup Software & User's Guide CD-ROM		
		MP Navigator EX; Solution Menu		
	•	Power Source: Hi-Speed USB		
	•	Max. Power Consumption: 2.5W (1.4W Standby)		
	•	Operating Temperature: 41° - 95°F		
	•	Operating Humidity: 10% - 90% RH		
	PRINT	TER (College of Industrial Technology and OSAS)		
	•	Print Method: On demand ink jet		
	•	Nozzle Configuration: 180 nozzles Black, 59		
		nozzles each colour (Cyan, magenta, Yellow)		
	•	Print Direction: Bi-directional printing, Uni-		
		directional printing		
	•	Maximum Resolution: 5760 x 1440 dpi (With		
		Variable-Sized Droplet Technology)		
		Maximum Ink Droplet Volume: 3pl		
	•	Print Speed		
	•	Max Black Draft Text – Memo (A4): Approx. 27		
		ppm / 15 ppm (Bk/Cl)		
		► ISO 24734, A4: Approx. 6.0 ipm/3.0 ipm		
		(Bk/Cl) ➤ Max photo Draft – 10x15cm/4x6" – Approx. 27		
		sec per photo (W/Border)		
		> Photo Default – 10x15cm/4x6" – Approx. 69		
		sce per photo (W/Border)		
	•	Copying ➤ Max. Black Draft Text – Memo (A4) – Approx. 5		
7		sec (Draft)	5 units	30 days
,		Max. Colour Draft Text - Memo (A4) - Approx.	5 units	30 days
		10 sec (Draft)		
		Copy Mode: Standard copy mode		
		Maximum Copies From Standalone: 20 sheets (fixed)		
	_	Scanning		
		ScanningScanner Type: Flatbed colour image scanner		
		Scanner Type: Platbed colour image scannerSensor Type: CIS		
		Optical Resolution: 600 x 1200 dpi		
		Maximum Scan Area: 216 x 297mm (8.5 x		
		11.7)		
		Scanner Bit Depth		
		→ Colour: 48-bit internal, 24-bit external		
		→ Grayscale: 16-bit internal, 8-bit external		
		→ Black & White: 16-bit internal, 1-bit		
		external		
	•	Scan Speed		
		Monochrome 300 dpi: 2.4 msec/line		
		Colour 300 dpi: 9.5 msec/lime		
		Monochrome 600 dpi: 7.2 msec/line		
		Colour 600 dpi: 14.3 msec/line		
		, dolour ood upi. I i.d indee/ inie		

	unients (based on Revised IRR of IRA 7104, Fourth Edition, December 2010)	1	1
	PRINTER (ICT)		
8	 Print Speed Black (Normal): Up to 33 ppm Print quality Black (Best): Up to 1200 x 1200 dpi Duty Cycle (monthly, A4): Up to 50,000 pages Print Technology: Laser Processor Speed: 800 Mhz Display: 2-line LCD (text and graphics) Connectivity, standard: 1 Hi-Speed USB 2.0		30 days
9	 Print Method: On-demand ink jet Nozzle Configuration: 180 nozzles Black, 59 nozzles each colour (Cyan, Magenta, Yellow) 	1 unit	30 days

- Print Direction: Bi-directional printing, Unidirectional printing
- Maximum Resolution: 5760 x 1440 dpi (with Variable-Sized Droplet Technology)
- Minimum Ink Droplet Volume: 3pl

Print Speed

- Max Black Draft Text Memo (A4): Approx. 33 ppm / 15 ppm (Bk/Cl)
- ➤ ISO 24734, A4: Approx. 9.0 ipm / 4.5 ipm (Bk/Cl))
- Max Photo Draft 10x15cm/4x6": Approx. 27 sec per photo (W/Border)
- Photo Default 10x15cm/4x6": Approx. 69 sec per photo (W/Border)
- Double-sided Printing: Yes (Manual)

Copying

Copy Speed

- Max. Black Draft Text Memo (A4): Approx. 5 sec (Draft)
- Max. Colour Draft Text Memo (A4): Approx.10 sec (Draft)
- Copy Mode: Standard copy mode
- Maximum Copies From Standalone: 20 sheets (fixed)

Scanning

- Scanner Type: Flatbed colour image scanner
- Sensor Type: CIS
- Optical Resolution: 600 x 1200 dpi
- Maximum Scan Area: 216 x 297mm (8.5 x 11.7")
- Scanner Bit Depth
 - → Colour: 48-bit internal, 24-bit external
 - → Grayscale: 16-bit internal, 8-bit external
 - Black & White: 16-bit internal, 1-bit external
- Scan Speed
 - → Monochrome 300 dpi: 2.4 msec/line
 - → Colour 300 dpi: 9.5 msec/line
 - → Monochrome 600 dpi: 7.2 msec/line
 - → Colour 600 dpi: 14.3 msec/line

Paper Handling

- Paper Feed Method: Friction feed
- Number of Paper Trays: 1
- Paper Hold Capacity
 - Input Capacity: 100 sheets, A4 Plain paper (75g/m2)
 - 20 sheets, Premium Glossy Photo Paper
 - Output Capacity: 30 sheets, A4 Plain paper
 20 sheets, Premium Glossy Photo Paper

Connectivity

Standard: USB 2.0 Hi-Speed

Printer Software

Operating System Compatibility: Windows XP/XP Professional x64 Edition/Vista/7 Mac OS X 10.5.8, 10.6.x, 10.7.x

L	APTOP (VPRDE)		
10	 Operating System: Windows 8 Processor: Intel®Core™i5 Processor 3317UM (1.7 Ghz, 3MB L3 Cache) LCD Display: 13.3" Super Bright 300 nit HD LED Display (1,366 x 768), Anti-Reflect Graphic Processor: Table System Memory: 4GB DDR3 System Memory at 1,600 Mhz (on BD 4GB) Memory Slot: 1 DIMM Slots HDD Storage: 500 GB S-ATA All Slim Hard drive (5,400 RPM) with Express Cache 2 Multimedia: Sound: HD Audio Sound Effect: Mic Noise Suppression SoundAlive™ Speaker: 4 watts Stereo Speaker (2 watts x 2) Integrated Camera: 1.3 megapixel HD Webcam Wired Ethernet LAN: 10/100/1,000 Gigabit Ethernet LAN Wireless LAN: Intel®Centrino®Advanced-N 6235 2 x 2 802.11 abg/n (up to 300Mb) Bluetooth: Bluetooth 4.0 Port Headphone Out: Headphone-out/Mic-Combo Mic-in: Headphone-out/Mic-Combo Mic-in: Headphone-out/Mic-Combo M	1 unit	30 days

	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	LAPTOP (ON-THE-JOB TRAINING OFFICE)		
	• Intel Core i5-4200U 1.6 Ghz Haswell		
	• 4GB DDR3		
	• 500 GB HDD		
	DVD writer		
	 14" Active Matrix TFT Colour 		
44	 LCD HD 1366 x 768 LED Backlit 	4	
11	Intel HD Graphics	1 unit	
	• Wifi		
	Gigabit LAN		
	Webcam Mic		
	HDMI		
	• USB 3.0		
	4 Hour Battery Life		
	4 Hour Battery Elle		
	LAPTOP (ICT)		
	 15.6" HD Intel-Core i7-5500U/8Fb/1Tb/2Gb 		
	GeForce 940 M/Windows 8.1		
	 Processor: Intel Core i7-5500U processor (4M 		
	Cache, up to 3.00 Ghz)		
	 Operating System: Windows 8.1 		
	Memory: 8 GB DDR3L 1600 Mhz SDRAM		
	• Display: 15.6" 16:9 HD (1366 x 768) Display		
	Graphic: 2 GB NVIDIA GeForce 940M DDR3 VRAM		
	Storage: 1TB HDD		
	Optical Drive: Super-Multi DVD		
	• Card Reader: 3 – in 1 card reader		
	(SD/SDHC/SDXC)		
	Camera: VGA web Camera		
	Networking: Integrated 802.11 b/g/n		
	Built-in Bluetooth™ V4.0		
	10/100/1000 Base T		
12	Interface: 1 X COMBO audio jack	2 sets	30 days
	1 X VGA port/Mini D-sub 15-pin for		
	external monitor		
	2 X USB 3.0 port (s)		
	1 X USB 2.0 port		
	1 X RJ45 LAN Jack for LAN insert		
	1 X HDMI		
	1 X SD card reader		
	Audio: Built-in Speakers And Microphone		
	Battery: 2 Cells 37 Whrs Polymer Battery		
	Power Adapter		
	► Output: 19 V DC, 3.42 A, 65 W		
	► Input: 19 v DC, 3.42 A, 63 w ► Input: 100-240 V AC, 50/60 Hz universal		
	• Dimensions: 38.2 x 25.6 x 2.58 cm (WxDxH)		
	Weight: 2.3 kg (with Polymer Battery) Security Konsington look		
	Security: Kensington lock PLOS Posting Hear Paggward Protection		
	BIOS Booting User Password Protection		
	HDD User Password Protection and		
	Security		

	LAPTO	OP (EXTENSION)		
	•	Color: White/Silver		
		Quad Core		
	•	Ultrathin		
	•	Operating System: Windows 8 Pro		
		Screen Size: 13.3 /14" HD LED Display (1366 x		
		768), Anti Reflective		
	•	Processor: Quad-Core Processor (up to 1.4 Ghz)		
	•	Graphics: AMD radeon HD Graphics		
	•	Memory: 4GB DDR3L System Memory at 1066		
13		MHz (on BD 4GB)	1 unit	30 days
	•	Storage: 500 GB Solid-state Drive		
	•	Connectivity: 802.11 bg/n 1 x 1 Bluetooth v4.0		
		Gigabit Ethernet (10/100/1000)		
	•	Camera: 720p HD Web Camera		
	•	Battery: 2-cell Battery		
	•	Power Consumption: 220V, 40W		
	•	With Laptop Bag, Mouse, Mouse Pad, Laptop		
		Screen Protector, Cooling Pad and 1TB External		
		Drive		
	16-P0 SWIT(RT FAST ETHERNET UNMANAGED DESKTOP CH		
	•	Inexpensive Fast Ethernet solution for SOHO/SMB		
	•	Auto MDI/MDIX crossover for all ports Store-and-		
		forward switching scheme		
	•	Full/half-duplex for Ethernet/Fast Ethernet		
		speeds		
	•	IEEE 802.3x Flow Control		
	•	Plug-and-play installation		
	•	Switching Fabric: 3.2 Gpbs		
	•	Standards:		
		➤ IEEE 802.3 10BASE-T Ethernet (twistedpair		
		copper)		
14		➤ IEEE 802.3u 100 BASE-TX Fast Ethernet		
		(twisted-pair copper)	5 units	30 days
		ANSI/IEEE 802.3 NWay Auto-Negotiation		
		> IEEE 802.3 x Flow Control		
		> IEEE 802.3az EEE function		
	•	Protocol: CSMA/CD		
	•	Data Transfer Rates Ethornet: 100 Mbps (half		
		Ethernet: 100 Mbps (half duplex)		
		20 Mbps (full duplex)		
		Fast Ethernet: 100 Mbps (half duplex)		
		200 Mbps (full duplex)		
	•	Number of ports: 16 10/100 Mbps fast Ethernet		
		ports		
	•	Topology: Star		
	•	Network Cables		
		> 10BASE-T:		
		→ UTP CAT 3/4/5/5e (100 m max.)		
		→ EIA/TIA-586 100-ohm STP (100 m max.)		
	1	,	1	

 ➤ 100BASE-TX → UTP CAT 5/5e (100 m max.) → EIA/TIA-568 100-ohm STP (100 m max.) • Media Interface Exchange: Auto MDI/MDIX adjustment for all ports • LED Indicators
 ▶ EIA/TIA-568 100-ohm STP (100 m max.) ▶ Media Interface Exchange: Auto MDI/MDIX adjustment for all ports ▶ LED Indicators ▶ Per port: Link/Activity ▶ Per device: Power ■ Transmission Method: Store-and-forward ● MAC Address Table: 8K entries per device ● MAC Address Learning: Automatic update ● Packet Filtering /Forwarding Rates (half duplex) ▶ Ethernet: 14,880 pps per port ▶ Fast Ethernet: 148,800 pps per port ● RAM Buffer: 256 Bytes (2M bits) ● Power Input: 100~240 V AC 50/60 Hz internal universal power supply ● Power Consumption ▶ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ▶ Max.: DC input: 1.55 Watts ▶ AC input: 2.89 Watts ● Heat Dissipation ▶ Power On (Standby): AC input: 4.06 BTU/h ▶ Maximum: AC input: 9.86 BTU/h ● MTBF: 2,266,559 hours ● Operating Temp.: 0° to 40°C (32° to104°F) ● Storage Temp.: 10° to 70°C (14° to 158°F) ● Operating Humidity: 10% to 90% RH non-
 ▶ EIA/TIA-568 100-ohm STP (100 m max.) ▶ Media Interface Exchange: Auto MDI/MDIX adjustment for all ports ▶ LED Indicators ▶ Per port: Link/Activity ▶ Per device: Power ■ Transmission Method: Store-and-forward ● MAC Address Table: 8K entries per device ● MAC Address Learning: Automatic update ● Packet Filtering /Forwarding Rates (half duplex) ▶ Ethernet: 14,880 pps per port ▶ Fast Ethernet: 148,800 pps per port ● RAM Buffer: 256 Bytes (2M bits) ● Power Input: 100~240 V AC 50/60 Hz internal universal power supply ● Power Consumption ▶ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ▶ Max.: DC input: 1.55 Watts ▶ AC input: 2.89 Watts ● Heat Dissipation ▶ Power On (Standby): AC input: 4.06 BTU/h ▶ Maximum: AC input: 9.86 BTU/h ● MTBF: 2,266,559 hours ● Operating Temp.: 0° to 40°C (32° to104°F) ● Storage Temp.: 10° to 70°C (14° to 158°F) ● Operating Humidity: 10% to 90% RH non-
adjustment for all ports • LED Indicators > Per port: Link/Activity > Per device: Power • Transmission Method: Store-and-forward • MAC Address Table: 8K entries per device • MAC Address Learning: Automatic update • Packet Filtering /Forwarding Rates (half duplex) > Ethernet: 14,880 pps per port > Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption > Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts > Max.: DC input: 1.55 Watts AC input: 2.89 Watts • Heat Dissipation > Power On (Standby): AC input: 4.06 BTU/h > Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to104°F) • Storage Temp::-10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
adjustment for all ports • LED Indicators > Per port: Link/Activity > Per device: Power • Transmission Method: Store-and-forward • MAC Address Table: 8K entries per device • MAC Address Learning: Automatic update • Packet Filtering /Forwarding Rates (half duplex) > Ethernet: 14,880 pps per port > Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption > Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts > Max.: DC input: 1.55 Watts AC input: 2.89 Watts • Heat Dissipation > Power On (Standby): AC input: 4.06 BTU/h > Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to104°F) • Storage Temp::-10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
adjustment for all ports • LED Indicators > Per port: Link/Activity > Per device: Power • Transmission Method: Store-and-forward • MAC Address Table: 8K entries per device • MAC Address Learning: Automatic update • Packet Filtering /Forwarding Rates (half duplex) > Ethernet: 14,880 pps per port > Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption > Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts > Max.: DC input: 1.55 Watts AC input: 2.89 Watts • Heat Dissipation > Power On (Standby): AC input: 4.06 BTU/h > Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to104°F) • Storage Temp::-10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
 LED Indicators Per port: Link/Activity Per device: Power Transmission Method: Store-and-forward MAC Address Table: 8K entries per device MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp::-10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Per port: Link/Activity Per device: Power Transmission Method: Store-and-forward MAC Address Table: 8K entries per device MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 ➤ Per device: Power Transmission Method: Store-and-forward MAC Address Table: 8K entries per device MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) ➤ Ethernet: 14,880 pps per port ➤ Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption ➤ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ➤ Max.: DC input: 1.55 Watts ➤ AC input: 2.89 Watts Heat Dissipation ➤ Power On (Standby): AC input: 4.06 BTU/h ➤ Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Transmission Method: Store-and-forward MAC Address Table: 8K entries per device MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 MAC Address Table: 8K entries per device MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.: 0° to 40°C (32° to 104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 MAC Address Learning: Automatic update Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Packet Filtering /Forwarding Rates (half duplex) Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
duplex) ➤ Ethernet: 14,880 pps per port ➤ Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption ➤ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ➤ Max.: DC input: 1.55 Watts AC input: 2.89 Watts • Heat Dissipation ➤ Power On (Standby): AC input: 4.06 BTU/h ➤ Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to 104°F) • Storage Temp: -10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
duplex) ➤ Ethernet: 14,880 pps per port ➤ Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption ➤ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ➤ Max.: DC input: 1.55 Watts AC input: 2.89 Watts • Heat Dissipation ➤ Power On (Standby): AC input: 4.06 BTU/h ➤ Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to 104°F) • Storage Temp: -10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
 Ethernet: 14,880 pps per port Fast Ethernet: 148,800 pps per port RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts
 ▶ Fast Ethernet: 148,800 pps per port • RAM Buffer: 256 Bytes (2M bits) • Power Input: 100~240 V AC 50/60 Hz internal universal power supply • Power Consumption ▶ Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts ▶ Max.: DC input: 1.55 Watts
 RAM Buffer: 256 Bytes (2M bits) Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Power Input: 100~240 V AC 50/60 Hz internal universal power supply Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Power Consumption Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Power Consumption Power On (Standby): DC input: 0.61 Watts
 Power On (Standby): DC input: 0.61 Watts
 Power On (Standby): DC input: 0.61 Watts
AC input: 1.19 Watts Max.: DC input: 1.55 Watts AC input: 2.89 Watts Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to 104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Max.: DC input: 1.55 Watts
AC input: 2.89 Watts • Heat Dissipation ➤ Power On (Standby): AC input: 4.06 BTU/h ➤ Maximum: AC input: 9.86 BTU/h • MTBF: 2,266,559 hours • Operating Temp.:0° to 40°C (32° to104°F) • Storage Temp.: -10° to 70°C (14° to 158°F) • Operating Humidity: 10% to 90% RH non-
 Heat Dissipation Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Power On (Standby): AC input: 4.06 BTU/h Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Maximum: AC input: 9.86 BTU/h MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 MTBF: 2,266,559 hours Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Operating Temp.:0° to 40°C (32° to104°F) Storage Temp.: -10° to 70°C (14° to 158°F) Operating Humidity: 10% to 90% RH non-
 Storage Temp.: -10 ° to 70 °C (14 ° to 158 °F) Operating Humidity: 10% to 90% RH non-
• Operating Humidity: 10% to 90% RH non-
• Storage Humidity: 5% to 90% RH non-condensing
Condensing
• Dimensions (W x D x H): 280 x 125.8 x 44 mm
(11.0 x 5.0 x 1.7 inches)
(11.0 x 3.0 x 1.7 inches)
• Certificationsf
FCC Class A
ICES-003 Class A
CE Class A
C-Tick Class A
> VCCI Class A
> cUL
> LVD
MULTIMEDIA PROJECTOR (ICT)
15 1 1 1 1 1 1 1 1 1
• Aspect Ratio: 16:10 (Native) 4:3, 16:9
Brightness (ANSI Lumens): 1000 ANSI lumens
Contrast Ratio: 10000:1 Page 13 of 16

Blading Doo	ruments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	_	
	Display Type: DLP		
	• Resolution (Native/Max): WXGA (1280 x 800)		
	HD (1920 X 1080)		
	• Video Compatibility: PAL, SECAM, NTSC, HDTV		
	(480i, 480p, 576i, 576p, 720p, 1080i)		
	Projection Lens: F=1.5Number of colors: 1.07 Billion Colors		
	 Dimension (WxHxD): 8.7 in. x 1.7 in. x 6.7 in. (22.1 cm x 4.32 cm x 17.02 cm) 		
	• Weight: 2.6 lbs (1.18 kg)		
	Connectivity		
	➤ Inputs: 1 x HDMI		
	1 x VGA D-Sub 15pin		
	1 x Composite		
	1 x Stereo Mini Jack		
	1 x USB Type A		
	> Outputs: 1 x Stereo Mini Jack		
	Audio: 1 x 3W Mono Speaker		
	Control: 1 x USB Type B		
	• Power Supply: 100~220V / 50-60 Hz		
	Projection Lens		
	Lamp Type: Laser/LED		
	Lamp Life: 20000 hrs (Normal)		
	30000 hrs (Eco mode)		
	Projection Distance: ft. ~ 3.0 ft. $(0m\sim 0.91m)$		
	Projection Mode: Front, Rear, Ceiling		
	Projection Screen Size: (Diagonal)		
	30in.~100in. (76.2cm~254cm)		
	Digital Zoom: 1.7x		
	Vertical Keystone Correction: +/- 40 Degrees		
	► H-Sync Range: 100 KHz		
	V-Sync Range: 120 Hz		
	PROJECTOR (VPRDE)		
	Native Aspect Ratio: 4x3		
	Technology: DLP Response (200) Technology: DLP Te		
	• Resolution: SVGA(800x600)		
	• Lumens (Eco/High): 2800/3000		
	• Contrast: 15000		
	3D: Supports 3D content from Blu-ray, cable bases dish assistance and many (asset HDM) at		
16	boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP	1	20 days
16	Link 3D glasses required.	1 unit	30 days
	 Closed Captioning: Yes 		
	Closed Captioning: TesSpeakers: 2W (1 x 2W)		
	Audible Noise (Eco/High, dBA): 29/30		
	 Keystone: ± 40° 		
	• Lamp: SP-LAMP-086		
	 Lamp Hours (Eco/High): 10000/5000 		
	 Connections: HDMI 1.4, VGA x 2, Composite video 		
	S-Video, 3.5 mm stereo in x 2, 3.5mm stereo out,		
	RS232C		
L	10000	1	l

	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
	 Image Offset: 15 Lens Shift: Horz (min/max): None Lens Shift: Vert (min/max): None Throw Ratio: 2.2~1.9 Weight(lbs/kg): 5.4/2.5 Product Dimensions HxWxD: 8.7in x 11.5in x 4.7in (220mm x 292mm x 121mm) Shipping Weight(lbs/kg): 7.1/3.2 		
17	 PROJECTOR (ON-THE-JOB TRAINING OFFICE) WXVGA (1280 x 800) UXGA (1,600 x 1,200), 1080p (1,920 x 1,080) 16:10 (Native), 4:3, 16:9 Contrast Ratio at 4000:1 1.07 Billion Colors 500 ANSI Lumens (Standard) 350 ANSI Lumens (ECO) USB and HDMI port LED Life 20,000 Hours Remote One Internal Speaker with 2 watts Output 2.73 Ibs (1.24 kg) 	1 unit	30 days
18	 PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 Technology: DLP Resolution: SVGA(800x600) Lumens (Eco/High): 3200/3500 Contrast: 15000 3D: Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP Link 3D glasses required. Closed Captioning: Yes Speakers: 2W (1 x 2W) Audible Noise (Eco/High, dBA): 30/32 Keystone: ± 40° Lamp Hours (Eco/High): 5000/3500 Connections: HDMI 1.4, VGA x 2, USB-A (for USB thumb drive or wireless network adapter), USB Mini-B (for display over USB & internal memory file mgmt), Composite Video, S-Video, 3.5 mm stereo in x 2, RS232, USB-B (control & firmware), VGA monitor out, 3.5mm audio out Image Offset: 15 	9 units	30 days

	• Throw Ratio: 2.2~1.9		
	 Weight(lbs/kg): 7/3.2 Product Dimensions HxWxD: 8.7in x 11.5in x 4.3in (220mm x 292mm x 108mm) Shipping Weight(lbs/kg): 8.1/3.7 Shipping Dimensions HxWxD: 12in x 14.25in x 7.75in (305mm x 362mm x 197mm) Product Warranty: 1 Year Lamp Warranty: 6 months 		
	PROJECTOR (CICS)		
19	 Native Aspect Ratio: 4:3 Technology: DLP Resolution: SVGA (800x600) Lumens (Eco/High): 3200/3500 Contrast: 15000 3D: Supports 3D content form Blu-ray, clable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz. DLP Link 3D glasses required Closed Captioning: Yes Speakers: 2W (1 x 2W) Audible Noise (Eco/High dBA): 30/32 Keystone ±40° Lamp Hours: 5000/3500 	2 units	30 days
20	 WIRELESS PROJECTOR SERVER (ICT) Wireless 802.11 b/g/n and 802.3ab gigabit LAN support Transfers computer content to a project/monitor wirelessly Features Quarter View, Direct Show, and a WPS Button Multiple video format support (codec installation needed) 	1 unit	30 days
	 Infrared remote control included Simultaneous content projection and web surfing Supports Windows XP/Vista/7 and Mac OS (10.4 & 10.5 only) 		
	Hard Drive (ICT) • 2TB	2 units	30 days

CONFORMITY WITH TECHNICAL SPECIFICATIONS

Item No.	Section VI-Schedule of Requirements	QTY.	REMARKS
			Comply/Not Comply
	DESKTOP COMPUTER		
1	 Processor: Intel Core i5-4690 Motherboard: Asus H81M-A Motherboard (Socket 1150) Memory: 2 x 2 GB Kingston DDR3 PCI 1600 (IKvR16N11S6/2) Hard Disk: Seagate 500GB7200RPM 3.5" SATA (ST500DM002) Case: ATX Casing V17 Powerlogic KB/Mouse: A4TECH KRS8520D Black Keyboard Monitor: AOC 18.5" LED E950SWN BLK monitor With AVR 	17 units	30 days
2	 PRINTER (REGISTRAR) Technology: Laser Print sped: up to 30 ppm – B/W – Letter A Size (8.5 x 11) Connectivity Technology: wired Interface: USB, LAN Mas Resolution (B&W) : 600 dpi Image Enhancement Technology: FastRes 1200 PostScript Support: Standard First Print Out Time B/W: 8 sec Language Simulation: PCL 5E Fonts Included: TrueType Media Handling: 250-sheet input tray, 50-sheet multipurpose tray Networking Connectivity Technology: wired Data Link Protocol: Ethernet, Fast Ethernet Remote Management Protocol: SNMP Networking: Print Server – integrated Network/Transport Protocol: Bonjour, TCP/IP Processor: 266 MHz Power Type: power supply Frequency Required: 60 Hz Power Consumption Operational: 550 Watt 	5 units	30 days

Bidding Documents	Based on Revised IR	R of RA 9184, Fourth Edition	December 2010)

Power Consumption Standby/Sleep: 7 Watt Software Included: Drivers and Utilities OS Required: Apple MAcOS X 10.3.9, Novell Netware, UNIX, Apple MacOS x 10.4.3, Apple MacOS X 10.5x, Microsoft Windows 2000, Microsoft Windows Server 20013. Microsoft Windows Vista, Microsoft Windows XP Home Edition, Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition RAM Installed (Max) - 16MB / 16 MB (max) Max Supported Size: 16 Mb Manufacturer Warranty: Service and support (1 year warranty) **Environmental Parameters:** Minimum Operating Temperature: 63.5°F Maximum Operating Temperature: 77°F Humidity Range Operating: 30-70% Media Handling Media Type: Bond Paper, Cards, Envelopes, Glossy Paper, Labels, Plain Paper, Recycled Paper, Transparencies Max Media Size (Custom): 8.5 x 14 in Envelope Sizes: Com-10 (4.13 in x 9.5 in), Monarch (3.87 in x 7.5 in) Total Media Capacity: 300 sheets Media Feeders 1 x autoload – 50 sheets – Letter A Size (8.5 in x 11 in) 1 x autoload - 250 sheets - Letter A Size (8.5 in x 11 in) Output Trays Capacity: 150 sheets Media Sizes: Letter A Size (8.5 x 11 in), Legal (8.5 in x 14 in), Executive (7.25 in x 10.5 in) Monthly Duty Cycle (max): 25,000 pages PRINTER (CASHIER) **Printing Technology** Print Method: Impact dot matrix Number of Pins in Head: 9 pins Print Direction: Bi-direction with logic seeking 3 ➤ Control Code: ESC/P and IBM PPDS emulation 3 units **Print Speed** High Speed Draft10/12/15 cpi: 347 / 357 / 390 cps ➤ High Speed Draft Condensed17/20 cpi: 383 / 298 cps > Draft10/12/15 cpi: 260 / 312 / 223 cps > Draft Condensed 17/20 cpi: 222 / 260 cps

- Draft Emphasized10 cpi: 130 cps
- NLQ10/12/15/17/20 cpi: 65 / 78 / 55 / 47 / 56 cps

• Print Characteristics

- Character Sets: Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15
- ➤ Bitmap Fonts: Epson Draft: 10, 12, 15 cpi; Epson Roman & San Serif: 10, 12, 15 cpi, Proportional; Epson Courier: 10, 12, 15 cpi; Epson Prestige: 10, 12 cpi; Epson Script, OCR-B, Orator & Orator-S: 10cpi; Epson Script C: Proporational
- ➤ Barcode Fonts: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet

• Printable Columns

Pitch10/12/15/17/20 cpi: 80 / 96 / 120 / 137 / 160 cpl

• Paper Handling Paper Path

- > Tractor: Rear in, Top out
- Manual Insertion: Rear in, Top out
- Cut Sheet (Single Sheet): 100 364mm(3.9 14.3")100 -

(3.9 - 10.1")0.065 -

0.14mm

257mm

(0.0025 - 0.0055")

Cut Sheet (Multi Part): 100 - 364mm

(3.9 - 14.3")100 - 257mm (3.9 - 10.1")0.12 - 0.39mm (0.0047 - 0.015") (Total)

Envelope (No.6): 92mm

(3.6")165mm (6.5")0.16 - 0.52mm (0.0063 - 0.0205") (Total)

Envelope (No.10): 105mm

(4.1")241mm (9.5")0.16 - 0.52mm (0.0063 - 0.0205") (Total)

Continuous Paper (Single Sheet an Multi part):

101.6 - 558.8mm (4.0 - 22.0")101.6 - 254.0mm (4.0 - 10.0")0.065 - 0.39mm (0.0025 - 0.015") (Total)

➤ Roll Paper: 216mm

(8.5")0.07 - 0.09mm

		(0.0025 - 0.0035")		-
		(0.0023 - 0.0033)		
		Paper Feeding		
		Standard: Friction, Push Tractor		
		> Optional: Roll Paper Holder		
		<u> </u>		
		Copies: Original + 4 copies		
F	PRINT	ER (REGISTRAR-ROSARIO)		
	•	Print Speed Black:		
		Normal: Up to 30 ppm		
		First page out (ready)		
		Black: As fast as 8.0 sec		
	•	Print Quality Black (best)		
		> Up to 600 x 600 dpi effective output with HP		
		FastRes 1200)		
		,		
	•	Duty Cycle: Up to 25,000 pages		
	•	Recommended monthly page volume: 500 to 2500		
	•	Print Technology: Laser		
	•	Processor Speed: 2660MHz		
	•	Print Languages: Host Based, UPD		
	•	Connectivity, standard		
		➤ Hi-Speed USB 2.0, IEEE 1284-compliant		
		parallel		
	•	Minimum System requirements:		
		Microsoft®Windows®2000, XP Home, XP		
		Professional, Server 2003: 512 MB RAM		
4		350 MB available Hard Disk Space	1 unit	30 days
		Windows Vista®, 32/64:512 MB RAM, 350		
		MB available hard disk space, CD-ROM Drive,		
		USB port		
		➤ Mac OS x v10.3.9, v10.4.3, v10.5		
		> 128 MB RAM minimum (256 MB		
		recommended), 150 MB available hard disk		
		space, CD-ROM Drive		
	•	USB port		
		Mac OS X v 10.3.9, v 10.4.3, v10.5		
		➤ 128 MB RAM minimum (256 recommended),		
		150 MB available hard disk space		
	•	Compatible operating System		
		Microsoft®Window®2000, XP Home, XP		
		Professional, XP Professional x 64, Server		
		2003, NT 4.0 (PCL5 driver on web only)		
		Windows Vista®, x 64		
		Mac OS X 10.3.9, v10.4.3, v10.5		
		Linux		
	_	> UNIX		
	•	Paper Handling		
		Paper handling input, standard: 250-sheet input tray, 50-sheet multipurpose tray		
		Paper handling output, standard: 150-sheet		

Bidding Documents	(Based on Re	evised IRR of RA	9184. Fourth Edition	December 2010)

Blading Doct	ıments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
		output bin		
		Maximum output capacity (sheets): Up to 150		
		Duplex printing: Manual (driver support		
		provided)		
		Media Sizes supported:		
		Tray 1: A4, A5, A6, B5, envelopes (C5,		
		B5, DL)		
		→ Tray 2: A4, A5, A6		
		Media sizes, custom		
		→ Tray 1: 76 x 127 to 216 x 356mm		
		→ Tray 2: 105 x 148 to 216 x 356mm		
		Media Types: Paper (bond, light, heavy, plain,		
		recycled, rough), envelopes, labels, cardstock,		
		transparencies, heavy media		
	•	Supported media weight		
	•	> Tray 1: 60 to 163 g/m ² (straight through		
		paper path for special media)		
		> Tray 2: 60 to 120 g/m ²		
		7 11ay 2. 00 to 120 g/ III-		
	DDINT	TER (ROSARIO CAMPUS)		
	KINI	ER (ROSARIO CAMFOS)		
	_	Functions Drint Conv. Con For		
	•	Functions: Print, Copy, Scan, Fax		
	•	Printing Specifications		
		Print Speed Black		
		→ ISO: Up to 7 ppm		
		→ Draft: Up to 20 ppm		
		Print speed color		
		→ ISO: Up to 4 ppm		
		Draft: Up to 16 ppm		
		First page out (ready)		
		Black: As fast 17 sec		
		Color: As fast 24 sec		
		Duty Cycle (monthly,A4): Up to 1000 pages		
		Recommended monthly page volume: 300 to		
5		400	1 unit	
		Print technology: Thermal Inkjet Print technology: Thermal Inkjet	1 unit	
		Print quality (best):		
		Color: Up to 4800 x 1200 optimised dpi colour		
		(when printing from a computer on selected		
		HP photo papers and 1200 input dpi)		
		Black: Up to 600 x 600 rendered dpi		
		Display: 5 cm (2.0 in) Hi-Res Mono LCD		
		Processor speed: 360 MHz Number of print cartridges: 2 (1 black 1 Tri		
		Number of print cartridges: 2 (1 black, 1 Tri-		
		color)		
	•	Connectivity, standard: Hi-Speed USB		
	•	Memory Specifications:		
		Memory, standard: 32 MB SDRAM		
		-		
		Memory, maximum: 32 MB SDRAM		
	•	Paper handling		
		Paper handling input, standard: 60-sheet input		
L		<u>, J, ,</u>		

Bluding Doc	uments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	1	
	tray		
	Paper handling output, standard: 25-sheet		
	output tray		
	Media sizes supported: A4, B5, A6, DL		
	envelope		
	Media sizes custom: 100 x 148 to 216 x 356		
	mm Media types: Paper (brochure, inkiet, plain).		
	(
	photo paper, envelopes, labels, cards (greeting)		
	Barcode scanner: 20 lb		
	Barcode scallier. 20 ib		
	• Scanner		
	Scanner type: Flatbed, ADF		
	Scan file format: PDF, BMP, PNG, TIF, JPG		
	Scan resolution, optical: Up to 1200 dpi		
	➤ Bit depth: 24-bit		
	Scan size (flatbed), maximum: 216 x 297 mm		
	Scan size (ADF), maximum: 216 x 356 mm		
	Automatic document feeder capacity:		
	Standard, 35 sheets		
	Scan input modes: Front-panel scan, copy, fax,		
	or from software		
	• Copy resolution (black text): 600 x 300 dpi		
	• Copy resolution (color text and graphics): 600 x		
	300 dpi		
	• Copy reduce / enlarge settings: 25 to 400%		
	 Copies, maximum: Up to 50 copies 		
	SCANNER (REGISTRAR-LIPA)		
	Cooper Type Clothed		
	Scanner Type: FlatbedScanning Element: Contact Image Sensor (CIS)		
	Light Source: Three-color (RGB) LED		
	• Features: 5 EZ Buttons, Advanced Z-lid, Auto Dust		
6	& Scratch Reduction, Auto Document Fix, Auto	1 unit	30 days
	Scan Mode, Backlight Correction, Convenient Filing Function (PDF Function), Digital Filing,		
	Fading Correction, Grain Correction, Gutter		
	Shadow Correction, High-Speed Scanning, Low		
	Power Consumption, One Cable for Data & Power, Vertical Scanning		
	 Scanner Buttons: Auto Scan, Copy, PDF (x2), E- 		
	mail		

Didding 20	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	1	
	Scanning Mode: A continuous services and a continuous services and a continuous services are services as a continuous services are services are services are services are services as a continuous services are services		
	Color: 48-bit internal/48- or24-bit external		
	Grayscale: 16-bit input/8-bit external		
	Max. Document Size: 8.5" x 11.7"		
	Interface: Hi-Speed USB		
	 Dimensions (W x D x H): 9.9" (W) x 14.4" (D) x 		
	1.6" (H)		
	• Weight: 3.4 lbs		
	 OS Compatibility: Windows® 7, Windows Vista® 		
	Windows XP/2000 and Mac OS® X v.10.4.1-10.6		
	Software: Setup Software & User's Guide CD-ROM		
	MP Navigator EX; Solution Menu		
	Power Source: Hi-Speed USB		
	 Max. Power Consumption: 2.5W (1.4W Standby) 		
	• Operating Temperature: 41° - 95°F		
	Operating Humidity: 10% - 90% RH		
	operating frametally 10 /0 /0 ftm		
	PRINTER (College of Industrial Technology and OSAS)	
	 Print Method: On demand ink jet 		
	 Nozzle Configuration: 180 nozzles Black, 59 		
	nozzles each colour (Cyan, magenta, Yellow)		
	 Print Direction: Bi-directional printing, Uni- 		
	directional printing		
	 Maximum Resolution: 5760 x 1440 dpi (With 		
	Variable-Sized Droplet Technology)		
	 Maximum Ink Droplet Volume: 3pl 		
	• Print Speed	_	
	Max Black Draft Text – Memo (A4): Approx. 2	′	
	ppm / 15 ppm (Bk/Cl)		
	ISO 24734, A4: Approx. 6.0 ipm/3.0 ipm (Bk/Cl)		
	Max photo Draft – 10x15cm/4x6" – Approx. 2	7	
7	sec per photo (W/Border)	5 units	30 days
	> Photo Default – 10x15cm/4x6" – Approx. 69		2 2 3 3 3 7 2
	sce per photo (W/Border)		
	• Copying		
	Max. Black Draft Text - Memo (A4) - Approx.	5	
	sec (Draft)		
	Max. Colour Draft Text - Memo (A4) - Approx		
	10 sec (Draft)		
	Copy Mode: Standard copy mode		
	Maximum Copies From Standalone: 20 sheets		
	(fixed)		
	Scanning		
	Scanner Type: Flatbed colour image scanner		
	Sensor Type: CIS Ontical Pacalution: 600 v 1200 dpi		
	 Optical Resolution: 600 x 1200 dpi Maximum Scan Area: 216 x 297mm (8.5 x 		
	11.7)		
	Scanner Bit Depth		
L	·	_1	I.

Bidding Documents	Based on Revised IRR of RA 9184, Fourth Edition, December 2010)
Didding Document	

Bidding Dod	uments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	-	
	 Colour: 48-bit internal, 24-bit external Grayscale: 16-bit internal, 8-bit external Black & White: 16-bit internal, 1-bit external Scan Speed Monochrome 300 dpi: 2.4 msec/line 		
	Colour 300 dpi: 9.5 msec/lime		
	Monochrome 600 dpi: 7.2 msec/line		
	Colour 600 dpi: 14.3 msec/line		
	PRINTER (ICT)		
	 Print Speed Black (Normal): Up to 33 ppm 		
	• Print quality Black (Best): Up to 1200 x 1200 dpi		
	• Duty Cycle (monthly, A4): Up to 50,000 pages		
	Print Technology: Laser		
	Processor Speed: 800 Mhz		
	Display: 2-line LCD (text and graphics)		
	Connectivity, standard: 1 Hi-Speed USB 2.0		
	1 Ethernet 10/100/1000T	1	
	network		
	 Network Ready: Standard (built-in Gigabit 		
	Ethernet)		
	• Minimum system requirements: Windows 8,		
	Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), 1 Chr. 22-bit (x86) or 64-bit (x64)		
	bit/64-bit): 1 Ghz 32-bit (x86) or 64-bit (x64) processor, 1 GB RAM (32-bit) or 2 GB RAM (64-		
	bit), 400 MB free hard disk space, CD/DVD ROM or		
	Internet, USB or Network port		
	Windows XP (32-bit) SP2: Pentium® 233 MHz		
8	processor, 512 MB RAM, 400 MB free hard disk	2 units	30 days
	space, CD/DVD-ROM or Internet, USB or Netwrok		·
	port		
	• MAC OS X v 10.5, v 10.6, 10.7		
	 PowerPC G4, G5, or Intel® Core™ Processor 		
	• 500 MB Hard Disk		
	CD-ROM/DVD-ROM or Internet		
	USB or Network		
	Paper Handling input, standard: 50-sheet Paper Handling input, standard: 50-sheet Paper Handling input, standard: 50-sheet		
	 multipurpose tray 1, 250-sheet input tray 2 Paper handling output, standard: 150-sheet 		
	Paper handling output, standard: 150-sheet output bin		
	 Maximum output capacity (sheets): Up to 150 		
	sheets		
	 Duplex printing: Manual (driver support 		
	provided)		
	• Media sizes supported: A4, A5, A6, B5(JIS)		
	Media sizes (custom): Media sizes (custom):		
	Multipurpose tray: 76 x 127 to 216 x 356mm		
	Tray 2 and optional 500-sheet tray 3: 105 x 148 to 216 x 356 mm		
	Media types: Paper (plain, Green mode, light,		
	Producty post 1 upor (plain), dreen mode, light,	I	<u> </u>

Didding Doc	uments	(Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		
		heavy, bond, color, letterhead, preprinted,		
		prepunched, recycled, rough), envelopes, labels		
	•	Supported media weight: Tray 1: 60 to 163 g/m ²		
		(straight through paper path for special media)		
		Tray 2: 500 sheet		
		Tray 3: 60 to 120 g/m ²		
	PRINT	TER (GENERAL ENGINEERING)		
	•	Print Method: On-demand ink jet		
	•	Nozzle Configuration: 180 nozzles Black, 59		
		nozzles each colour (Cyan, Magenta, Yellow)		
	•	Print Direction: Bi-directional printing, Uni-		
		directional printing		
	•	Maximum Resolution: 5760 x 1440 dpi (with		
		Variable-Sized Droplet Technology)		
	•	Minimum Ink Droplet Volume: 3pl		
	•	Print Speed		
		Max Black Draft Text - Memo (A4): Approx.		
		33 ppm / 15 ppm (Bk/Cl)		
		► ISO 24734, A4: Approx. 9.0 ipm / 4.5 ipm		
		(Bk/Cl))		
		► Max Photo Draft - 10x15cm/4x6": Approx. 27		
		sec per photo (W/Border)		
		Photo Default - 10x15cm/4x6": Approx. 69		
		sec per photo (W/Border)		
		Double-sided Printing: Yes (Manual)		
	•	Copying		
		Copy Speed		
		Max. Black Draft Text - Memo (A4): Approx. 5		
9		sec (Draft)	1 unit	30 days
		Max. Colour Draft Text - Memo (A4): Approx.		-
		10 sec (Draft)		
		Copy Mode: Standard copy mode		
		Maximum Copies From Standalone: 20 sheets		
		(fixed)		
	•	Scanning		
		Scanner Type: Flatbed colour image scanner		
		> Sensor Type: CIS		
		> Optical Resolution: 600 x 1200 dpi		
		Maximum Scan Area: 216 x 297mm (8.5 x		
		11.7")		
		Scanner Bit Depth		
		Colour: 48-bit internal, 24-bit external		
		→ Grayscale: 16-bit internal, 8-bit external		
		Black & White: 16-bit internal, 1-bit		
		external		
		Scan Speed		
		→ Monochrome 300 dpi: 2.4 msec/line		
		→ Colour 300 dpi: 9.5 msec/line		
		→ Monochrome 600 dpi: 7.2 msec/line		
		→ Colour 600 dpi: 14.3 msec/line		
	•	Paper Handling		
		Paper Feed Method: Friction feed		

Didding Do	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)		Т
	Number of Paper Trays: 1		
	Paper Hold Capacity		
	Input Capacity: 100 sheets, A4 Plain paper		
	(75g/m2)		
	20 sheets, Premium Glossy Photo Paper		
	Output Capacity: 30 sheets, A4 Plain paper		
	20 sheets, Premium Glossy Photo Paper		
	Connectivity		
	l =		
	Standard: USB 2.0 Hi-Speed		
	Printer Software		
	Operating System Compatibility: Windows		
	XP/XP Professional x64 Edition/Vista/7		
	Mac OS X 10.5.8, 10.6.x, 10.7.x		
	LAPTOP (VPRDE)		
	an for (vinal)		
	Operating System: Windows 8		
	 Processor: Intel®Core™i5 Processor 3317UM (1.7 		
	Ghz, 3MB L3 Cache)		
	100 Dt 1 40 0 0 0 0 0 1 1 0 0 0 1 1 1 0 1 0 0		
	_ = = = = = = = = = = = = = = = = = = =		
	Display (1,366 x 768), Anti-Reflect		
	Graphic Processor: Table		
	System Memory: 4GB DDR3 System Memory at		
	1,600 Mhz (on BD 4GB)		
	Memory Slot: 1 DIMM Slots		
	 HDD Storage: 500 GB S-ATA All Slim Hard drive 		
	(5,400 RPM) with Express Cache 2		
	Multimedia:		
	➤ Sound: HD Audio		
	Sound Effect: Mic Noise Suppression		
	SoundAlive™		
	> Speaker: 4 watts Stereo Speaker (2 watts x 2)		
	Integrated Camera: 1.3 megapixel HD		
10	Webcam	1 unit	30 days
	Wired Ethernet LAN: 10/100/1,000 Gigabit Ethernet LAN		
	Ethernet LAN		
	Wireless LAN: Intel®Centrino®Advanced-N 6235 3 202311	,	
	2 x 2 802.11 abg/n (up to 300Mb)		
	Bluetooth: Bluetooth 4.0		
	• Port		
	Headphone Out: Headphone-out/Mic-Combo		
	Mic-in: Headphone-out/Mic-Combo		
	➤ USB: 1 USB 3.0, 2 USB 2.0		
	Mulkti Card Slot: 4-in-1 (SD, SDHC, SDXC,		
	MMC)		
	Keyboard: 81 Key		
	80 Key		
	Touch Pad, Touch Screen: Touch Pad (Scroll		
	Scope, Flat Type, Gesture UI)		
	AC Adapter: 40 watts		
	Standard Battery: 4 Cell (45 Wh)		
	Standard DVD: OS DVD		
	Universal Printer/ Scanner Driver		
<u> </u>	Universal Finitely Scanner Driver	1	L

Didding Do	cuments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)]	
	1 X SD card reader • Audio: Built-in Speakers And Microphone • Battery: 2 Cells 37 Whrs Polymer Battery • Power Adapter ▶ Output: 19 V DC, 3.42 A, 65 W ▶ Input: 100-240 V AC, 50/60 Hz universal • Dimensions: 38.2 x 25.6 x 2.58 cm (WxDxH) • Weight: 2.3 kg (with Polymer Battery) • Security: Kensington lock BIOS Booting User Password Protection HDD User Password Protection and		
	Security		
13	 Color: White/Silver Quad Core Ultrathin Operating System: Windows 8 Pro Screen Size: 13.3 /14" HD LED Display (1366 x 768), Anti Reflective Processor: Quad-Core Processor (up to 1.4 Ghz) Graphics: AMD radeon HD Graphics Memory: 4GB DDR3L System Memory at 1066 MHz (on BD 4GB) Storage: 500 GB Solid-state Drive Connectivity: 802.11 bg/n 1 x 1 Bluetooth v4.0 Gigabit Ethernet (10/100/1000) Camera: 720p HD Web Camera Battery: 2-cell Battery Power Consumption: 220V, 40W With Laptop Bag, Mouse, Mouse Pad, Laptop Screen Protector, Cooling Pad and 1TB External Drive 	1 unit	30 days
14	 16-PORT FAST ETHERNET UNMANAGED DESKTOP SWITCH Inexpensive Fast Ethernet solution for SOHO/SMB Auto MDI/MDIX crossover for all ports Store-and-forward switching scheme Full/half-duplex for Ethernet/Fast Ethernet speeds IEEE 802.3x Flow Control Plug-and-play installation Switching Fabric: 3.2 Gpbs Standards: IEEE 802.3 10BASE-T Ethernet (twistedpair copper) IEEE 802.3u 100 BASE-TX Fast Ethernet (twisted-pair copper) ANSI/IEEE 802.3 NWay Auto-Negotiation IEEE 802.3 x Flow Control IEEE 802.3az EEE function 	5 units	30 days

- Protocol: CSMA/CD
- Data Transfer Rates
 - Ethernet: 100 Mbps (half duplex)

20 Mbps (full duplex)

- Fast Ethernet: 100 Mbps (half duplex) 200 Mbps (full duplex)
- Number of ports: 16 10/100 Mbps fast Ethernet ports
- Topology: Star
- Network Cables
 - ➤ 10BASE-T:
 - → UTP CAT 3/4/5/5e (100 m max.)
 - → EIA/TIA-586 100-ohm STP (100 m max.)
 - ➤ 100BASE-TX
 - → UTP CAT 5/5e (100 m max.)
 - → EIA/TIA-568 100-ohm STP (100 m max.)
- Media Interface Exchange: Auto MDI/MDIX adjustment for all ports
- LED Indicators
 - ➤ Per port: Link/Activity
 - > Per device: Power
- Transmission Method: Store-and-forward
- MAC Address Table: 8K entries per device
- MAC Address Learning: Automatic update
- Packet Filtering /Forwarding Rates (half duplex)
 - Ethernet: 14,880 pps per port
 - Fast Ethernet: 148,800 pps per port
- **RAM Buffer:** 256 Bytes (2M bits)
- **Power Input:** 100~240 V AC 50/60 Hz internal universal power supply
- Power Consumption
 - Power On (Standby): DC input: 0.61 Watts AC input: 1.19 Watts
 - Max.: DC input: 1.55 Watts AC input: 2.89 Watts
- Heat Dissipation
 - ➤ Power On (Standby): AC input: 4.06 BTU/h
 - Maximum: AC input: 9.86 BTU/h
- **MTBF:** 2.266.559 hours
- **Operating Temp.:**0° to 40°C (32° to 104°F)
- **Storage Temp.:** -10 ° to 70 °C (14 ° to 158 °F)
- **Operating Humidity:** 10% to 90% RH noncondensing
- Storage Humidity: 5% to 90% RH noncondensing
- **Dimensions (W x D x H):** 280 x 125.8 x 44 mm (11.0 x 5.0 x 1.7 inches)

	• Certificationsf ➤ FCC Class A ➤ ICES-003 Class A ➤ CE Class A ➤ C-Tick Class A ➤ VCCI Class A ➤ cUL ➤ LVD		
	 Aspect Ratio: 16:10 (Native) 4:3, 16:9 Brightness (ANSI Lumens): 1000 ANSI lumens Contrast Ratio: 10000:1 Display Type: DLP Resolution (Native/Max): WXGA (1280 x 800) HD (1920 X 1080) Video Compatibility: PAL, SECAM, NTSC, HDTV (480i, 480p, 576i, 576p, 720p, 1080i) Projection Lens: F=1.5 Number of colors: 1.07 Billion Colors Dimension (WxHxD): 8.7 in. x 1.7 in. x 6.7 in. (22.1 cm x 4.32 cm x 17.02 cm) Weight: 2.6 Ibs (1.18 kg) Connectivity 		
15	 Inputs: 1 x HDMI 1 x VGA D-Sub 15pin 1 x Composite 1 x Stereo Mini Jack 1 x USB Type A Outputs: 1 x Stereo Mini Jack Audio: 1 x 3W Mono Speaker Control: 1 x USB Type B Power Supply: 100~220V / 50-60 Hz Projection Lens Lamp Type: Laser/LED Lamp Life: 20000 hrs (Normal)	1 unit	30 days
16	PROJECTOR (VPRDE) • Native Aspect Ratio: 4x3	1 unit	30 days

Bidding Doci	uments (Based on Revised IRR of RA 9184, Fourth Edition, December 2010)	1	
	 Technology: DLP 		
	 Resolution: SVGA(800x600) 		
	 Lumens (Eco/High): 2800/3000 		
	• Contrast: 15000		
	• 3D: Supports 3D content from Blu-ray, cable		
	boxes, dish services and more (over HDMI) at		
	144Hz and PC-based 3D content at 120Hz. DLP		
	Link 3D glasses required.		
	 Closed Captioning: Yes 		
	G I OVA (4 OVA)		
	• Audible Noise (Eco/High, dBA): 29/30		
	• Keystone: ± 40°		
	• Lamp: SP-LAMP-086		
	 Lamp Hours (Eco/High): 10000/5000 		
	 Connections: HDMI 1.4, VGA x 2, Composite video, 		
	S-Video, 3.5 mm stereo in x 2, 3.5mm stereo out,		
	RS232C		
	Image Offset: 15		
	 Lens Shift: Horz (min/max): None 		
	 Lens Shift: Vert (min/max): None 		
	• Throw Ratio: 2.2~1.9		
	Weight(lbs/kg): 5.4/2.5		
	• Product Dimensions HxWxD: 8.7in x 11.5in x 4.7in		
	(220mm x 292mm x 121mm)		
	• Shipping Weight(lbs/kg): 7.1/3.2		
	5		
	PROJECTOR (ON-THE-JOB TRAINING OFFICE)		
	• MANACA (1200 v 000)		
	• WXVGA (1280 x 800)		
	• UXGA (1,600 x 1,200),		
	• 1080p (1,920 x 1,080)		
	• 16:10 (Native), 4:3, 16:9		
	 Contrast Ratio at 4000:1 		
17	• 1.07 Billion Colors	1 unit	30 days
1,	• 500 ANSI Lumens (Standard)	1 unit	50 days
	• 350 ANSI Lumens (ECO)		
	USB and HDMI port LED Life 20 202 H		
	• LED Life 20,000 Hours		
	 Remote 		
j	 One Internal Speaker with 2 watts Output 		
1	one meernar speaker with 2 water output		· · · · · · · · · · · · · · · · · · ·
	• 2.73 lbs (1.24 kg)		
	*		
	• 2.73 lbs (1.24 kg)		
	2.73 lbs (1.24 kg) PROJECTOR (OSAS and ROSARIO CAMPUS)		
	 2.73 lbs (1.24 kg) PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 	9 unite	30 days
18	 2.73 lbs (1.24 kg) PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 Technology: DLP 	9 units	30 days
	 2.73 lbs (1.24 kg) PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 Technology: DLP Resolution: SVGA(800x600) 	9 units	30 days
	 2.73 lbs (1.24 kg) PROJECTOR (OSAS and ROSARIO CAMPUS) Native Aspect Ratio: 4x3 Technology: DLP 	9 units	30 days

2 22 3 20	3D: Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz.		
	DLP Link 3D glasses required.		
	Closed Captioning: Yes		
	• Speakers: 2W (1 x 2W)		
	 Audible Noise (Eco/High, dBA): 30/32 		
	• Keystone: ± 40°		
	• Lamp Hours (Eco/High): 5000/3500		
	• Connections: HDMI 1.4, VGA x 2, USB-A (for		
	USB thumb drive or wireless network		
	adapter), USB Mini-B (for display over USB &		
	internal memory file mgmt), Composite Video,		
	S-Video, 3.5 mm stereo in x 2, RS232, USB-B (control & firmware), VGA monitor out,		
	3.5mm audio out		
	Image Offset: 15		
	• Throw Ratio: 2.2~1.9		
	Weight(lbs/kg): 7/3.2		
	 Product Dimensions HxWxD: 8.7in x 11.5in x 		
	4.3in (220mm x 292mm x 108mm)		
	Shipping Weight(lbs/kg): 8.1/3.7		
	Shipping Dimensions HxWxD: 12in x 14.25in x		
	7.75in (305mm x 362mm x 197mm)		
	Product Warranty: 1 Year		
	Lamp Warranty: 6 months		
	PROJECTOR (CICS)		
	Native Aspect Ratio: 4:3		
	Technology: DLP		
	• Resolution: SVGA (800x600)		
	• Lumens (Eco/High): 3200/3500		
	• Contrast: 15000		
19	3D: Supports 3D content form Blu-ray, clable have dish consider and more (aver HDM) at	2 units	30 days
	boxes, dish services and more (over HDMI) at 144Hz and PC-based 3D content at 120Hz.		
	DLP Link 3D glasses required		
	Closed Captioning: Yes		
	• Speakers: 2W (1 x 2W)		
	Audible Noise (Eco/High dBA): 30/32		
	• Keystone ±40°		
	• Lamp Hours: 5000/3500		
20	WIRELESS PROJECTOR SERVER (ICT)	1 unit	30 days
	Wireless 802.11 b/g/n and 802.3ab gigabit LAN		j
	, , , , , , , , , , , , , , , , , , , ,		

 Features Quarter View, Direct Show, and a WPS Button Multiple video format support (codec installation needed) Infrared remote control included Simultaneous content projection and web surfing Supports Windows XP/Vista/7 and Mac OS (10.4 & 10.5 only) 		
Hard Drive (ICT) • 2TB	2 units	30 days

Omnibus Sworn Statement

REPUBLIC OF THE PHILIPPINES)
CITY/MUNICIPALITY OF) S.S

AFFIDAVIT

I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:

1. Select one, delete the other:

If a sole proprietorship: I am the sole proprietor of [Name of Bidder] with office address at [address of Bidder];

If a partnership, corporation, cooperative, or joint venture: I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. Select one, delete the other:

If a sole proprietorship: As the owner and sole proprietor of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to represent it in the bidding for [Name of the Project] of the [Name of the Procuring Entity];

If a partnership, corporation, cooperative, or joint venture: I am granted full power and authority to do, execute and perform any and all acts necessary and/or to represent the [Name of Bidder] in the bidding as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate issued by the corporation or the members of the joint venture)];

- 3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board;
- 4. Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- 5. *[Name of Bidder]* is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;

6. *Select one, delete the rest:*

If a sole proprietorship: I am not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

If a partnership or cooperative: None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

If a corporation or joint venture: None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards;
- 8. [Name of Bidder] did not give or pay, directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity; and
- 9. [Name of Bidder] is aware of and has undertaken the following responsibilities as a Bidder:
 - a) Carefully examine all of the Bidding Documents;
 - b) Acknowledge all conditions, local or otherwise, affecting the implementation of the Contract;
 - c) Made an estimate of the facilities available and needed for the contract to be bid, if any; and
 - d) Inquire or secure Supplemental/Bid Bulletin(s) issued for the [Name of the Project].

IN WITNESS WHEREOF, I have hereunto s	set my hand this day of, 20 at
Philippines.	
	Bidder's Representative/Authorized Signatory

[JURAT]

REQUEST FOR CLARIFICATION

							_
r	tσ	.et	FΙ	n	tΔ	12	n
	10	.61		()	10	ы	

ATTY. EDGARD E. VALDEZ

Name of the Bidder

BAC Chairman
Batangas State University
Rizal Avenue, Batangas City
Telephone No.: 980-0385 local 1811

Dear Sir:
In relation to the Sectionof Pageof the Bidding Documents for (<u>Name of the Project</u>), to wit:
<u>" (Quote unclear provision)</u> "
We would appreciate it if you could provide further explanation or clarification on the above. Thank you very much.
Very truly yours,
Name of Representative of the Bidder

Bill of Quantities

Name of Bidder	. Invitation to Bid	Number	Page of	
Traine of Brader	IIIVItation to Dia	runnber	1 ugc . 01	

1	2	3	4	5	6	7	8	9	10
Item	Description	Country of origin	Quantity	Unit price EXW per item	Cost of local labor, raw material, and component ²	Total price EXW per item (cols. 4 x 5)	Unit prices per item final destination and unit price of other incidental services	Sales and other taxes payable per item if Contract is awarded	Total Price delivered Final Destination (col 8 + 9) x 4